

CHEMICALS & LUBRICANTS (Cont.)

NOTE: All dimensions in inches

Non-Aerosol Silicone Lubricant

- Prevents sticking without transferring to end product.
- Effective from -58° F to 450° F.
- Use on slides, guide-rails, knives, saws, slicers, grinders, dough mixers, conveyors, food racks and ovens.
- USDA H-1 rated.
- NSF listed.
- Each can comes with a trigger.



Non-Food Grade
14 Fl. Oz.

Order Number
85-1139

Food Grade
14 Fl. Oz.

Order Number
85-1137

Silicone Lubricant

- Ideal for food service equipment.
- FDA approved spray is non-flammable.



16 Oz.

Order Number
32-1686

Must ship by ground only

High Temp Anti-Seize Lubricant

- Lubricates bolts, bushings, pipe fittings, gaskets, nuts, screws, etc.
- Prevents seizing caused by high temperatures, heavy loads, corrosion and vibration.
- Works in temperature range from -95° F to 1800° F.



1 Fl. Oz.

Order Number
32-1712

Thread Sealant — Loctite 567

High Temp Thread Sealant



.20 Fl. Oz.

Order Number
32-1674

Thread Sealant — Loctite 243

Medium Strength,
Oil Resistant



.5 ml.

Order Number
32-1869

Thread Locker — Loctite 242



Blue
0.8 Fl. Oz.

Order Number
32-1738

(PTFE) Heavy Duty Thread Sealer

- Non-toxic.
- Non-separating.



1/4 Pint

Order Number
85-1136

“Gripp” Pipe Joint & Gasket Seal

- Lead-free.
- All purpose.
- Leak proof, non-hardening.



1/4 Pint

Order Number
85-1101

7 HARDWARE, TOOLS & SUPPLIES GENERAL USE

CHEMICALS & LUBRICANTS (Cont.)

NOTE: All dimensions in inches

High Heat Paint

- Spray on high heat spray paint withstands temperatures to 600° F for long periods and 1000° F intermittent periods.
- Dries in approximately 10 minutes.
- Use on boilers, furnaces, radiators, heaters, gas grills, ranges and ovens.



12 Oz. Aluminum
(Case of 12)

Order Number
85-1104



12 Oz. Black
(Case of 12)

Order Number
85-1105

Must ship by ground only

Steel Reinforced Epoxy Putty

- Fast acting, single stick, steel-reinforced epoxy putty, makes steel hard repairs in 20 minutes.
- Seals, mends, bonds, repairs almost anything — even under water.
- Two-part epoxy compound mixes quickly and easily and adheres to metals, masonry, wood, glass, ceramics and most plastics.
- Withstands temperatures to 300° F.
- Compression strength 18,000 PSI.
- Tensile strength 6,000 PSI.
- Electrically non-conductive.
- When cured, may be drilled, sanded, filed and painted.



4 Oz.

Order Number
85-1107

Food Grade Silicone Sealants

Color	Maximum Temperature	3 Oz. Tube Order #	10.3 Oz. Cartridge Order #
White	400° F	85-1091	85-1115
Clear	400° F	85-1094	85-1116
Aluminum	400° F	—	85-1095
Red	500° F	85-1092	85-1117



Stainless Steel Polish

- Removes greasy films, water mark and fingerprints.
- Repels water.

Description	Order Number
10 OZ. SPRAY	32-1704
QUART CAN	32-1703
GALLON CAN	32-1702



Order Number
32-1074



Order Number
32-1073



Order Number
32-1072

Sherlock 5-Second Leak Detector

- For below and above freezing temperatures detects leaks in gas lines, tanks, cylinders, valves or anything that can be tested with gas or air pressure.
- Plastic dispenser with dauber cap.



8 Oz.

Order Number
85-1097