



911/911P

Single & Double
Gas Deck Oven



OPTIONS AND ACCESSORIES

(AT ADDITIONAL CHARGE)

- **Flexible gas hose with quick disconnect and restraining device**
 - 36" (914 mm)
 - 48" (1219mm)
- Black legs with casters
- Stainless steel crown angle trim
- Vent kit
- 911 - QHT Rokite shelves, 1" (25.4mm) thick (pizza type shelf)
- Steam jets
- 911 - FDTH 300°F (149°C) to 650°F (343°C) Temperature thermostat

OPTIONS AND ACCESSORIES

(AT NO ADDITIONAL CHARGE)

- Centigrade dial, 100°C to 300°C

Project _____

Item No. _____

Quantity _____

Ovens consist of basic sections and are a complete and separate unit capable of operating alone or in combination. All data is shown per oven section, unless otherwise indicated.

Refer to operator manual specification chart for listed model names.

EXTERIOR CONSTRUCTION

- Full angle iron frame
- Stainless steel front, top, sides and back
- Counterbalanced doors with concealed hinges
- Heavy chrome plated tubular steel door handle
- 27-1/2" (699mm) stainless steel legs (for single units)
- 19" (483mm) stainless steel legs (for double units)
- 7" (179mm) stainless steel legs (for triple units)
- Burner doors open easily for ignition, cleaning or adjustment, without removal of any fastenings
- Vitreous fiber insulation at top, back, sides, bottom and doors

INTERIOR CONSTRUCTION

- 33" x 22" x 7" (838mm x 559mm X 178mm) oven compartment interior
- Aluminized steel baking compartment liner
- Aluminized steel combustion chamber
- Deck supported by an angle iron frame
- 12 gauge (3.02mm) press-formed, reinforced and flanged aluminized steel deck

OPERATION

- Free-floating, easily removable duplex-tube burner
- Removable fixed orifices on main and pilot burner
- Main gas valve, temperature control valve and safety pilot valve fully within section body and are accessible through a covered and ventilated compartment in front
- Air mixers with adjustable air shutters and locking device
- 911 - Liquid pressure thermostat with temperature range of 200°F (93°C) to 500°F (288°C)
- 911P - Liquid pressure thermostat with temperature range of 300°F (149°C) to 650°F (343°C)

STANDARD FEATURES

- 911 - Fahrenheit dial 200° to 500°
- 911P - Fahrenheit dial 300° to 650°
- 911 - Steel oven deck
- 911P - QHT (Quick Heat Technology) Rokite deck
- Gas connector for double stack ovens only
- Two year parts and one year labor warranty
- Five year limited oven door warranty*

* For all international markets, contact your local distributor.

NOTE: The company reserves the right to make substitutions of components without prior notice




www.blodgett.com


42 Allen Martin Drive, Essex Junction, VT 05452
Phone: (802) 658-6600 | Fax: (802) 864-0183



911/911P DECK OVEN



APPROVAL/STAMP



SHORT FORM SPECIFICATIONS Provide Blodgett single deck oven, model 911. Construction shall be stainless steel on front, top, back and sides, and shall be fully insulated on all sides. Oven shall be supported by formed adjustable legs. Door(s) shall be counterbalanced (no springs) with concealed hinges and chrome plated tubular steel handles. Separate burner door provided for ignition, cleaning and adjustment. Each baking compartment shall be 33" W x 7" H x 22" D and shall be lined with aluminized steel. Deck shall be 11 gauge press-formed, reinforced and flanged steel (911) or QHT Rokite (911-P). Unit shall be gas heated by a free-floating, easily removable, duplex-type burner controlled by a liquid pressure thermostat with range of 200°F to 500°F (911) or 300°F to 650°F (911P). Each compartment provided with flue vent. Provide with two year oven parts and one year labor warranty. Provide with options and accessories as indicated

DIMENSIONS

Floor space 51" (1495mm) wide x 30" (762mm) deep
Cooking Compartment (per section)
 Size 33" (838mm) W x 7" (178mm) H x 22" (559mm) D
 Area 5.04 sq. ft. (0.47m²)

SECTION DETAILS

	Single	Double	Triple
Number of section	1	2	3
Number of controls	1	2	3
Number of compartments	1	2	3

PRODUCT CLEARANCE

From combustible and non-combustible construction
 6" (152 mm)

PAN CAPACITIES

	Single	Double	Triple
10" (254mm) pie tins:	6	12	18
18" x 26" (457mm x 660mm) bun pans	1	2	3
9-1/2" x 5" (241mm x 127mm) bread pans	12	24	36
9" x 7" (228mm x 178mm) roll pans	9	18	27
19" x 4" (483mm x 102mm) pullman pans	8	16	24
13" x 16-1/2" (330mm x 419mm) cup tins	2	4	6
20" x 28" (508mm x 711mm) roast pans	1	2	3
No. 200 pans (324mm x 527mm)	2	4	6
#1 bean pot	15	30	45
#2 bean pot	8	16	24
#3 bean pot	6	12	18

GAS SUPPLY (per section)

3/4" NPT
Inlet Pressure
 Natural Gas 7.0" W.C. min. - 10.5" W.C. max.
 Propane 11.0" W.C. min. - 13.0" W.C. max.
Manifold Pressure
 Natural Gas 5" W.C.
 Propane 10" W.C.

MAXIMUM INPUT

911 20,000 BTU/hr per oven section
911P 27,000 BTU/hr per oven section

MINIMUM ENTRY CLEARANCE

Uncrated 23-1/4" (591mm)
Crated 27" (686mm)

SHIPPING INFORMATION

Approx. Weight	911	911P
Single	495 lbs. (225kg)	585 lbs. (265kg)
Double	905 lbs. (410kg)	1130 lbs. (512kg)
Triple	1285 lbs. (583kg)	1640 lbs. (744kg)

Crate Size

56" (1422mm) x 46.5" (1181mm) x 27" (686mm)
 (1 crate per section)