



Stainless steel cabinet construction

Stainless steel interior and exterior (aglyanized steel back & bottom).



Temperature range between

Air guard on rear wall ensures proper air circulation and cooling.



Hydrocarbon refrigerants (R-290)

Increases energy HFC refrigerants. It is safer for the environment and does not cause ozone depletion.



Visual and audible door

Alarm sounds when doors are not completely closed to protect against food spoilage





Exterior Dimensions (inches/mm)

L D H
72 13/32" 37 21/64" 44 11/64"
1839 mm 948 mm 1122 mm

Weight (lbs/kg)

Net Weight 311 lbs 141 kg Ship Weight 390 lbs 177 kg

Cabinet construction

- Oyclopentane Insulation Contains no hydro-fluorocarbons (HFCs) and is environmentally friendly.
- Fans force cold air into this enclosed area keeping stored food items consistently cold
- Insulated pan cover with a stainless steel divider which prevents food spillage into the storage area beneath
- Side rail cutting board bracket with 9 ½" deep, 1/2" thick cutting board included
- Epoxy coated wire shelves with adjustable shelving height.
- Four 4" Diameter swivel casters with front brakes standard.


Refrigeration

- Self-contained system, rear mounted compressor.
- Electrodeposition coated evaporator increases performance by maintaining the heat transfer rates over the life of the evaporator and reducing potential corrosion.
- Innovative hot gas frame heating system reduces condensation and increases energy.







Front view



Side view



Top view



Doors

- Self-closing doors (doors close at 90° or less)
- Durable door gasket with easy replacement.
- Lifetime guaranteed heavy duty all metal door handles. (Ni-Cr Plated)
- Door designed to open easily.

Design & Features

- Self-diagnostic digital temperature control & monitor system.
- Digital display allows for easy monitoring.
- Digital controls include automatic evaporator fan motor delay
- Rounded corner design gives a stylish appearance and reduces chances of injury.

Optional Features & Accessories

- 2.5" diameter casters available.
- · Additional shelves are available.

Doors 3 Capacity 20.2 Cu.Ft. **Shelves** Refrigerant R-290 Temperature 33°F ~ 39°F Range Sliding Easy Condensing Unit Maintenance 9.8 ft long (3m) flexible three Connection wire cord with modeled plug HP 1/4 115V/60Hz Voltage Amps 5.4 NEMA 5-15 NEMA Config.



- This product may exprose you to chemicals including Diisononyl Phthalate(DINP), which is known to the State of California to cause cancer. For more information go to www.P65War nings.ca.gov.
- Ce produit peut vous exposer á des agents chimiques incluant le Diisononyl
 Phthalate(DINP), reconnu par l'Esat de Californie comme causant le cancer, Pour de plus
 amples renseignements, consulter le site www.P65Wamings.ca.gov.





orders@blueairfse.com



1-886-677-8500



223 W. Rosecrans Ave., CA 90248 9 W. Sh T: 310-808-0102 T: 908-