



**FRONT LOAD**



**DOUBLE SECTION**




**SIDE LOAD**

**Options:**

- /011 Caster Brakes
- /CC Card Clip
- /009 Pan Stop Aluminum
- /010 Pan Stop Stainless Steel
- /PG Pan Stop Gravity

**Lifter Options:**



Lifters



Ball Locator



"C" Lift

Item No. \_\_\_\_\_

Quantity \_\_\_\_\_

Job Name \_\_\_\_\_

Spec No. \_\_\_\_\_

## BUN PAN RACKS

### OVEN RACKS

ALUMINUM OR STAINLESS CONSTRUCTION

ALUMINUM		STAINLESS		Spacing/ Capacity	H	W	D
Model	Wt.	Model	Wt.				
<b>SINGLE SECTION Front Loading</b>							
400A-OR-	47	400S-OR-	77	2" / 30 Pans	69¾"	20½"	26"
401A-OR-	38	401S-OR-	68	3" / 20 Pans	69¾"	20½"	26"
402A-OR-	34	402S-OR-	64	4" / 15 Pans	69¾"	20½"	26"
403A-OR-	31	403S-OR-	61	5" / 12 Pans	69¾"	20½"	26"
404A-OR-	29	404S-OR-	59	6" / 10 Pans	69¾"	20½"	26"
<b>SINGLE SECTION Side Loading</b>							
410A-OR-	47	410S-OR-	72	2" / 30 Pans	69¾"	28½"	18"
411A-OR-	38	411S-OR-	66	3" / 20 Pans	69¾"	28½"	18"
412A-OR-	34	412S-OR-	63	4" / 15 Pans	69¾"	28½"	18"
413A-OR-	31	413S-OR-	60	5" / 12 Pans	69¾"	28½"	18"
414A-OR-	29	414S-OR-	54	6" / 10 Pans	69¾"	28½"	18"
<b>DOUBLE SECTION Side Loading</b>							
410A-DOR-	77	410S-DOR-	158	2" / 60 Pans	69¾"	29"	36"
411A-DOR-	67	411S-DOR-	122	3" / 40 Pans	69¾"	29"	36"
412A-DOR-	31	412S-DOR-	104	4" / 30 Pans	69¾"	29"	36"
413A-DOR-	45	413S-DOR-	93	5" / 24 Pans	69¾"	29"	36"
414A-DOR-	39	414S-DOR-	86	6" / 20 Pans	69¾"	29"	36"

Listed are the model numbers for base oven racks excluding any lifting devices, pan stops, referencing pins, bottom brackets and or roller devices. Please call the factory for your add-on configuration.

**APPLICATIONS:** Channel oven racks are equipped with 4" phenolic extra high temperature wheels. 475°F continuous use, 575°F intermittent use, and down to -45°F for blast chillers. Fully assembled and ready for use.

**CONSTRUCTION: Aluminum:** Heavy duty, high tensile extruded aluminum. Type 6063-T5 alloy. Lifetime guarantee against rust and corrosion. **Stainless:** 18 Gauge, 304 Series stainless steel.

**TRAY SLIDES:** Angle pan slides will accommodate 18" X 26" bun pans or 18" X 26" perforated trays.

**CASTERS:**

4" diameter full swivel design. Non marking phenolic wheel. Casters are securely bolted to frame to facilitate replacements.



Notes

55 Channel Drive • Port Washington, NY 11050-2216

8891 NW 102nd Street • Medley, FL 33178

Tel: 516-944-6271 • Fax: 516-944-0625

Toll Free: 866-712-7283

www.channelmfg.com • Email: sales@channelmfg.com