

**LIFETIME
TOUGH**

**CORRECTIONS
APPROVED**



DR2036-2

DR2036-3



DR2036-4

Item No. _____

Quantity _____

Job Name _____

Spec No. _____

DUNNAGE SHELVING

LIFETIME DUNNAGE SHELVING

ALUMINUM CONSTRUCTION

Custom Sizes Available

Two Shelf Style – 52½" Spacing

| Model | H | W | D | Weight |
|----------|-----|-----|-----|--------|
| DR2036-2 | 64" | 36" | 20" | 39 |
| DR2436-2 | 64" | 36" | 24" | 53 |
| DR2042-2 | 64" | 42" | 20" | 46 |
| DR2442-2 | 64" | 42" | 24" | 56 |
| DR2048-2 | 64" | 48" | 20" | 48 |
| DR2448-2 | 64" | 48" | 24" | 64 |
| DR2054-2 | 64" | 54" | 20" | 54 |
| DR2454-2 | 64" | 54" | 24" | 73 |
| DR2060-2 | 64" | 60" | 20" | 56 |
| DR2460-2 | 64" | 60" | 24" | 75 |
| DR2072-2 | 64" | 72" | 20" | 64 |
| DR2472-2 | 64" | 72" | 24" | 86 |

Three Shelf Style – 26" Spacing

| Model | H | W | D | Weight |
|----------|-----|-----|-----|--------|
| DR2036-3 | 64" | 36" | 20" | 34 |
| DR2436-3 | 64" | 36" | 24" | 43 |
| DR2042-3 | 64" | 42" | 20" | 37 |
| DR2442-3 | 64" | 42" | 24" | 55 |
| DR2048-3 | 64" | 48" | 20" | 40 |
| DR2448-3 | 64" | 48" | 24" | 57 |
| DR2054-3 | 64" | 54" | 20" | 44 |
| DR2454-3 | 64" | 54" | 24" | 57 |
| DR2060-3 | 64" | 60" | 20" | 46 |
| DR2460-3 | 64" | 60" | 24" | 59 |
| DR2072-3 | 64" | 72" | 20" | 52 |
| DR2472-3 | 64" | 72" | 24" | 67 |

Four Shelf Style – 16½" Spacing

| Model | H | W | D | Weight |
|----------|-----|-----|-----|--------|
| DR2036-4 | 64" | 36" | 20" | 39 |
| DR2436-4 | 64" | 36" | 24" | 53 |
| DR2042-4 | 64" | 42" | 20" | 46 |
| DR2442-4 | 64" | 42" | 24" | 56 |
| DR2048-4 | 64" | 48" | 20" | 48 |
| DR2448-4 | 64" | 48" | 24" | 64 |
| DR2054-4 | 64" | 54" | 20" | 54 |
| DR2454-4 | 64" | 54" | 24" | 73 |
| DR2060-4 | 64" | 60" | 20" | 56 |
| DR2460-4 | 64" | 60" | 24" | 75 |
| DR2072-4 | 64" | 72" | 20" | 64 |
| DR2472-4 | 64" | 72" | 24" | 86 |

Options:

- /O52 5x2 Plate Caster (for conversion to mobile shelving, must be factory installed)
- /5B HD caster brakes
- /AF Adjustable Feet
- /PP Prison Package

APPLICATIONS: All welded aluminum dunnage shelving keeps product organized and off of the floor. Prolongs product life by circulating air underneath. 12" height meets all sanitary health codes. Made to measure for walk-in freezers, refrigerators and dry storage areas.

CONSTRUCTION: Heavy duty, high tensile extruded aluminum type 6063-T5 alloy. Shipped assembled for immediate use. 2,500 lbs. distributed weight capacity. LIFETIME WARRANTY for traditional food-service applications.

FRAME AND CROSS SUPPORTS: Vertical and horizontal frame sections are 1-1/2" extruded aluminum tubing. Channel arch construction of solid high tensile aluminum. Plastic bottom feet and top caps. All heli-arc welded.



Notes

55 Channel Drive • Port Washington, NY 11050-2216

8891 NW 102nd Street • Medley, FL 33178

Tel: 516-944-6271 • Fax: 516-944-0625

Toll Free: 866-712-7283

www.channelmfg.com • Email: sales@channelmfg.com