

TOP-LINE®

1890 Swarthmore Avenue, PO Box 2020, Lakewood, NJ 08701
Phone: 800-526-3694, 732-363-4700, Fax: 732-364-8110
www.encoreplumbing.com • www.componenthardware.com

PROJECT NAME: _____

LOCATION: _____


SPECIFIER ITEM NO. _____ QTY: _____

TOP-LINE PART NO. _____

TOP-LINE® 4" Deck Mount Faucet with Tubular Swing Spout & Lever Handles

TLL57-4xxx-SE1 Series

TLL57-4006-SE1 6" Spout, Compression Valves
TLL57-4008-SE1 8" Spout, Compression Valves
TLL57-4010-SE1 10" Spout, Compression Valves
TLL57-4012-SE1 12" Spout, Compression Valves
TLL57-4014-SE1 14" Spout, Compression Valves
TLL57-4016-SE1 16" Spout, Compression Valves



Dimensions shown in inches (mm) are for reference only
and are subject to change.

1-1/8" (29mm) holes for deck are recommended to
accommodate 1/2" supply nipples.

1/2" NPSM Male Inlets

Operating Temperature: 40-180°F (5-83°C)

Operating Pressure: 15-125psi

Approximate shipping weight - 6 lbs
Warranty - 2 years parts

Solid heavy duty cast body is specification and commercial quality

Commercial Quality Features


- Tubular swing spout design
- ADA-compliant lever handles
- Built-in check valve to prevent cross-flow and back-flow
- Leak proof double O-ring spout design
- Stainless steel spout

SPECIFICATIONS:

4" Deck Mount Faucet to be Encore TLL57 Series
in the following configuration:

- _____ TLL57-4006-SE1 6" Spout, Compression Valves
- _____ TLL57-4008-SE1 8" Spout, Compression Valves
- _____ TLL57-4010-SE1 10" Spout, Compression Valves
- _____ TLL57-4012-SE1 12" Spout, Compression Valves
- _____ TLL57-4014-SE1 14" Spout, Compression Valves
- _____ TLL57-4016-SE1 16" Spout, Compression Valves

Faucet body to be constructed of polished chrome plated brass with total
lead content less than 0.25% by weighted average. Handles to be lever
style. Color coded temperature indexes shall meet international standards.
Valve to be full turn compression type. Spout to be stainless steel tubular
swing style with leak proof double O-ring seal design. 2.2gpm aerator @
60psi standard with full flow stream bubbler screen spout tip.



Model No.	A	B	C
TLL57-4006-SE1	6" (152mm)	5-7/8" (150mm)	8-1/8" (207mm)
TLL57-4008-SE1	8" (203mm)	6-3/8" (162mm)	8-5/8" (219mm)
TLL57-4010-SE1	10" (254mm)	6-13/16" (173mm)	9-1/16" (230mm)
TLL57-4012-SE1	12" (305mm)	7-5/16" (185mm)	9-9/16" (243mm)
TLL57-4014-SE1	14" (356mm)	7-3/4" (197mm)	10" (254mm)
TLL57-4016-SE1	16" (406mm)	8-3/16" (208mm)	10-7/16" (265mm)

COMPLIES WITH:
THE FEDERAL "REDUCTION OF LEAD
IN DRINKING WATER ACT" -
2011 - US SENATE BILL NO. S.3874
NSF/ANSI 61/9, ANNEX G

