BACK BAR EQUIPMENT

Model: **BB59NSSSGD**

Natural Refrigerant R-290 Model

59" Back Bar Display Cooler with Sliding Glass Doors

Stainless steel exterior, countertop, interior back and side panels with reinforced stainless steel floor.



Options and Accessories

(upcharge and lead times may apply)		
Additional epoxy coated shelves	Condensing unit on right	
Stainless steel shelves	Wine rack	
Food storage rated stainless steel interior (NSF-7)	Casters or legs	
Riser base* (field installed)	Shallow depth	
Solid doors (consult factory)	Pass-thru (consult factory)	
Hinged glass doors (consult factory)		

Consult factory for other model configurations, options and accessories.

* Adding a Riser Base increases overall height 2"



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Project Name:		
Model Specified:		
Location:		
Item No:	Quantity:	
AIA #:	SIS #:	

Standard Model Features

REFRIGERATION SYSTEM

Performance rated front breathing refrigeration system

Natural, environmentally safe, high efficiency R-290 refrigerant¹

Automatic, hot gas condensate evaporator

Extra large, balanced evaporator coil

CABINET ARCHITECTURE

High density, non-CFC polyurethane foamed-in-place insulation Front, rear and side venting louvered grills Double pane, tempered low emissivity sliding glass doors Stainless steel reinforced threshold

MODEL FEATURES

Low profile cabinet design Electronic controller with digital display & hi-low alarm LED interior lighting Off-cycle defrost Easily accessible and serviceable slide-out condensing unit

¹ R-290 refrigerant meets all federal and state regulatory requirements.

APPROVAL:

Model Specifications

Model Plan Views



Net Capacity (cubic feet)	22 (623 cu l)
Width, Overall (inches)	59 (1499 mm)
Depth, Overall (inches) (including top & bumpers)	28 (711 mm)
Depth, Body Only (inches) (less doors)	25 (635 mm)
Height, Overall (inches)	34 ¾ (883 mm)
Capacity: # Barrel Kegs	2
Capacity: # Straight Wall Kegs	3
Capacity : # 1/6 Size Kegs	9
Number of Doors	2
Number of Shelves	4

REFRIGERANT DATA

Condensing Unit Size (H.P.)	1/4
Capacity (BTU per hour)*	2025

ELECTRICAL DATA


Voltage (International)	115/60/1 (220/50/1)
Feed Wires (including ground)	3
Total Amps (International)	3.7 (3.4)
10 ft. Cord/Plug [attached] (International)	Yes (No)

SHIPPING DATA

Weight (pounds)	415 (188 kg)
Height - Crated (inches)	46 (1168 mm)
Width - Crated (inches)	65 (1651 mm)
Depth - Crated (inches)	42 (1067 mm)

* Rating @ +25°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.





Due to our continued efforts in developing innovative products, specifications subject to change without notice.





Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579 539 Dunksferry Road

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com



© Copyright 2021. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.





IMPORTANT NOTE: Models are completely front breathing and take in and exhaust air through the front grill. For proper operation, the area in front of the cabinet **must** not be obstructed in any way. A clearance of 1" on the back and 3" on the sides is recommended.