
WORKTOP FREEZER (0°F)

Model: SWF27NBS

Natural Refrigerant R-290 Model

27" Worktop Freezer with Solid Door and 5½" Backsplash

Stainless steel front, top and end panels, aluminum back and interior.





Options and Accessories

(upcharge and lead times may apply)

(4433		
Stainless steel interior	Stainless steel shelves	
Stainless steel back	Door lock	
Overshelves (single or double)	Special electrical requirements (consult factory)	
Additional epoxy coated steel shelves	Hinged glass door (consult factory)	
Adjustable legs		

Consult factory for other model configurations, options and accessories.

Standard Model Features

REFRIGERATION SYSTEM

Performance rated refrigeration system

Natural, environmentally safe, high efficiency R-290 refrigerant¹

Automatic, hot gas condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, back mounted compressor

CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation

Smooth, polished chrome door handle

Spring loaded, self closing door

Magnetic snap in Santoprene™ door gasket

Heavy duty, epoxy coated steel shelf

Completely enclosed, vented and removable case back

5" casters

MODEL FEATURES

Field rehingeable door

Electronic controller with digital display & hi/low alarm

Automatic electric defrost

¹ R-290 refrigerant meets all federal and state regulatory requirements.



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

APPROVAL:

Model Specifications

DIMENSIONAL DATA Net Capacity (cubic feet) 7.4 (210 cu I) Width, Overall (inches) 27 ½ (699 mm) Depth, Overall (inches) 32 3/16 (818 mm) (including handle & bumpers) Height, Overall (inches) 40 3/4 (1035 mm) (including 5" casters) Shelf Area (square feet) 3.5 (0.3 sq m) Number of Shelves 1 Number of Doors 1 Interior Depth (inches) See Drawing Interior Height (inches) 26 ½ (667 mm) Interior Width (inches) 24 ½ (622 mm)

REFRIGERANT DATA

Condensing Unit Size (H.P.)	1/4	
Capacity (BTU per hour)*	1572	

ELECTRICAL DATA

Voltage (International)	115/60/1 (220/50/1)
Total Amps (International)	4.0 (2.8)
Defrost Amps (International)	4.8 (2.4)
10 ft. Cord/Plug [attached] (International)	Yes (No)

SHIPPING DATA

Weight (pounds)	170 (77 kg)
Height - Crated (inches)	48 ¾ (1238 mm)
Width - Crated (inches)	35 ½ (902 mm)
Depth - Crated (inches)	37 1/4 (946 mm)

* Rating @ -15°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug (varies by country)



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.









© Copyright 2021. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

Model Plan Views





IMPORTANT NOTE: If the cabinet is located directly against a wall, a <u>minimum clearance of 3" is required</u> on sides, front and rear.