

JOB	ITEM#

### **DURATHERM™ INDUCTION CHARGER**



# Item Numbers Duratherm Induction Charger DX2011208 (208V) 3-Phase

#### **Bases for Induction System**

DX1411003 - Onyx

DX1411050 - Midnight Blue

DX1411061 - Cranberry

DX1411084 - Sage

DX1411031 - Latte

# **Drying & Storage Racks For Induction Bases**

DXIBDRS90 - Holds 90 Induction Bases DXIBDRS180 - Holds 180 Induction Bases DXIBDRS270 - Holds 270 Induction Bases

**Replacement Cradle for Storage Rack** DX10251

#### **Application**

The Ideal Induction Charging System for tray line meal delivery systems which delivers 4 trays per minute and can be used for room service applications. The charging cycle of a DX1411 base is 15 seconds and 10 seconds for a DX821 base at nominal voltage.

#### Construction

The charger is manufactured in the United States and constructed with the main body of stainless steel and a heavy duty composite surface. The charger is equipped with a microprocessor that performs unique automatic standby/shut-off functions, self diagnostics and incorporates a proprietary automatic sensor for use with Dinex® Induction Bases. A visible Information Center displays the portion of the charge that has been completed, user prompts, operational status and trouble conditions.

#### **Standard Features**

- Countertop design, stainless steel housing, heavy duty electronic components, and composite material top, engineered for use in commercial kitchens.
- User-friendly control buttons for ease of use and automatic power control.
- A visible display using LCD technology Information Center and an audible alert.
- Display easily converted to other languages. (French, Spanish, English)
- · Automatic standby/shut-off feature.
- Easy-to-clean composite top surface.
- Integral cooling fan keeps internal electronics cool.
- 208V 3-Phase base cycle time approx.
   15 seconds. Note: Fluctuation in voltage may effect heating cycle time.
- Space efficient 15.3" x 18.3".
- · Washable filter.
- · Internal surge protection.
- Twist lock plug- NEMA L15-20P.

#### **Duratherm System**

- Senses both, Dinex Duratherm base DX1411 series, and SmarTherm base DX821 series ,automatically and gives the correct amount of energy to get correct temperature every time.
- Microprocessor monitors vital components and runs a performance check on average of 120 times per second. Charger shuts off automatically and displays "trouble codes" codes in plain text enabling user to diagnose or identify minor problems.
- Uses new, durable Dinex Induction Bases


#### Warranty


Two years parts and labor.



4711 E Hefner Road Oklahoma City, OK 73131 800.654.8210 • 405.475.5600 www.dinex.com

# **Duratherm INDUCTION CHARGER**















## Specifications

Item Number	Model Number	Overall Size		Electrical Specifications				Shipping Specs		
		w	D	Н	Volts	AMPS	Watt	NEMA Number	Ship Weight	Ship Cube
DX2011208	2011208	15.3" (38.9cm)	18.3" (46.5cm)	7.01" (17.8cm)	208V 3-Phase	20	6700	L15-20P	26 lb.	1.6