

LEAD FREE FLEXIBLE STAINLESS STEEL CONNECTORS – WATER & STEAM SERVICE

LEAD FREE*

Water Connector Solutions

Dormont Hi-PSI® Flex water connectors provide long, trouble-free service life—and permit quick, safe connection of hot and cold water service lines and steam lines to moveable/castered and stationary foodservice equipment. Use with utility distribution systems, steam kettles, steam tables, combi-ovens and other foodservice equipment.

Coated Water Connectors with 2-Way Quick Disconnect



ID / Length	24"	36"	48"	60"	72"
1/4"	W25BP2Q24	W25BP2Q36	W25BP2Q48	W25BP2Q60	W25BP2Q72
3/8"	W37BP2Q24	W37BP2Q36	W37BP2Q48	W37BP2Q60	W37BP2Q72
1/2"	W50BP2Q24	W50BP2Q36	W50BP2Q48	W50BP2Q60	W50BP2Q72
3/4"	W75BP2Q24	W75BP2Q36	W75BP2Q48	W75BP2Q60	W75BP2Q72
1"	W100BP2Q24	W100BP2Q36	W100BP2Q48	W100BP2Q60	W100BP2Q72

- Stainless steel corrugated hose with braid
- 2-Way disconnect
- Coated in gray antimicrobial PVC, with blue (cold) and red (hot) labels included.

Coated Water Connectors



ID / Length	24"	36"	48"	60"	72"
1/4"	W25BP24	W25BP36	W25BP48	W25BP60	W25BP72
3/8"	W37BP24	W37BP36	W37BP48	W37BP60	W37BP72
1/2"	W50BP24	W50BP36	W50BP48	W50BP60	W50BP72
3/4"	W75BP24	W75BP36	W75BP48	W75BP60	W75BP72
1"	W100BP24	W100BP36	W100BP48	W100BP60	W100BP72

- Stainless steel corrugated hose with braid
- Coated in gray antimicrobial PVC, with blue (cold) and red (hot) labels

Uncoated Water Connectors with Quick Disconnect



ID / Length	24"	36"	48"	60"	72"
1/4"	W25B2Q24	W25B2Q36	W25B2Q48	W25B2Q60	W25B2Q72
3/8"	W37B2Q24	W37B2Q36	W37B2Q48	W37B2Q60	W37B2Q72
1/2"	W50B2Q24	W50B2Q36	W50B2Q48	W50B2Q60	W50B2Q72
3/4"	W75B2Q24	W75B2Q36	W75B2Q48	W75B2Q60	W75B2Q72
1"	W100B2Q24	W100B2Q36	W100B2Q48	W100B2Q60	W100B2Q72

- Stainless steel corrugated hose with braid
- 2-Way disconnect

Uncoated Water Connectors



ID / Length	24"	36"	48"	60"	72"
1/4"	W25B24	W25B36	W25B48	W25B60	W25B72
3/8"	W37B24	W37B36	W37B48	W37B60	W37B72
1/2"	W50B24	W50B36	W50B48	W50B60	W50B72
3/4"	W75B24	W75B36	W75B48	W75B60	W75B72
1"	W100B24	W100B36	W100B48	W100B60	W100B72

- Stainless steel corrugated hose with braid

NOTES:

1. 150 PSI maximum.
2. Hot water temperatures up to 225°F (107°C)

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.