

Plug In SpeeDelight with flexible plate, ribbed removable teflon plate

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



603885 (HSG3RPRSE3)

SpeeDelight with Flexible Top Contact ribbed Plate, dark grey

Main Features

- combines 3 cooking technologies: contact, infrared radiation and microwaves to provide perfectly cooked food, heated to the core.
- Self adjusting ribbed upper plate to heat food adapting to its thickness.
- The Energy Saving Mode automatically switches to stand-by after an amount of time settled by the operator (from 1 to 60 minutes).
- Delivered with USB port and wi-fi connection to optimize workflows allowing local and remote inteaction (temperatures, countdowns, warnings).
- Electronic control with digital 4.3" LED display with adjustable brightness.
- Countdown display and buzzer with adjustable volume at the end of the cycle.
- Automatic mechanical lid holding and opening system controlled.
- IPX4 water resistance certification.
- Ergonomic handle for easy movement of the lid.
- Compliant with Regulation (EC) No 1935/2004 and its amendments, Regulation (EC) No 2023/2006 and its amendments.
- 8 pre-loaded programs (editable):-P1 = 70 sec. (12 sec. MW)-P2 = 80 sec. (12 sec. MW)-P3 = 60 sec. (20 sec. MW)-P4 = 75 sec. (20 sec. MW)-P5 = 85 sec. (25 sec. MW)-P6 = 85 sec. (18 sec. MW)-P7 = 30 sec. (25 sec. MW)-P8 = 12 sec. (no MW) With Top temperature = 249° C and bottom temperature = 220° C

APPROVAL:





Plug In SpeeDelight with flexible plate, ribbed removable teflon plate

Construction

- Aluminum ribbed top contact plate (215 x 215 mm) treated with a special non-stick coating.
- Smooth 4 mm thick quartz glass bottom cooking surface (250 x 250 mm).
- 2 temperature probes for an independent control of the top and bottom plate temperature.
- Included accessories: brush, spatula, scraper and degreasing liquid.
- Automatic lifting of the lid at the end of the cooking cycle via mechanical spring.
- Lid, back cover and bottom all in AISI 304 S/S.
- Lid covers, handle and side panels in high-grade reinforced composite material.
- 800W heating element on the top plate.
- 800W electrical armored heating element on the bottom plate.
- 2 x 1050W magnetrons for microwave.
- Front air inlet and back outlet for efficient cooling ventilation allows easy air filters removal and side by side installation.
- Independent temperature setting of the top and bottom plates from 50 to 250 °C.
- Delivered with IEC 309 3P+N+E IP44 380/480V 16A plug.

Included Accessories

• 1 of Glass saver for HSG Panini	PNC 653527
• 1 of Cleaning brush for SpeeDelight	PNC 653623
• 1 of Spatula for SpeeDelight	PNC 653625
• 1 of Special scraper for SpeeDelight	PNC 653690
• 1 of 4 rubber feet - Height = 26 mm for SpeeDelight	PNC 653792
• 1 of 11t bottle of detergent grease for SpeeDelight	PNC 653796

1 of 4 rubber feet - Height = 26 mm for	PNC 653792
SpeeDelight 1 of 11t bottle of detergent grease for SpeeDelight	PNC 653796
Optional Accessories	
• Glass saver for HSG Panini	PNC 653527 ☐
 Cleaning brush for SpeeDelight 	PNC 653623 □
 Spatula for SpeeDelight 	PNC 653625 □
 Special scraper for SpeeDelight 	PNC 653690 □
 Spray bottle (0,5lt) for detergent - SpeeDelight 	PNC 653695 □
 Removable teflon plate for SpeeDeligh 	t PNC 653787
 4 stainless steel feet - Height = 76 mm for SpeeDelight 	PNC 653791 □
 4 rubber feet - Height = 40 mm for SpeeDelight 	PNC 653793






Plug In SpeeDelight with flexible plate, ribbed removable teflon plate


91/1 91/1 91 10 mm 1 3/16 " 370 mm

7

Side



EI = Electrical inlet (power)
EO = Electrical Outlet



Electric

Supply voltage:

603885 (HSG3RPRSE3) 380-400 V/3N ph/50 Hz

Rated amps: 9 A Total Watts: 5 kW

Installation:

Clearance: 190mm from rear vertical panel

Key Information:

External dimensions, Width:	361 mm
External dimensions, Height:	630 mm
External dimensions, Depth:	675 mm
Net weight:	47 kg
Shipping weight:	60 kg
Shipping height:	700 mm
Shipping width:	450 mm
Shipping depth:	760 mm
Shipping volume:	0.24 m³

