



Model RSSL578SC

HIGH PROFILE 24" SLIM LINE MERCHANDISERS

| MERCHA | | _, | |
|------------------------|---------------------------------------|---------------------------------------|--------------|
| MODEL | DESCRIPTION (L X D X H) | ELECTRICAL | SHIP WEIGH |
| REFIGERATED | SELF-SERVE 🛞 | | |
| RSSL-360SC | 36" x 24" x 60" | 120/60/1 | 740 |
| RSSL-460SC | 48" x 24" x 60" | 120/60/1 | 800 |
| RSSL-560SC | 60" x 24" x 60" | 208-240/60/1 | 1,015 |
| RSSL-660SC | 72" x 24" x 60" | 208-240/60/1 | 1,075 |
| RSSL378SC | 36" x 24" x 78" | 120/60/1 | 800 |
| RSSL478SC | 48" x 24" x 78" | 208-240/60/1 | 892 |
| RSSL578SC | 60" x 24" x 78" | 208-240/60/1 | 904 |
| RSSL678SC | 72" x 24" x 78" | 208-240/60/1 | 1,180 |
| ACCESSORIES | High Profile Slim-Line Refrig | gerated Self-Serve Mo | erchandisers |
| LED Top Light – 350 | | <u> </u> | |
| | rior, Exterior, Trim and Base) | | |
| White Interior (Inclu | des Shelving) | | |
| Stainless Interior (In | cludes Shelving) | | |
| 360, 37 | 8, 460, 478 | | |
| 578 | | | |
| 678 | | | |
| Stainless Steel Inter | ior Back | | |
| 36", 48 | " | | |
| 60", 72 | | | |
| Stainless Steel Shel | | | |
| 36", 48 | ", 60" | | |
| 72" | | | |
| 2 1/2" Casters | | | |
| 2 1/2" Casters with | Skirt | | |
| 6" Legs | | | |
| Seismic Legs | | | |
| | nuous lineups (N/A with Casters | option) | |
| Cord and Plug | | | |
| Laminate Base | | | |
| Formic | a® Standard Offerings (finishings | ending in -58, -NT and | I -43) |
| | art® Standard Offerings (finishing | | |
| | ss Steel Finish In Lieu of Lamina | | |
| 36", 48 | " | | |
| 60", 72 | " | | |
| LED Lights Below S | | | |
| 360, 46 | | | |
| 378, 47 | '8 | | |
| 578, 67 | '8 | | |
| Security Night Cove | r – Removable Black Polycarbo | nate | |
| Additional Black Sh | elf (Non Lighted) | | |
| Additional Black Sh | elf (LED Lighted-3500K) | | |
| Glass Shelves (Per | Tier) | | |
| Sound Deadening K | · · · · · · · · · · · · · · · · · · · | | |
| | Tier) (In Lieu of Shelves) | | |
| | n with Outdoor Condensing Uni | t (EEV Included) | |
| | n with Indoor Condensing Unit (| <u> </u> | |
| | n without Compressor Supplied | · · · · · · · · · · · · · · · · · · · | |
| Condensate Pump - | | | |
| | ator Assembly – Required if No | Drain Available | |
| | dicated 120V / 5A Circuit Requir | | |
| Pofloative End Class | - (D-:-) | | |

Reflective End Glass (Pair)