

COFFEE BREWING SYSTEMS


CBS-2240 NG Brewers 1.0 GALLON BREWING SYSTEM

Shown with D448 4.0L / 1G LUXUS® Thermal Dispenser



CAPACITIVE TOUCHSCREEN DISPLAY

The NG line features a capacitive LED touchscreen display. Set brew times, program recipe buttons and more with just the touch of a finger. It's as easy as a smartphone.



LED STATUS BAR

Quickly identify where your machine is at in the brewing process from anywhere in the room. The LED Status Bar changes color during the brewing process to let you know when it's ready to brew, brewing, almost done and ready to serve.



BREW BASKET LOCKS

Brew baskets lock in place during the brewing process for added safety and quality control.

DISPENSERS

CBS-2240 NG Brewers

DISPENSERS

D451

4.0 Liter / 1 Gallon
LUXUS® Thermal
Server
L4S-10

NSF



D482

4.0 Liter / 1 Gallon
LUXUS® Sight
Gauge Server
LGS-10

NSF



D448

4.0 Liter / 1 Gallon
LUXUS® Thermal
Dispenser
L4D-10

NSF



D479

4.0 Liter / 1 Gallon
LUXUS® Sight
Gauge Dispenser
LGD-10

NSF



SERVING STATION FOR THERMAL SERVERS

A147

Single Serving
Station for
L4S-10 & LGS-10
S4S-10-1



A148

Twin Serving
Station for
L4S-10 & LGS-10
S4S-10-2



A149

Triple Serving
Station for
L4S-10 & LGS-10
S4S-10-3



All dispensers and serving stations **SOLD SEPARATELY**.



BREW BASKET DESIGN

Advanced brew basket design provides a deeper bed depth and superior thermal insulation for better extraction.



CASCADING SPRAY DOME

Patented design provides even saturation of the coffee bed for maximum extraction. Lime resistant design makes for less service calls.



ECO MODE

Reduces tank temperature during periods of non-operation to cut down on electricity usage.

ACCESSORIES

CBS-2240 NG Brewers

NOTE

Coffee brewers are available with **Plastic** or **Metal** brew basket options. Material type is of personal preference and does not affect flavor profile, however if you are looking for color identification the plastic brew baskets are the best option.

BREW BASKETS AND PAPER FILTERS

Item Number	Brew Basket	Coffee Capacity	Filter Size	Filter SKU	Filter/Case
All configurations	Standard Plastic / Stainless Steel	Up to 8oz / 227g	13" x 5"	F002	500/cs

B003218B1
13" x 5"
Stainless Steel
Brew Basket


B014218BN2BK
13" x 5"
Plastic Brew
Basket


F002
13" x 5"
Paper Filters


Contact Customer Service or your Sales Person for more options.

COLORED BREW BASKET HANDLE INSERTS

1023.00180.00 Blue Insert 	1023.00190.00 Red Insert 	1023.00191.00 Green Insert 	1023.00192.00 Orange Insert 
---	--	---	---

WATER FILTRATION SYSTEM

Filtration System	Item Number	Item Description	Rated Capacity	Working Pressure	Weight
Everpure®	A039	In-Line System	113,563 liters	10-125 psi [0.7-8.6 bar], non-shock	6.0 lbs / 2.7 kg
Everpure®	A075	Replacement Cartridge	113,563 liters	10-125 psi [0.7-8.6 bar], non-shock	6.0 lbs / 2.7 kg
BWT Bestmax	A138	In-Line System	3,002 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A139	Replacement Cartridge	3,002 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A140	In-Line System	4,562 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A141	Replacement Cartridge	4,562 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg

EVERPURE®

In-Line Water
Filtration System



SET INCLUDES: 1ea. commercial quality corrosion resistant filter head 1ea. taste and odor filter cartridge (FETCO® #A075) / 1ea. 3/8" x 4' connection hose / 1 set — mounting bracket and hardware.

- Recommended for large-sized operations
- Taste and odor filter for extremely turbid (cloudy) water
- Granular-activated carbon reduces sediment and chlorine
- Quick-disconnect style head/cartridge design cartridge for effortless replacement
- Durable, corrosion-resistant head includes built-in shutoff valve

BWT BESTMAX

In-Line Water
Filtration System



SET INCLUDES: 1ea. filter cartridge / 1ea. universal filter head / 1ea. wall mounting bracket Braided hose supplies 3/8" and 3/4" compression, in 24" or 48" lengths

- Recommended for small- to medium-sized operations
- Carbonate hardness removal prevents scale deposits and retains minerals
- Granular-activated carbon reduces sediment and chlorine
- Quick-disconnect style head/cartridge design cartridge for effortless replacement
- Durable, corrosion-resistant head includes built-in shutoff valve
- Four bypass settings allows for different water qualities and product preferences

TECHNICAL SPECIFICATIONS

NORTH AMERICA

CBS-2241 NG Brewer

ELECTRICAL										
Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E2241US-1A115-MA011	13x5" Metal	100-120	1 x 1.5 kW / 120 V	1	2+G	1.1-1.6	NEMA 5-15P	10.8-12.5	4.0 / 15.1	 
E2241US-1A115-PA011	13x5" Plastic	100-120	1 x 1.5 kW / 120 V	1	2+G	1.1-1.6	NEMA 5-15P	10.8-12.5	4.0 / 15.1	 
E2241US-1X117-MA011 DUAL VOLTAGE	13x5" Metal	100-120 120/208-240	1 x 1.7 kW / 120 V 2 x 1.7 kW / 120 V	1 1	2+G 3+G	1.3-1.8 3.5	NEMA 5-15P No Cord	12.2-14.6 14.6	4.5 / 17.1 9.0 / 34.2	 
E2241US-1X117-PA011 DUAL VOLTAGE	13x5" Plastic	100-120 120/208-240	1 x 1.7 kW / 120 V 2 x 1.7 kW / 120 V	1 1	2+G 3+G	1.3-1.8 3.5	NEMA 5-15P No Cord	12.2-14.6 14.6	4.5 / 17.1 9.0 / 34.2	 
WATER										
Water Inlet		Water Pressure [psig] / [Bar]		Minimum Flow Rate [gpm] / [L/min]			Tank Capacity [Gal] / [L]			
3/8" Male Flare		20-75 / 1.37-5.17		1.50 / 5.68			4.10 / 15.50			

CBS-2242 NG Brewer

ELECTRICAL										
Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E2242US-1B230-MA010	13x5" Metal	208-240	2 x 3.0 kW / 240 V	1	2+G	4.6-6.1	No Cord	22.1-25.4	12.2 / 46.3	NSF cULus
E2242US-1B230-PA010	13x5" Plastic	208-240	2 x 3.0 kW / 240 V	1	2+G	4.6-6.1	No Cord	22.1-25.4	12.2 / 46.3	NSF cULus
WATER										
Water Inlet	Water Pressure [psig] / [Bar]		Minimum Flow Rate [gpm] / [L/min]		Tank Capacity [Gal] / [L]					
3/8" Male Flare	20-75 / 1.37-5.17		1.50 / 5.68		7.48 / 28.31					

1 This version is made to order and it might require longer production lead time. Please ask your local sales representative for more information.

TECHNICAL SPECIFICATIONS

INTERNATIONAL

CBS-2241 NG Brewer

ELECTRICAL

Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E2241IN-1B123-PA010	13x5" Plastic	200-240	1 x 2.3 kW / 240 V	1	L/N/PE	1.7-2.4	No Cord	8.4-10.0	8.0 / 30.2	 
E2241IN-1B130-PA010 ¹	13x5" Plastic	200-240	1 x 3.0 kW / 240 V	1	L/N/PE	2.2-3.1	No Cord	10.8-12.9	10.0 / 37.9	 
E2241IN-1B140-PA010 ¹	13x5" Plastic	200-240	1 x 4.0 kW / 240 V	1	L/N/PE	2.9-4.1	No Cord	14.3-17.1	6.1 / 23.2	 
E2241NM-1B140-PA010 ¹	13x5" Plastic	208-240	1 x 4.0 kW / 240 V	1	2+G	3.1-4.1	No Cord	14.8-17.1	10.0 / 37.9	 
E2241NM-1X123-PA012 DUAL VOLTAGE	13x5" Plastic	100-120 120/208-240	1 x 2.3 kW / 240 V 2 x 2.3 kW / 240 V	1 1	2+G 3+G	1.7-2.4 4.7	No Cord	16.4-19.6 19.6	6.1 / 23.2 10.0 / 37.9	 
E2241CE-1B123-PA005	13x5" Plastic	230	1 x 2.3 kW / 240 V	1	L/N/PE	2.2	No Cord	9.6	7.4 / 28.2	 

WATER

Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	1.50 / 5.68	4.10 / 15.50

CBS-2242 NG Brewer

ELECTRICAL

Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E2242IN-1B223-PA010	13x5" Plastic	200-240	2 x 2.3 kW / 240 V	1	L/N/PE	3.3-4.7	No Cord	16.4-19.6	12.2 / 46.3	 
E2242IN-1B230-PA010	13x5" Plastic	200-240	2 x 3.0 kW / 240 V	1	L/N/PE	4.3-6.1	No Cord	21.2-25.4	15.9 / 60.4	 
E2242NM-1B230-PA010	13x5" Plastic	208-240	2 x 3.0 kW / 240 V	1	2+G	4.6-6.1	No Cord	22.1-25.4	15.9 / 60.4	 
E2242CE-1B230-PA010	13x5" Plastic	230	2 x 3.0 kW / 240 V	1	2L/N/PE	5.6	No Cord	24.4	14.9 / 56.4	 

WATER

Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	1.50 / 5.68	7.48 / 28.31

¹ This version is made to order and it might require longer production lead time. Please ask your local sales representative for more information.


DIMENSIONS

CBS-2241 NG Brewer

DIMENSIONS							WEIGHT		
	Height (A)	Width (B)	Depth (D)	Depth (E)	Brew Basket Clearance (F)	Faucet Clearance (G)		Empty [lbs] / [kg]	Filled [lbs] / [kg]
Product Dimensions	34.5" 87.63 cm	11.75" 29.84 cm	20.5" 52.07 cm	15.13" 38.43 cm	21.38" 54.30 cm	12.13" 30.80 cm	Product Weight	38 lbs 17.2 kg	64 lbs 29.0 kg
Shipping Dimensions	35.0" 88.90 cm	17.0" 43.18 cm	22.0" 55.88 cm	N/A	N/A	N/A	Shipping Weight	50 lbs 22.7 kg	N/A

CBS-2242 NG Brewer

DIMENSIONS							WEIGHT		
	Height (A)	Width (C)	Depth (D)	Depth (E)	Brew Basket Clearance (F)	Faucet Clearance (G)		Empty [lbs] / [kg]	Filled [lbs] / [kg]
Product Dimensions	34.5" 87.63 cm	19.75" 50.16 cm	20.5" 52.07 cm	15.13" 38.43 cm	21.38" 54.30 cm	12.13" 30.80 cm	Product Weight	56 lbs 25.4 kg	101 lbs 45.8 kg
Shipping Dimensions	35.0" 88.90 cm	22.0" 55.88 cm	24.0" 60.96 cm	N/A	N/A	N/A	Shipping Weight	66 lbs 29.9 kg	N/A



FAX
+1.847.719.3001