

COFFEE BREWING SYSTEMS

CBS-2260 NG Brewers

3.0-3.5 GALLON BREWING SYSTEM

Shown with D012 12.0L / 3.0G LUXUS® Thermal Dispenser




CAPACITIVE TOUCHSCREEN DISPLAY

The NG line features a capacitive LED touchscreen display. Set brew times, program recipe buttons and more with just the touch of a finger. It's as easy as a smartphone.



LED STATUS BAR

Quickly identify where your machine is at in the brewing process from anywhere in the room. The LED Status Bar changes color during the brewing process to let you know when it's ready to brew, brewing, almost done and ready to serve.



BREW BASKET LOCKS

Brew baskets lock in place during the brewing process for added safety and quality control.



DISPENSERS

CBS-2260 NG Brewers

DISPENSERS

D012

12.0 Liter / 3.0 Gallon
LUXUS® Thermal
Dispenser
TPD-30

NSF



All dispensers **SOLD SEPARATELY**.



BREW BASKET DESIGN

Advanced brew basket design provides a deeper bed depth and superior thermal insulation for better extraction.



CASCADING SPRAY DOME

Patented design provides even saturation of the coffee bed for maximum extraction. Lime resistant design makes for less service calls.



ECO MODE

Reduces tank temperature during periods of non-operation to cut down on electricity usage.

ACCESSORIES

CBS-2260 NG Brewers

BREW BASKETS AND PAPER FILTERS

Item Number	Brew Basket	Coffee Capacity	Filter Size	Filter SKU	Filter/Case
All configurations	Stainless Steel	Up to 32oz / 907g	20" x 8"	F004	500/cs

B00828004

21" x 7"
Stainless Steel
Brew Basket



B00828005

21" x 7"
Stainless Steel
Brew Basket
with Clips

F004

20" x 8"
Paper Filters



Contact Customer Service or your Sales Person for more options.

WATER FILTRATION SYSTEM

Filtration System	Item Number	Item Description	Rated Capacity	Working Pressure	Weight
Everpure®	A039	In-Line System	113,563 liters	10-125 psi [0.7-8.6 bar], non-shock	6.0 lbs / 2.7 kg
Everpure®	A075	Replacement Cartridge	113,563 liters	10-125 psi [0.7-8.6 bar], non-shock	6.0 lbs / 2.7 kg
BWT Bestmax	A138	In-Line System	3,002 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A139	Replacement Cartridge	3,002 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A140	In-Line System	4,562 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A141	Replacement Cartridge	4,562 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg

EVERPURE®

In-Line Water
Filtration System



SET INCLUDES: 1ea. commercial quality corrosion resistant filter head 1ea. taste and odor filter cartridge (FETCO® #A075) / 1ea. 3/8" x 4' connection hose / 1 set — mounting bracket and hardware.

- Recommended for large-sized operations
- Taste and odor filter for extremely turbid (cloudy) water
- Granular-activated carbon reduces sediment and chlorine
- Quick-disconnect style head/cartridge design cartridge for effortless replacement
- Durable, corrosion-resistant head includes built-in shutoff valve


BWT BESTMAX

In-Line Water
Filtration System



SET INCLUDES: 1ea. filter cartridge / 1ea. universal filter head / 1ea. wall mounting bracket Braided hose supplies 3/8" and 3/4" compression, in 24" or 48" lengths

- Recommended for small- to medium-sized operations
- Carbonate hardness removal prevents scale deposits and retains minerals
- Granular-activated carbon reduces sediment and chlorine
- Quick-disconnect style head/cartridge design cartridge for effortless replacement
- Durable, corrosion-resistant head includes built-in shutoff valve
- Four bypass settings allows for different water qualities and product preferences



TECHNICAL SPECIFICATIONS

NORTH AMERICA


CBS-2261 NG Brewer

ELECTRICAL											
Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification	
E2261US-UB230-MA110 DUAL PHASE	21x7" Metal	208-240	2 x 3.0 kW / 240 V	1	2+G	4.6-6.1	No Cord	22.1-25.4	15.9 / 60.4	 	
	21x7" Metal	208-240	3 x 3.0 kW / 240 V	3	3+G	6.9-9.1	No Cord	19.2-22.1	23.9 / 90.6		
WATER											
Water Inlet		Water Pressure [psig] / [Bar]			Minimum Flow Rate [gpm] / [L/min]			Tank Capacity [Gal] / [L]			
3/8" Male Flare		20-75 / 1.37-5.17			1.50 / 5.68			8.63 / 32.67			

CBS-2262 NG Brewer

ELECTRICAL										
Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E2262US-3B330-MA110	21x7" Metal	208-240	3 x 3.0 kW / 240 V	3	3+G	6.9-9.1	No Cord	19.2-22.1	23.9 / 90.6	 
E2262US-3B630-MA110	21x7" Metal	208-240	6 x 3.0 kW / 240 V	3	3+G	13.6-18.1	No Cord	37.5-43.7	31.9 / 120.8	 
E2262US-3B340-MA110	21x7" Metal	208-240	6 x 4.0 kW / 240 V	3	3+G	6.9-9.1	No Cord	25.5-29.3	47.8 / 181.3	 
E2262US-3B640-MA110	21x7" Metal	208	6 x 4.0 kW / 240 V	3	3+G	18.1	No Cord	50.4	47.8 / 181.3	 
WATER										
Water Inlet		Water Pressure [psig] / [Bar]		Minimum Flow Rate [gpm] / [L/min]			Tank Capacity [Gal] / [L]			
3/8" Male Flare		20-75 / 1.37-5.17		3.00 / 11.36			15.86 / 60.04			

1 This version is made to order and it might require longer production lead time. Please ask your local sales representative for more information.



TECHNICAL SPECIFICATIONS
INTERNATIONAL

CBS-2261 NG Brewer

ELECTRICAL										
Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E2261IN-3C330-MA110	21x7" Metal	220/380-240/415	3 x 3.0 kW / 240 V	3	3L/N/PE	7.7-9.1	No Cord	11.9-12.9	23.9 / 90.6	NSF cULus
E2261IN-3C340-MA110	21x7" Metal	220/380-240/415	3 x 4.0 kW / 240 V	3	3L/N/PE	10.2-12.1	No Cord	15.7-17.1	30.0 / 113.7	NSF cULus
E2261IN-3C350-MA110¹	21x7" Metal	220/380-240/415	3 x 5.0 kW / 240 V	3	3L/N/PE	12.7-15.1	No Cord	19.6-21.3	30.0 / 113.7	NSF cULus
E2261NM-3B350-MA110	21x7" Metal	208-240	3 x 5.0 kW / 240 V	3	3+G	11.4-15.1	No Cord	31.7-36.5	30.0 / 113.7	NSF NOM
E2261CE-3C330-MA110	21x7" Metal	230/400	3 x 3.0 kW / 240 V	3	3L/N/PE	8.4	No Cord	12.3	22.1 / 83.6	NSF CE
E2261CE-3C340-MA110	21x7" Metal	230/400	3 x 4.0 kW / 240 V	3	3L/N/PE	11.1	No Cord	16.3	29.2 / 110.8	NSF CE

WATER			
Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	1.50 / 5.68	8.63 / 32.67

CBS-2262 NG Brewer

ELECTRICAL										
Item Number	Brew Basket	Voltage	Heater Config.	Phase	Wires	kW	Connection	Max Amp Draw	[Gal] / [L] Hour	Certification
E2262IN-3C350-MA110¹	21x7" Metal	220/380-240/415	3 x 5.0 kW / 240 V	3	3L/N/PE	12.7-15.1	No Cord	19.6-21.3	39.9 / 151.1	NSF cULus
E2262IN-3C630-MA110	21x7" Metal	220/380-240/415	6 x 3.0 kW / 240 V	3	3L/N/PE	15.2-18.1	No Cord	23.4-25.4	47.8 / 181.3	NSF cULus
E2262NM-3B630-MA110	21x7" Metal	208-240	6 x 3.0 kW / 240 V	3	3+G	13.6-18.1	No Cord	37.9-43.7	47.8 / 181.3	NSF NOM
E2262CE-3C340-MA110	21x7" Metal	230/400	3 x 4.0 kW / 240 V	3	3L/N/PE	11.1	No Cord	16.3	29.2 / 110.8	NSF CE
E2262CE-3C350-MA110	21x7" Metal	230/400	3 x 5.0 kW / 240 V	3	3L/N/PE	13.9	No Cord	20.3	36.7 / 139.0	NSF CE

WATER			
Water Inlet	Water Pressure [psig] / [Bar]	Minimum Flow Rate [gpm] / [L/min]	Tank Capacity [Gal] / [L]
3/8" Male Flare	20-75 / 1.37-5.17	3.00 / 11.36	15.86 / 60.04

1 This version is made to order and it might require longer production lead time. Please ask your local sales representative for more information.
2 Based on standard (factory) settings: 6.0 minute brew time (0% prewet; 93°C water), DT=140°F, 3 gallon per batch.

DIMENSIONS

CBS-2261 NG Brewer

DIMENSIONS						
	Height (A)	Width (B)	Depth (D)	Depth (E)	Brew Basket Clearance (F)	Faucet Clearance (G)
Product Dimensions	41.38" / 105.11 cm	17.88" / 45.42 cm	27.50" / 69.85 cm	22.25" / 56.52 cm	23.88" / 60.66 cm	12.13" / 30.80 cm
Shipping Dimensions	39.0" / 99.06 cm	23.0" / 58.42 cm	28.0" / 71.72 cm	N/A	N/A	N/A

WEIGHT		
	Empty [lbs] / [kg]	Filled [lbs] / [kg]
Product Weight	88 lbs / 39.9 kg	160 lbs / 72.6 kg
Shipping Weight	97 lbs / 44.0 kg	N/A

CBS-2262 NG Brewer

DIMENSIONS						
	Height (A)	Width (C)	Depth (D)	Depth (E)	Brew Basket Clearance (F)	Faucet Clearance (G)
Product Dimensions	41.38" / 105.11 cm	32.0" / 81.28 cm	27.50" / 69.85 cm	22.25" / 56.52 cm	23.88" / 60.66 cm	12.13" / 30.80 cm
Shipping Dimensions	39.0" / 99.06 cm	37.0" / 93.98 cm	29.0" / 73.66 cm	N/A	N/A	N/A

WEIGHT		
	Empty [lbs] / [kg]	Filled [lbs] / [kg]
Product Weight	130 lbs / 59.0 kg	266 lbs / 120.7 kg
Shipping Weight	140 lbs / 63.5 kg	N/A



FAX
+1.847.719.3001