

APPLICATION:		PRODUCT NAME: PRE-RINSE SPRING STYLE DECK MOUNT	
JOB NAME:		☐ SPECIAL CONFIGURATION ☐ CHECK BASE MODEL AND OPTIONS	
QUANTITY:	ITEM NO.	MODEL: ☐ 2010 ULTRA SPRAY VALVE, NO WALL BRACKET ☐ 2010-WB ULTRA SPRAY VALVE, WALL BRACKET	
		OPTIONS OR MODIFICATIONS: ☐ SUPPLY LINES (24" OR 36") CIRCLE LENGTH ☐ ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE ☐ IN-LINE DUAL CHECK VALVE ☐ BRUSH ☐ VANDAL RESISTANT KIT ☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE ☐ OTHER _____	
		FEATURES CONTROL VALVE * SINGLE DECK MOUNT * TEMPERATURE CONTROL VALVE WITH INTERNAL SPRING LOADED CHECK VALVES * STEM - LEFT HAND * HOT & COLD INDEX BUTTONS * SWIVELLING SEAT DISKS * STAINLESS STEEL SEATS * STAINLESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS HOSE * 36" LENGTH * STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET * 3 PLY FIBER REINFORCED INTERNAL RUBBER HOSE * REPAIRABLE IN FIELD WITH SIMPLE TOOLS ULTRA SPRAY VALVE * LOWEST ENERGY USER - 1.15 GPM @ 60 PSI * CLEANS FASTER - TEST PROVEN * ENGINEERED TO LAST - NO 'O' RINGS TO LEAK * INTERCHANGEABLE - FITS ALL BRANDS WALL BRACKET * ADJUSTS FROM 2" TO 12" SYSTEM LIMITS * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE: 200 PSI MAX. STATIC SHIPPING WEIGHT * 12.0 LBS	
ROUGH-IN: 		 FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com	
EPAct 2005 Compliant		ANSI/A112.18.1M	