SWIVEL OUTLET  1/2" SLIP JOINT	APPLICATION:		PRODUCT NAME:  4" C/C BACKSPLASH MOUNT	SPEC. 3600 REV. A
SWIVEL OUTLET  1/2" SLIP JOINT  1/2" SLIP JOINT				3
SWIVEL OUTLET  1/2" SLIP JOINT	JOB NAME:			00 K
SWIVEL OUTLET  1/2" SLIP JOINT	QUANTITY:	ITEM NO.		
FEATURES  1-7/8" [48mm]  1-7/8"  4" BACKSPLASH  9 SWIVELLING SEAT DISKS  1-7 STEM - RIGHT HAND  1-7 SLIP JOINT  1/2" SLIP JOINT  1/2" SLIP JOINT  1/2" SLIP JOINT  1/2" SLIP JOINT	─ SWIVEL OUTLET  ─ 1/2" SLIP JOINT			
4 "BACKSPLASH SWIVELLING SEAT DISKS HOT SIDE STEM - RIGHT HAND COLD SIDE STEM - LEFT HAND STAINLESS STEEL SEATS STAINLESS STEEL SEAT SCREWS STAINLESS STEEL HANDLE SCREWS SYSTEM LIMITS TEMP: 40°F MIN. TO 140°F MAX. PRESSURE: 200 PSI MAX. STATIC SHIPPING WEIGHT 3.75 LBS  ROUGH-IN:			FEATURES	
* PRESSURE: 200 PSI MAX. STATIC SHIPPING WEIGHT * 3.75 LBS  ROUGH-IN:  1/2" SLIP JOINT  27/8" [22mm]	8" -	[48mm]	* 4" BACKSPLASH  * SWIVELLING SEAT DISKS  * HOT SIDE STEM - RIGHT HAND  * COLD SIDE STEM - LEFT HAND  * STAINLESS STEEL SEATS  * STAINLESS STEEL SEAT SCREWS  * STAINLESS STEEL HANDLE SCREWS  SYSTEM LIMITS	
ROUGH-IN:  * 3.75 LBS  * 3.75 LBS				
7/2" SLIP JOINT  Ø7/8"  [22mm]				
7/2" SLIP JOINT  Ø7/8" [22mm]				
7/2" SLIP JOINT  Ø7/8" [22mm]				
7/2" SLIP JOINT  Ø7/8" [22mm]				
7/2" SLIP JOINT  Ø7/8" [22mm]				
7/2" SLIP JOINT  Ø7/8" [22mm]				
Ø7/8" [22mm]	ROUGH-IN:			
Ø7/8" [22mm]				
4" [104mm]				
			FISHER	$\dashv$

(F)

ANSI/A112.18.1M