



FOOTPRINT:



ROUGH-IN:



PRODUCT NAME: STAINLESS STEEL SINGLE DECK PRE-RINSE WITH ADD-ON

MODEL:

- 68012 6" SWING SPOUT W/ LEVER HANDLES
- 68020 8" SWING SPOUT W/ LEVER HANDLES
- 68039 10" SWING SPOUT W/ LEVER HANDLES
- 68047 12" SWING SPOUT W/ LEVER HANDLES
- 68055 14" SWING SPOUT W/ LEVER HANDLES
- 68063 16" SWING SPOUT W/ LEVER HANDLES
- 75930 6" SWING SPOUT W/ WRIST HANDLES
- 75949 8" SWING SPOUT W/ WRIST HANDLES
- 75957 10" SWING SPOUT W/ WRIST HANDLES
- 75965 12" SWING SPOUT W/ WRIST HANDLES
- 75973 14" SWING SPOUT W/ WRIST HANDLES
- 75981 16" SWING SPOUT W/ WRIST HANDLES

FEATURES:

- CONTROL VALVE
- * SINGLE DECK
 - * STAINLESS STEEL CONSTRUCTION
 - * SWIVEL SEAT DISK
 - * STEM - LEFT HAND
 - * LEVER HANDLES OR WRIST HANDLES
 - * STAINLESS STEEL SWING SPOUT

- ADD-ON CONTROL VALVE
- * STEM - RIGHT HAND SWIVEL
 - * HOT INDEX BUTTON
 - * SWIVELLING SEAT DISKS
 - * STAINLESS STEEL SEATS, SEAT SCREWS AND HANDLE SCREWS.

- HOSE
- * 36" LENGTH
 - * STAINLESS STEEL END FITTINGS
 - * STAINLESS STEEL EXTERNAL JACKET
 - * 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE
 - * REPAIRABLE IN FIELD WITH SIMPLE TOOLS

- ULTRA SPRAY VALVE
- * LOWEST ENERGY USER - 1.15 GPM @ 60 PSI
 - * CLEANS FASTER - TEST PROVEN
 - * ENGINEERED TO LAST - NO 'O' RINGS TO LEAK
 - * INTERCHANGEABLE - FITS ALL BRANDS

- WALL BRACKET
- * ADJUSTS FROM 2" TO 12"

- SYSTEM LIMITS
- * TEMP: 40°F MIN. TO 140°F MAX. STATIC
 - * PRESSURE 200 PSI MAX. STATIC
 - * SHIPPING WEIGHT: 15.0 LBS

* NSF 61-9 APPROVED & LISTED
www.truesdail.com

FISHER
FISHER MANUFACTURING COMPANY
TOLL FREE: 800-421-6162 - FAX: 800-832-8238
information@fisher-mfg.com - www.fisher-mfg.com