APPLICATION:	PRODUCT NAME:
	GLASS FILLER HOSE ASSEMBLY
JOB NAME:	98590 SPECIAL CONFIGURATION
QUANTITY: ITEM NO.	(CHECK BASE MODEL AND OPTIONS) MODEL:
11210	■ 1465
	OPTIONS OR MODIFICATIONS
	■ OTHER 2542 - 1/4" BACKFLOW PREVENTER
A/OUE NET INVET	
1/2"F NPT INLET -	FEATURES:
	GLASS FILLER VALVE
	* NOZZLE THREADED INTO VALVE * AERATED STREAM
1/2"F X 1/4"F NPT ADAPTER-	* 45° ANGLED HEAD
1/4"M X 1/4"F NPT_	HOSE
BACKFLOW PREVENTER	* 84" I FNGTH
	* STAINLESS STEEL END FITTINGS * * STAINLESS STEEL EXTERNAL JACKET
7 1/8"	* BRAIDED USDA APPROVED FOODGRADE
[179.6mm] 84" FOODGRADE HOSE	INTERNAL HOSE
	BACKFLOW PREVENTER
	* ATMOSPHERIC VENT * FOR IN-LINE CONTINUOUS PRESSURE APPLICATIONS
	* FOR EXPOSED SERVICEABLE INSTALLATIONS
	SYSTEM LIMITS
	* FLOW RATE: 5.0 GPM AT 80 PSI
	* TEMP: 40°F MIN. TO 140°F MAX.
	* PRESSURE 200 PSI MAX. STATIC
	SHIPPING WEIGHT
	* STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET * BRAIDED USDA APPROVED FOODGRADE INTERNAL HOSE BACKFLOW PREVENTER * ATMOSPHERIC VENT * FOR IN-LINE CONTINUOUS PRESSURE APPLICATIONS * FOR EXPOSED SERVICEABLE INSTALLATIONS SYSTEM LIMITS * FLOW RATE: 5.0 GPM AT 80 PSI * TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE 200 PSI MAX. STATIC SHIPPING WEIGHT * 5.0 LBS
	- SHER
	*
	FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238

information@fisher-mfg.com - www.fisher-mfg.com

ANSI/A112.18.1M

SPEC. 98590 REV. A