

www.glastender.com



WT-12-SS

NOTE: Faucet handles not included.

Project:		AIA#
Item #:_	Qty:	SIS#
Model #		0.0

Wall Mount Towers

WT-__-SS

Size: Specify the number of faucets from 4, 5, 6, 8, 10, 12

Standard Features

- 1/4" shanks with 3/16" restriction lines
- · All stainless steel including faucets
- Grainline finish
- · Integral drain pan with lift-out perforated inserts
- Built-in wall mounting bracket with open back
- Removable front cover for access to wall mounting flange

Configurable Options

- 4, 5, 6, 8, 10, or 12 faucet sizes
- Air cooled for direct-draw system or glycol cooled for recirculating system
- Back or bottom beverage line orientation

Mounting Details

Specifications

Materials

- · Stainless steel faucets and shanks
- Stainless steel body and drain pan
- Galvanized steel inner structure on glycol chilled models

Shank Sizes


• 1/4" I.D. with 3/16" fittings

Drains

• 1/2" tailpiece on drain pan



4004503 Conforms to NSF/ANSI STD 372




Glastender, Inc. • 5400 N Michigan Rd • Saginaw, MI • 48604-9780 989.752.4275 • 800.748.0423 • Fax 989.752.4444 www.glastender.com

Specifications subject to change without notice. For current specifications please visit our website.


Approval/Notes:

Printed in USA WT Rev. 05-30-23

FRONT ELEVATION




SIDE ELEVATION




Note: Faucet handles not included.

PLAN VIEW

BOTTOM LINE ORIENTATION



BACK LINE ORIENTATION



Wall Mount Towers		
Number of faucets	Width	
4	14"	
5	17"	
6	20"	
8	26"	
10	32"	
12	38"	