



Table Top Kettles model TDC/3

Description

Kettle shall be a Groen Model TDC/3 - _____ (specify 3,6,10 or 20 quart) stainless steel 2/3 steam jacketed unit operating from direct steam per Bulletin 141045 as follows:

Construction

Kettle interior shall be of 304 stainless steel, solid, one-piece welded construction. Support arms are heavy stainless steel tubing. Rim shall be heavy reinforced with a welded "Butterfly" shaped pouring lip for pouring control and durability. Kettle shall have two operating handle lugs so that the handle can be attached on right or left side.

Finish

Interior of kettle shall be polished to a 180 emery grit finish. Exterior of kettle shall be finished to a bright high buff finish, ensuring maximum ease in cleaning and maintaining brilliant appearance, which is ideal for back bar presentation cooking or open display kitchen mounting.

ASME Code

Unit shall be ASME shop inspected, stamped and registered with the National Board for operation up to a maximum working pressure of 55 PSI.

Sanitation

Unit shall be designed and constructed to meet NSF requirements and be NSF listed.

Steam Pressure

Kettle shall operate dependably at any steam pressure between 5 and 55 PSI. Higher working pressure available.

Performance/Features

Pouring height shall be such that kettle can be emptied into an 8" high pan on a flat table. Design shall make it possible for one person to tilt kettle, even when kettle is filled to capacity.

All sizes, including 3 and 6 quart models, have full bottom hemisphere steam jacket, for rapid product heating.

Mounting

Kettle shall be mounted on sturdy tubular stainless steel arms. The steam supply shall enter through the left kettle support arm into the jacket at the rotary joint. Condensate shall be removed through the right rotary joint, down through the support arm. No exposed steam piping shall be on the kettle body.

Multiple kettles can be table or back bar mounted for display cooking. Minimum table space required: 14" for 3-10 quart and 16" for 20 quart.

Installation

Steam trap assembly is required and not provided unless ordered as an option. 3/8" IPS steam inlet and condensate outlet required. Safety valve and remote steam source required.



Options/Accessories

- Steam trap assembly
- 316 stainless steel interior
- Lift off cover
- Basket insert
- Steam regulator

Related Products

- T5C tables with kettles
- Cabinet base

Origin of Manufacture

Kettle shall be designed and manufactured in the United States.

**Stainless Steel
2/3 Steam Jacketed
Kettle**

**Table Top Mounted
Tilting
Direct Steam Heated
3, 6, 10 & 20-
Quart Capacity**

Short Form

Groen Model TDC/3 (specify 3, 6, 10 or 20 quart capacity) stainless steel, direct steam jacketed kettle per Bulletin 141045. Unit shall have full bottom hemisphere steam jacket with one piece welded construction of Type 304 stainless steel, and sturdy tubular support arms. Reinforced bar rim, with butterfly shaped pouring lip standard. Lugs provided for use of handles on either side of unit. NSF listed, ASME code constructed and National Board registered. Operates dependably from 5 up to 55 PSI maximum. Steam and condensate connections required. Made in USA.



Applications

Browning Meats
Vegetables
Soups
Sauces
Pasta
Rice
Pie Fillings
Gravies
Chili
Stews

TABLE OF DIMENSIONS

DIM.	3 QT. (2.8 L)		6 QT. (5.7 L)		10 QT. (9.5 L)		20 QT. (18.9 L)	
	IN.	MM	IN.	MM	IN.	MM	IN.	MM
A	10	254	12	304	10	254	12	304
B	12 7/8	327	14 7/8	378	12 7/8	327	14 7/8	378
C	13 1/4	336	15 1/4	387	13 1/4	336	15 1/4	387
D	8	203	9	229	8	203	9	229
E	4 7/8	124	6 7/8	177	10	254	12	305
F	12 1/8	307	13 1/8	333	16 1/8	409	17 1/8	438
G	8 7/8	225	8 7/8	225	8 7/8	225	8 7/8	225
H	5	127	6	152	5	127	6	152
J	11	279	12 1/8	308	15	381	16 1/8	409
K	8 1/2	215	8 1/4	209	8 3/4	222	8 1/2	216
L	2 7/8	73	3 7/8	98	6 1/8	155	7 1/8	181
M	12 1/8	307	14 1/8	359	12 1/8	307	14 1/8	359
N	21 1/2	546	22 1/2	571	25 1/2	648	26 1/2	673
P	6	152	7	178	6	152	7	178

NOTES:

1. SEE DWG.C-7059-2 FOR PIPING INSTALLATION DETAILS.
2. EXTENDED STEM, GLOBE VALVE & COLLARED SLEEVE FURNISHED AT EXTRA COST. SEE DWG.C-7059-2
3. DIMENSIONS IN BRACKETS () ARE MM.

