



Freight Class: 125
Ships in: **5** days or less!

NSF Model #7120

4 TOUGH TRANSPORT
1000 LBS | 450 KG

Ergo-One® SYSTEM UTILITY CARTS | STAINLESS STEEL

This beneficial cart was designed with the help of an orthopedic specialist to prevent body strain and unnecessary worker's comp expenses.

- Vertical handle with comfortable grip ensures wrists are in the correct position for pushing and steering
- "Safety Zone" shelves are the proper height for loading and unloading*
- No-mark®, extra load, cushion tread wheels absorb impact, reducing vibration and strain
- All joints are fully welded to better withstand heavy loads and frequent use
- 14-gauge stainless steel shelves reinforced for added strength
- Stainless steel is easy to clean and sanitize
- Leg bumpers protect walls and furniture
- All models are NSF listed

FACTORY INSTALLED OPTIONS (PAGE 55):

- Ground and polished joint welds
- Hi-Temp nylon casters, up to 400° F. (204° C.) 5" (127) 2 ea. fixed, 2 ea. swivel casters
- Handle Set Both Ends
- Perimeter Channel Bumper
- 2 Brake Casters
- 4 - 5" Swivel Casters
- 2 - 5" Swivel, 2 - 5" Fixed Casters
- 2 - 5" Swivel, 2 - 5" Fixed

Model	# of Shelves	Shelf Size	Shelf Clearance	Top Shelf Height	Overall Size			Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m³)
					W	L	H		
7120	2	21" x 33" (533 x 838)	18-1/2" (470)	40" (1016)	21-5/8" (549)	41-3/8" (1051)	46-3/4" (1187)	88 (39.9)	25.7 (1.0)
7130	2	21" x 49" (533 x 1245)	18-1/2" (470)	40" (1016)	21-5/8" (549)	57-7/16" (1459)	46-3/4" (1187)	163 (74.1)	80.1 (3.1)
7140	2	24" x 42" (610 x 1067)	18-1/2" (470)	40" (1016)	24-5/8" (625)	50-7/16" (1281)	46-3/4" (1187)	166 (75.5)	76.8 (2.9)

Measurements in () denote metric millimeters, unless otherwise specified. *Top shelf is 40" (1016) from the floor and bottom shelf is 20" (508) Handle assembly required. Lake-Glide® Casters: 5" (127) - 2 ea. swivel, 8" (203) - 2 ea. fixed; Extra load, No-Mark cushion tread.

4 TOUGH TRANSPORT
1000 LBS | 450 KG

HANDLER™ SERIES UTILITY CARTS | STAINLESS STEEL

Handler Series Carts are the smart choice for maneuvering in confined spaces, even with the heaviest loads.

- Unique one-piece vertical handle offers more control for guiding the cart
- All swivel casters provide tight turn handling for crowded kitchens and make it easier to navigate into storage area corners.
- Angled "U"-shaped frame design provides superior structural strength
- All joints are fully welded to better withstand heavy loads and frequent use
- Stainless steel shelves reinforced for added strength
- No-mark, extra load, cushion tread wheels absorb impact, reducing strain
- Stainless steel is easy to clean and sanitize
- Leg bumpers protect walls and furniture

FACTORY INSTALLED OPTIONS (55):

- Offset perimeter bumpers
- Ground and polished joint welds
- Hi-Temp nylon casters, up to 400° F. (204° C.) 5" (127) 2 ea. fixed, 2 ea. swivel casters
- 8" (203) - 2 ea. fixed wheel



Freight Class: 125
Ships in: **5** days or less!

Model	# of Shelves	Shelf Size	Shelf Clearance	Top Shelf Height	Overall Size			Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m³)
					W	L	H		
4938	2	18" x 27" (457 x 686)	19" (483)	35-3/4" (908)	19-3/4" (502)	33" (838)	46-3/4" (1174)	66 (29.9)	10.4 (.40)
4939	3	18" x 27" (457 x 686)	10" (254)	35-3/4" (908)	19-3/4" (502)	33" (838)	46-3/4" (1174)	80 (36.3)	10.4 (.40)
4943	2	21" x 33" (533 x 838)	21" (533)	35-3/4" (908)	22-3/4" (578)	39" (991)	39-3/8" (1000)	88 (39.9)	9.3 (.36)
4944	3	21" x 33" (533 x 838)	11-3/8" (289)	35-3/4" (908)	22-3/4" (578)	39" (991)	39-3/8" (1000)	106 (48.1)	25.6 (.99)
4958	2	21" x 49" (533 x 1245)	21" (533)	35-3/4" (908)	22-3/4" (578)	55" (1397)	39-3/8" (1000)	123 (55.8)	32.3 (.90)
4959	3	21" x 49" (533 x 1245)	11-3/8" (289)	35-3/4" (908)	22-3/4" (578)	55" (1397)	39-3/8" (1000)	150 (68)	32.3 (.90)

Measurements in () denote metric millimeters, unless otherwise specified. Handle assembly required. Lake-Glide Casters: 5" (127) - all swivel.