

REGULAR and ADA-COMPLIANT DROP-IN PLATE DISPENSERS OPEN, SHIELDED and HEATED | STAINLESS STEEL

Fits into counters for attractive hidden dispensing with quick and easy access.

- Adjusting height level is easy and convenient. Simply detach and attach springs as needed with no tools required
- Easy glide design is non-stick for smooth operation
- Choose the type of dispenser that best fits your needs
 - **Open model** for economic dispensing
 - **Shielded** to protect against contaminants and plate chipping
 - **Heated** with adjustable thermostatic control to heat dishes (thermostat min- 100° F, max- 175° F)
- Stainless steel material is durable and easy to clean and sanitize
- Regular height models have 25" (635) stacking height capacity
- ADA-compliant height models have 22" (559) stacking height capacity

ELECTRICAL SPECIFICATIONS			
Models #6000, 6005, 6006, 6007, 6008, 600025, 600525, 600625, 600725, 600825	300 W	2.5 A	120 V
Models #6009, 6010, 6012, 600925, 601025, 601225	450 W	3.8 A	120 V
<i>208 / 240V, 60 Hz; 220V, 50 Hz also available, please specify.</i>			

ACCESSORIES (PAGE 75):

- Stainless Steel Dish Covers

 Freight Class: **92.5**
Ships in: **4** days or less!



Regular Model	ADA* Model	Accommodates Plate Sizes	Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m ³)
Open Models				
4000	400025	Up to 5" (127)	10 (4.5)	3.9 (.11)
4005	400525	5-1/8" to 5-3/4" (130 to 146)	11 (4.9)	3.9 (.11)
4006	400625	5-7/8" to 6-1/2" (149 to 165)	12 (5.4)	3.9 (.11)
4007	400725	6-5/8" to 7-1/4" (168 to 184)	12 (5.4)	3.9 (.11)
4008	400825	7-3/8" to 8-1/8" (200 to 206)	12 (5.4)	3.9 (.11)
4009	400925	8-1/4" to 9-1/8" (210 to 232)	15 (6.8)	6.9 (.19)
4010	401025	9-1/4" to 10-1/8" (235 to 257)	16 (7.3)	6.9 (.19)
4011	401125	10-1/4" to 11" (260 to 279)	17 (7.7)	6.9 (.19)
4012	401225	11-1/4" to 12-1/4" (286 to 311)	18 (8.2)	6.9 (.19)
Shielded Models				
5000	500025	Up to 5" (127)	15 (6.8)	3.9 (.11)
5005	500525	5-1/8" to 5-3/4" (130 to 146)	16 (7.3)	3.9 (.11)
5006	500625	5-7/8" to 6-1/2" (149 to 165)	17 (7.7)	3.9 (.11)
5007	500725	6-5/8" to 7-1/4" (168 to 184)	18 (8.2)	3.9 (.11)
5008	500825	7-3/8" to 8-1/8" (200 to 206)	20 (9.1)	3.9 (.11)
5009	500925	8-1/4" to 9-1/8" (210 to 232)	23 (10.4)	6.9 (.19)
5010	501025	9-1/4" to 10-1/8" (235 to 257)	24 (10.9)	6.9 (.19)
5011	501125	10-1/4" to 11" (260 to 279)	26 (11.8)	6.9 (.19)
5012	501225	11-1/4" to 12-1/4" (286 to 311)	29 (13.2)	6.9 (.19)
Heated Models				
6000	600025	Up to 5" (127)	20 (9.1)	3.9 (.11)
6005	600525	5-1/8" to 5-3/4" (130 to 146)	20 (9.1)	3.9 (.11)
6006	600625	5-7/8" to 6-1/2" (149 to 165)	20 (9.1)	3.9 (.11)
6007	600725	6-5/8" to 7-1/4" (168 to 184)	21 (9.5)	3.9 (.11)
6008	600825	7-3/8" to 8-1/8" (200 to 206)	23 (10.4)	3.9 (.11)
6009	600925	8-1/4" to 9-1/8" (210 to 232)	26 (11.8)	6.9 (.19)
6010	601025	9-1/4" to 10-1/8" (235 to 257)	28 (12.7)	6.9 (.19)
6011	601125	10-1/4" to 11" (260 to 279)	30 (13.6)	6.9 (.19)
6012	601225	11-1/4" to 12-1/4" (286 to 311)	32 (14.5)	6.9 (.19)

*ADA counter height models. Measurements in () denote metric millimeters, unless otherwise specified. Heated Models include 5' (1524) cord with NEMA L5-15P twist lock plug for 120 V. All Models can ship FedEx Ground and UPS.