

REGULAR TUBULAR FRAME PLATE DISPENSERS | STAINLESS STEEL



Award-winning plate dispensing with the sturdiness of tubular frame design.

- Lightweight open tubular frame design for back-of-the-house applications
- Adjusting height level is easy and convenient. Simply detach and attach springs as needed
- Easy glide design is non-stick for smooth operation
- All 4" swivel casters, 2 with brake, allow easy maneuverability
- Extra load casters provide additional support for full dispensers
- Stainless steel material is easy to clean

FACTORY INSTALLED OPTIONS:

- Round corner bumpers

ACCESSORIES (PAGE 79):

- Stainless Steel Dish Covers



Ships in: **4** days or less!

Non-Heated Model	Case Wt Lbs. (Kg)	Case Cube Cu. ft. (m³)	Heated Model	Case Wt Lbs. (Kg)	Case Cube Cu. ft. (m³)	Accom. Plate Size	Overall Size		
							W	L	H
2 Stack									
7200	65 (29.5)	18.9 (.5)	8200	73 (33.1)	18.9 (.5)	Up to 5" (127)	17-3/4" (451)	35-1/2" 902	38-5/16" (989)
7205	67 (30.4)	18.9 (.5)	8205	75 (34)	18.9 (.5)	5-1/8" to 5-3/4" (130 to 146)	17-3/4" (451)	35-1/2" 902	38-5/16" (989)
7206	68 (30.8)	18.9 (.5)	8206	78 (35.4)	18.9 (.5)	5-7/8" to 6-1/2" (149 to 165)	17-3/4" (451)	35-1/2" 902	38-5/16" (989)
7207	70 (31.8)	18.9 (.5)	8207	79 (35.8)	18.9 (.5)	6-5/8" to 7-1/4" (168 to 184)	17-3/4" (451)	35-1/2" 902	38-5/16" (989)
7208	74 (33.6)	18.9 (.5)	8208	86 (39)	18.9 (.5)	7-3/8" to 8-1/8" (187 to 206)	17-3/4" (451)	35-1/2" 902	38-5/16" (989)
7209	77 (34.9)	18.9 (.5)	8209	90 (40.8)	18.9 (.5)	8-1/4" to 9-1/8" (210 to 232)	17-3/4" (451)	35-1/2" 902	38-5/16" (989)
7210	80 (36.3)	18.9 (.5)	8210	93 (42.2)	18.9 (.5)	9-1/4" to 10-1/8" (235 to 257)	17-3/4" (451)	35-1/2" 902	38-5/16" (989)
7211	85 (38.3)	18.9 (.5)	8211	95 (42.8)	18.9 (.5)	10-1/4" to 11" (260 to 279)	17-3/4" (451)	35-1/2" 902	38-5/16" (989)
7212	90 (40.8)	18.9 (.5)	8212	96 (43.6)	18.9 (.5)	11-1/4" to 12-1/4" (286 to 311)	17-3/4" (451)	35-1/2" 902	38-5/16" (989)
3 Stack									
7300	90 (40.8)	21.3 (.6)	8300	101 (45.8)	21.3 (.5)	Up to 5" (127)	17-3/4" (541)	52-1/2" 1334	38-5/16" (989)
7305	92 (41.7)	21.3 (.6)	8305	104 (47.2)	21.3 (.5)	5-1/8" to 5-3/4" (130 to 146)	17-3/4" (541)	52-1/2" 1334	38-5/16" (989)
7306	95 (43.1)	21.3 (.6)	8306	106 (48.1)	21.3 (.5)	5-7/8" to 6-1/2" (149 to 165)	17-3/4" (541)	52-1/2" 1334	38-5/16" (989)
7307	97 (44)	21.3 (.6)	8307	109 (49.4)	21.3 (.5)	6-5/8" to 7-1/4" (168 to 184)	17-3/4" (541)	52-1/2" 1334	38-5/16" (989)
7308	102 (46.3)	21.3 (.6)	8308	115 (52.1)	21.3 (.5)	7-3/8" to 8-1/8" (187 to 206)	17-3/4" (541)	52-1/2" 1334	38-5/16" (989)
7309	106 (48.1)	21.3 (.6)	8309	120 (54.4)	21.3 (.5)	8-1/4" to 9-1/8" (210 to 232)	17-3/4" (541)	52-1/2" 1334	38-5/16" (989)
7310	110 (49.9)	21.3 (.6)	8310	124 (56.3)	21.3 (.5)	9-1/4" to 10-1/8" (235 to 257)	17-3/4" (541)	52-1/2" 1334	38-5/16" (989)
4 Stack									
7400	102 (46.3)	25.8 (.7)	8400	115 (52.1)	25.8 (.7)	Up to 5" (127)	31" (787)	31" 787	38-5/16" (989)
7405	106 (48.1)	25.8 (.7)	8405	120 (54.4)	25.8 (.7)	5-1/8" to 5-3/4" (130 to 146)	31" (787)	31" 787	38-5/16" (989)
7406	107 (48.5)	25.8 (.7)	8406	121 (54.9)	25.8 (.7)	5-7/8" to 6-1/2" (149 to 165)	31" (787)	31" 787	38-5/16" (989)
7407	108 (49)	25.8 (.7)	8407	122 (55.3)	25.8 (.7)	6-5/8" to 7-1/4" (168 to 184)	31" (787)	31" 787	38-5/16" (989)
7408	130 (59)	25.8 (.7)	8408	146 (66.2)	25.8 (.7)	7-3/8" to 8-1/8" (187 to 206)	31" (787)	31" 787	38-5/16" (989)
7409	135 (61.2)	25.8 (.7)	8409	152 (69)	25.8 (.7)	8-1/4" to 9-1/8" (210 to 232)	31" (787)	31" 787	38-5/16" (989)
7410	140 (63.5)	25.8 (.7)	8410	157 (71.2)	25.8 (.7)	9-1/4" to 10-1/8" (235 to 257)	31" (787)	31" 787	38-5/16" (989)

#'s in () denote millimeters unless noted. Lake-Glide® Casters: 4" (102) - All swivel, 2 ea. w/brake, extra-load. Heated Models include 6' (1829) cord w/ 5-15P NEMA plug for 120 V except Models 8409 and 8410 (5-20P).

ELECTRICAL SPECIFICATIONS 208 / 240V, 60 Hz; 220V, 50 Hz also available, please specify.

Models #776, 777, 778, 786, 787, 788, 796, 797

900 W 7.5 A 120 V

Models #8210, 8212, 8300, 8305, 8306, 8400, 8405, 8406, 8407, 8408, 8409, 8410

900 W 7.5 A 120 V

Models #8200, 8205, 8206, 8207, 8208,

600 W 5.0 A 120 V

