

REGULAR and ADA-COMPLIANT ADJUST-A-FIT® DROP-IN PLATE DISPENSERS: OPEN, SHIELDED and HEATED | STAINLESS STEEL

Fits into counter cutout for attractive hidden dispensing with quick and easy access.

- Adjust-a-fit diameter hand adjustment of 3 1/4" (83) allows flexibility for varying dish sizes
- Adjusting height level is easy and convenient. Simply detach and attach springs as needed with no tools required
- Choose the type of dispenser that best fits your needs
 - **Open model** for economic dispensing
 - **Shielded** to protect against contaminants and plate chipping
 - **Heated** with adjustable thermostatic control to heat dishes (thermostat min- 100° F, max- 175° F)
- Stainless steel material is durable and easy to clean and sanitize
- Regular height models have 25" (635) stacking height capacity
- ADA-compliant height models have 22" (559) stacking height capacity



Freight Class: **92.5**

Regular Models Ship in: **4** days or less!

ADA Models Ship in: **10** days or less!



Standard Height Model	ADA* Model	Accommodates Plate Sizes	Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m ³)
Open Models				
902	90225	2-3/4" to 6" (70 to 152)	13 (5.9)	3.9 (.11)
912	91225	4-1/4" to 7-1/2" (108 to 191)	15 (6.8)	3.9 (.11)
922	92225	6-1/2" to 9-3/4" (165 to 248)	18 (8.2)	6.9 (.19)
932	93225	8-3/4" to 12" (222 to 305)	20 (9.1)	6.9 (.19)
1942	194225	10" to 13-1/4" (254 to 337)	21 (9.6)	6.9 (.19)
Shielded Models				
903	90325	2-3/4" to 6" (70 to 152)	20 (9.1)	3.9 (.11)
913	91325	4-1/4" to 7-1/2" (108 to 191)	22 (10.0)	3.9 (.11)
923	92325	6-1/2" to 9-3/4" (165 to 248)	27 (12.2)	6.9 (.19)
933	93325	8-3/4" to 12" (222 to 305)	31 (14.1)	6.9 (.19)
1943	194325	10" to 13-1/4" (254 to 337)	32 (14.5)	6.9 (.19)
Heated Models				
914	91425	4-1/4" to 7-1/2" (108 to 191)	25 (11.3)	3.9 (.11)
924	92425	6-1/2" to 9-3/4" (165 to 248)	30 (13.6)	6.9 (.19)
934	93425	8-3/4" to 12" (222 to 305)	34 (15.4)	6.9 (.19)
1944	194425	10" to 13-1/4" (254 to 337)	35 (15.9)	6.9 (.19)

*ADA counter height models. Measurements in () denote metric millimeters, unless otherwise specified. Heated Models include 5' (1524) cord with L5-15P NEMA twist lock plug for 120 V. All models can ship FedEx Ground or UPS.

HEIGHT AND RING CUT OUT INFORMATION (INCLUDES ADA COMPLIANT MODELS)

Regular Model	Height to Ring	ADA Models	Height to Ring	Ring Diameter	Counter Cut Out Size
902	27-3/4" (705)	90225	24-3/4" (629)	10" (254)	9-1/8" (232)
903	28" (711)	90325	25" (635)	10" (254)	9-1/8" (232)
912	27-3/4" (705)	91225	24-3/4" (629)	11-1/2" (292)	10-5/8" (270)
913, 914	28" (711)	91325, 91425	25" (635)	11-1/2" (292)	10-5/8" (270)
922	27-3/4" (705)	92225	24-3/4" (629)	13-3/4" (349)	12-7/8" (327)
923, 924	28" (711)	92325, 92425	25" (635)	13-3/4" (349)	12-7/8" (327)
932	27-3/4" (705)	93225	24-3/4" (629)	16" (406)	15-1/8" (384)
933, 934	28" (711)	93325, 93425	25" (635)	16" (406)	15-1/8" (384)
1942	27-3/4" (705)	194225	24-3/4" (629)	17-1/16" (432)	16-1/4" (413)
1943, 1944	28" (711)	194325, 194425	25" (635)	17-1/16" (432)	16-1/4" (413)