

# REGULAR and ADA-COMPLIANT ADJUST-A-FIT® DROP-IN PLATE DISPENSERS: OPEN, SHIELDED and HEATED | STAINLESS STEEL

*Fits into counter cutout for attractive hidden dispensing with quick and easy access.*

- Adjust-a-fit diameter hand adjustment of 3 1/4" (83) allows flexibility for varying dish sizes
- Adjusting height level is easy and convenient. Simply detach and attach springs as needed with no tools required
- Choose the type of dispenser that best fits your needs
  - **Open model** for economic dispensing
  - **Shielded** to protect against contaminants and plate chipping
  - **Heated** with adjustable thermostatic control to heat dishes (thermostat min- 100° F, max- 175° F)
- Stainless steel material is durable and easy to clean and sanitize
- Regular height models have 25" (635) stacking height capacity
- ADA-compliant height models have 22" (559) stacking height capacity



Freight Class: **92.5**

Regular Models Ship in: **4** days or less!

ADA Models Ship in: **10** days or less!



Standard Height Model	ADA* Model	Accommodates Plate Sizes	Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m <sup>3</sup> )
<b>Open Models</b>				
902	90225	2-3/4" to 6" (70 to 152)	13 (5.9)	3.9 (.11)
912	91225	4-1/4" to 7-1/2" (108 to 191)	15 (6.8)	3.9 (.11)
922	92225	6-1/2" to 9-3/4" (165 to 248)	18 (8.2)	6.9 (.19)
932	93225	8-3/4" to 12" (222 to 305)	20 (9.1)	6.9 (.19)
1942	194225	10" to 13-1/4" (254 to 337)	21 (9.6)	6.9 (.19)
<b>Shielded Models</b>				
903	90325	2-3/4" to 6" (70 to 152)	20 (9.1)	3.9 (.11)
913	91325	4-1/4" to 7-1/2" (108 to 191)	22 (10.0)	3.9 (.11)
923	92325	6-1/2" to 9-3/4" (165 to 248)	27 (12.2)	6.9 (.19)
933	93325	8-3/4" to 12" (222 to 305)	31 (14.1)	6.9 (.19)
1943	194325	10" to 13-1/4" (254 to 337)	32 (14.5)	6.9 (.19)
<b>Heated Models</b>				
914	91425	4-1/4" to 7-1/2" (108 to 191)	25 (11.3)	3.9 (.11)
924	92425	6-1/2" to 9-3/4" (165 to 248)	30 (13.6)	6.9 (.19)
934	93425	8-3/4" to 12" (222 to 305)	34 (15.4)	6.9 (.19)
1944	194425	10" to 13-1/4" (254 to 337)	35 (15.9)	6.9 (.19)

\*ADA counter height models. Measurements in ( ) denote metric millimeters, unless otherwise specified. Heated Models include 5' (1524) cord with L5-15P NEMA twist lock plug for 120 V. All models can ship FedEx Ground or UPS.

## HEIGHT AND RING CUT OUT INFORMATION (INCLUDES ADA COMPLIANT MODELS)

Regular Model	Height to Ring	ADA Models	Height to Ring	Ring Diameter	Counter Cut Out Size
902	27-3/4" (705)	90225	24-3/4" (629)	10" (254)	9-1/8" (232)
903	28" (711)	90325	25" (635)	10" (254)	9-1/8" (232)
912	27-3/4" (705)	91225	24-3/4" (629)	11-1/2" (292)	10-5/8" (270)
913, 914	28" (711)	91325, 91425	25" (635)	11-1/2" (292)	10-5/8" (270)
922	27-3/4" (705)	92225	24-3/4" (629)	13-3/4" (349)	12-7/8" (327)
923, 924	28" (711)	92325, 92425	25" (635)	13-3/4" (349)	12-7/8" (327)
932	27-3/4" (705)	93225	24-3/4" (629)	16" (406)	15-1/8" (384)
933, 934	28" (711)	93325, 93425	25" (635)	16" (406)	15-1/8" (384)
1942	27-3/4" (705)	194225	24-3/4" (629)	17-1/16" (432)	16-1/4" (413)
1943, 1944	28" (711)	194325, 194425	25" (635)	17-1/16" (432)	16-1/4" (413)