CNF0201/202

**UNF0300** 



W 16.25" D 24" H 35" W 41.3 D 61 H 106.7 cm 70/50°F \*222lbs/101 kg daily at 90/70°F



W 16.25" D 24" H 42" W 41.3 D 61 H 106.7 cm \*315lbs/143 kg daily at \*315lbs/143 kg daily at 70/50°F \*222lbs/101 kg daily at 90/70°F

| Model         | type   | Cooming | Electrical  | Weight           | Model       |
|---------------|--------|---------|-------------|------------------|-------------|
| CNF0201A-161L | Nugget | Air     | 115v/60Hz/1 | 184 lbs / 127 kg | RNS12A-161  |
| CNF0201A-161  | Nugget | Air     | 115v/60Hz/1 | 184 lbs / 127 kg | RNS12AT-161 |
| CNF0201A-161N | Nugget | Air     | 115v/60Hz/1 | 184 lbs / 127 kg |             |
| CNF0202A-161L | Nugget | Air     | 115v/60Hz/1 | 198 lbs / 90 kg  | RNS20A-161  |
| CNF0202A-161  | Nugget | Air     | 115v/60Hz/1 | 198 lbs / 90 kg  | RNS20AT-161 |
| CNF0202A-161N | Nugget | Air     | 115v/60Hz/1 | 198 lbs / 90 kg  |             |
| CNF0201A-251L | Nugget | Air     | 230v/50hz/1 | 184 lbs / 127 kg | RNS12A-251  |
| CNF0201A-251  | Nugget | Air     | 230v/50hz/1 | 184 lbs / 127 kg | RNS12AT-251 |
| CNF0202A-251L | Nugget | Air     | 230v/50hz/1 | 198 lbs / 90 kg  | RNS20A-251  |
| CNF0202A-251  | Nugget | Air     | 230v/50hz/1 | 198 lbs / 90 kg  | RNS20AT-251 |

Note Dispensing Type: "-161L" is lever activated and "-161" is sensor activated. 3 dispensing options: ice, water, and ice/water together. Bin capacity is 10lbs/4.5 kg for CNF0201 and 20lbs/9 kg for CNF0202. Legs sold separately, see kit K00345001 below. . Use cleaner (000000084) only with this model. Not compatible with iAuCS. Price list performance rating is 60hz data. -161N is a solid front panel option. Push buttons are covered to make machine completely touchless.



W 22.2" D 29.2" H 36" W 56.4 D 74.2 H 76.2 cm

| Kit       | Description  | Electrical | Shipping<br>Weight |  |
|-----------|--|------------|--------------------|--|
| K00345001 | Leg kit<br>(Adjustable: 4.5" – 6.5" / 11.43-16.5 cm)                       | _          | 3 lbs./1.3 kg      |  |
| K00377    | Kit to convert from lever activated to touchless sensing dispensing option | 115/60/1   | 3 lbs./1.3 kg      |  |
| K00453    | CNF Stand  | _          | 100 lbs./45.4 kg   |  |

K00453 has been rated to accommodate weight of 850 lbs. Can be used with the S-150 (without the legs) with either the iT0420 or iT620 Indigo NXT ice machine

| NF0200 |                                |
|--------|--------------------------------|
| ⊃      | UNF0200 W 19.69" D 25.98" H 33 |

W 50 D 66 H 84.3 cm \*213 lbs / 97 kg daily at 70/50°F \*164 lbs /74 kg daily at 90/70°F

| Model         | Ice type | Cooling | Electrical  | Shipping Weight | Replaces Model |
|---------------|----------|---------|-------------|-----------------|----------------|
| UNF0200A-161  | Nugget   | Air     | 115v/60Hz/1 | 157 lbs / 72kg  | RNS0244A-161   |
| UNK0200AZ-251 | Nugget   | Air     | 230v/50hz/1 | 157 lbs / 72kg  | RNS0244AZ-251  |

Application ice storage capacity: 30 lbs /14kg. Measured cubic volume 1.03. Storage capacity is AHRI certified. Application storage capacity measured 90% of total volume in cu. ft x 22 lbs/ft3 Includes 6'/1.8 m power cord with NEMA 5-15P plug.

Use cleaner (000000084) only with this model. Not compatible with iAuCS, LuminIce II, or casters. Price list performance rating is 60hz data.50 Hz Electric Connection:

Add Z for Bare Lead cord.

| m.              |                  |
|-----------------|------------------|
| amananan        |                  |
| IINEO300 W 20 0 | K" D 27 17" U 20 |

UNF0300 W 29.06" D 27.17" H 39.52" W 73.8 D 69 H 100.4 cm \*330 lbs / 150 kg daily at 70/50° \*275 lbs / 125 kg daily at 90/70°

| UNF0300A-161  | Nugget | Air | 115v/60Hz/1 | 224 lbs / 102 kg | RNS0385A-161  |
|---------------|--------|-----|-------------|------------------|---------------|
| UNK0300AZ-251 | Nugget | Air | 230v/50hz/1 | 224 lbs / 102 kg | RNS0385AZ-251 |

Application storage capacity: 60 lbs / 27kg. Measured cubic volume 2.04. Storage capacity is AHRI certified. Application storage capacity measured 90% of total volume in cu. ft x 22 lbs/ft3 Includes 6'/1.8 m power cord with NEMA 5-15P plug. Use cleaner (000000084) only with this model. Not compatible with iAuCS, LuminIce II, or casters. Price list performance rating is 60hz data.

50 Hz Electric Connection: Add Z for Bare Lead cord.