

Models

- ☐ IDT0750WM ☐ IDT0900WM
☐ IYT0900WM




Model shown-
IDT0750WM



Model shown-
IDT0900WM

Stainless Steel:

Top Cover
 Side Panels
 Back Panel
 Bulkhead
 Brackets
 Fasteners



Stainless Steel Bulkhead



Isolation switch

These 30" (76.2cm) wide models offer special Marine specifications. Choose between the series 750 and 900 water-cooled models. Ice production from 661 to 879 lbs (300 to 399 kg) of ice per day.

- **Isolation switch** immediately cuts power to the entire unit.
- **Indigo®NXT feature set** including automatic cleaning that returns to the ice making process without manual intervention.
- **Cupra-nickel condenser** adds protection from salt water.
- **Completely sealed unit:** front, back, top and sides.
- Meets **USPHS** specifications.
- All exterior panels made from **High Grade Stainless Steel**.
- Check current price list for available ice type and electrical options.



Need a Marine Bin?

Please contact the Manitowoc Ice sales department for details.



Model Shown
IBW-M4 Marine Bin

Ice Shape




Half Dice
 $\frac{3}{8}" \times 1\frac{1}{8}" \times \frac{7}{8}"$
 (0.95 x 2.86 x 2.22 cm)



Dice
 $\frac{7}{8}" \times \frac{7}{8}" \times \frac{7}{8}"$
 (2.22 x 2.22 x 2.22 cm)





- Ⓐ Electrical Entrance (2) Options
- Ⓑ 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet
- Ⓒ 1/2" (1.27 cm) F.P.T. Ice Making Water Drain
- Ⓓ 1/2" (1.27 cm) F.P.T. Water Condenser Outlet
- Ⓔ 3/8" (0.95 cm) F.P.T. Water Condenser Inlet
- Ⓕ 1/2" (1.27 cm) Auxiliary Base Drain Socket

Installation Note: Minimum 2-3/4" clearance at back.

Series iT0750W & iT0900W Operating Limits

- Ambient Temperature Range:
40° to 110°F (4.4° to 43.3°C)
- Water Temperature Range:
Potable Water: 40° to 90°F (4.4° to 32.3°C)
- Water Pressure Ice Maker Water In:
Min. 20 psi (137.9 kPa), Max. 80 psi (551.1 kPa)
- Condenser Inlet Water In:
Min. 20 psi (137.9 kPa), Max. 276 psi (1902.95 kPa)

Machine Ice Types & Electrical Options

iT0750WM	
Dice Cube	261
iT0900WM	
Dice Cube	261
Half Dice Cube	261

Series iT0750WM
21.50" H x 30.00" W x 24.50" D
54.6 cm x 76.2 cm x 62.2 cm
Order ice storage bin separately. Note: Placing iT0750W ice machine on non-Manitowoc Ice bin or "F" model Manitowoc Ice bin, requires installation of ice deflector K-00347.

Electric: 208-230/60/1 standard.
Min. circuit ampacity: 7.9
Max. fuse size: 15 amps
BTU Per Hour:
12,800 (average) 13,700 (peak)

Series iT0900WM
26.50" H x 30.00" W x 24.50" D
67.3 cm x 76.2 cm x 62.2 cm
Order ice storage bin separately. Note: Placing iT0900W ice machine on non-Manitowoc Ice bin or "F" model Manitowoc Ice bin, requires installation of ice deflector K-00347.

Electric: 208-230/60/1 standard.
Min. circuit ampacity:
8.8 - 1ph
Max. fuse size:
15 amps - 1ph
BTU Per Hour:
12,700 (average) 14,800 (peak)

Specifications

Model	Ice Shape	Ice Production 24 Hours		Power Usage kWh/100 lbs. @ 32° Air/21° C water 90° Air/70° F water	Potable Water Usage/100 lbs. 45.4 kgs. of Ice
		70° Air/ 50° F Water 21° Air/10° C Water	90° Air/ 70° F Water 32° Air/21° C water		
IDT0750WM	dice	703 lbs.	600 lbs.	4.07	20 Gal.
		319 kgs	272 kgs		75.7 L
IDT0900WM	dice	780 lbs.	665 lbs.	4.02	19 Gal.
		354 kgs	302 kgs		71.9 L
IYT0900WM	half-dice	785 lbs.	665 lbs.	4.02	19 Gal.
		356 kgs	302 kgs		71.9 L

Water-cooled Condenser water usage 100lbs/45.4kg of Ice: iT0750 and iT0900 135 gal / 511 L

This product is hermetically sealed and contains fluorinated greenhouse gas R410a.

Accessories

LuminIce® II Virus and Bacteria Inhibitor

controls viruses and
bacteria inside the ice
machine



Arctic Pure® Plus Water Filters

reduce sediments and
chlorine contaminants
down to .5 microns.
Use with a Pre-filter is
recommended.



IAuCS®

schedules and performs routine
ice machine
cleaning
automatically.



External Scoop Holder

protect the ice scoop with
the NSF
approved
versatile
scoop
holder.



Welbilt reserves the right to make changes to the design or specifications without prior notice.

2110 South 26th Street
Manitowoc, WI 54220

Tel: 1.920.682.0161
Fax: 1.920.683.7589

www.manitowocice.com
6779D
10/2021

 **WELBILT®**