


IT1900 Series



W 48" D 24.5" H 29.5"
W 121.9 D 62.2 H 74.9 cm

*1965 lbs / 891 kg at 70/50°F
*1535 lbs / 696 kg at 90/70°F



Not Stackable

Model	Ice type	Cooling	Electrical	Shipping Weight	Replaces Model
IRT1900A-261E	Regular	Air	208-230v/60hz/1	317 lbs / 144 kg	IRT1900A-261
IRT1900A-263E	Regular	Air	208-230v/60hz/3	317 lbs / 144 kg	IRT1900A-263
IRT1900N-261E	Regular	Remote	208-230v/60hz/1	324 lbs / 147 kg	IRT1900N-261A
IRT1900N-263E	Regular	Remote	208-230v/60hz/3	324 lbs / 147 kg	IRT1900N-263
IRT1900N-263EX	Regular	Remote	208-230v/60hz/3	324 lbs / 147 kg	IRT1900N-263X
IDT1900A-261E	Dice	Air	208-230v/60hz/1	317 lbs / 144 kg	IDT1900A-261
IDT1900A-263E	Dice	Air	208-230v/60hz/3	317 lbs / 144 kg	IDT1900A-263
IDT1900W-261E	Dice	Water	208-230v/60hz/1	319 lbs / 145 kg	IDT1900W-261A
IDT1900W-263E	Dice	Water	208-230v/60hz/3	319 lbs / 145 kg	IDT1900W-263
IDT1900N-261E	Dice	Remote	208-230v/60hz/1	324 lbs / 147 kg	IDT1900N-261A
IDT1900N-263E	Dice	Remote	208-230v/60hz/3	324 lbs / 147 kg	IDT1900N-263
IYT1900A-261E	1/2 Dice	Air	208-230v/60hz/1	321 lbs / 146 kg	IYT1900A-261
IYT1900A-263E	1/2 Dice	Air	208-230v/60hz/3	321 lbs / 146 kg	IYT1900A-263
IYT1900W-261E	1/2 Dice	Water	208-230v/60hz/1	322 lbs / 146 kg	IYT1900W-261A
IYT1900W-263E	1/2 Dice	Water	208-230v/60hz/3	322 lbs / 146 kg	IYT1900W-263
IYT1900N-261E	1/2 Dice	Remote	208-230v/60hz/1	330 lbs / 150 kg	IYT1900N-261A
IYT1900N-261EX	1/2 Dice	Remote	208-230v/60hz/1	335 lbs / 152 kg	IYT1900N-261X
IYT1900N-263E	1/2 Dice	Remote	208-230v/60hz/3	330 lbs / 150 kg	IYT1900N-263
IYT1900N-263EX	1/2 Dice	Remote	208-230v/60hz/3	335 lbs / 152 kg	IYT1900N-263X
IRT1900A-251E	Regular	Air	230v/50hz/1	317 lbs / 144 kg	IRT1900A-251
IDT1900A-251E	Dice	Air	230v/50hz/1	317 lbs / 144 kg	IDT1900A-251
IDT1900N-251E	Dice	Remote	230v/50hz/1	324 lbs / 147 kg	IDT1900N-251
IYT1900A-251E	1/2 Dice	Air	230v/50hz/1	321 lbs / 146 kg	IYT1900A-251

If factory installed LuminIce II not offered, use aftermarket kit found on page 24.


Recommended Bins: D970, F1300, F1325, F1650, FC1350 (See page 19).

See pages 22-23 for required adapters and deflectors.

¹Use JCT1500remote condenser and RL()R-410A tubing kit (see page 10). Kit K0034900 ice deflector must be ordered separately if used with: non-Manitowoc bins, Manitowoc F-Style bins.


Price list performance rating is 60hz data. Refer to individual 50hz spec sheets for 50hz performance rating.

S-3000 Series



W 48" D 31" H 36"
W 121.9 D 78.7 H 91.4 cm

*3200 lbs / 1451 kg daily at 70/50°F
*2584 lbs / 1172 kg daily at 90/70°F



Not Stackable

Recommended Bins: F1300, F1325, F1650, FC1350 (See page 19). See pages 22-23 for required adapters and deflectors.

Not for use with iAuCS cleaning system or LuminIce II.

Kit K00391 ice deflector must be ordered separately if used with:

non-Manitowoc bins, Manitowoc 48"/121.9 cm & 60"/152.4 cm F-Style bins.

H = High pressure valve regulates from 20 psi to 350 psi or 137.9 kPa to 2413.2 kPa.

Model	Ice type	Cooling	Electrical	Shipping Weight	Replaces Model
SDT3000W-263H	Dice	Water	208-230v/60hz/3	501lbs/227kg	SD3303W3-263HP
SYT3000W-263H	1/2 Dice	Water	208-230v/60hz/3	516 lbs / 234 kg	SY3305W3-263HP

★ ENERGY STAR® Qualified Model

Air filter standard on self-contained air-cooled ice cube machines.

*Daily ice production based on Half-Dice air-cooled condenser model at air temperature/water temperature.