


RFF1300



W 30" D 23.6" H 27.4"  
 W 76.2 D 59.9 H 70.0 cm  
 \*1264 lbs / 573 kg daily at 70/50F  
 \*951 lbs / 431 kg daily at 90/70F

Model	Ice type	Cooling	Electrical	Shipping Weight	Replaces Model
<b>RFF1300A-261</b>	Flake	Air	208-230v/60hz/1	263 lbs / 119 kg	<b>RFS1200A-261</b>
<b>RFF1300W-261</b>	Flake	Water	208-230v/60hz/1	263 lbs / 119 kg	<b>RFS1200W-261</b>
<b>RFK01300AZ-251</b>	Flake	Air	230v/50hz/1	263 lbs / 119 kg	<b>RFS1200AZ-251</b>
<b>RFK01300WZ-251</b>	Flake	Water	230v/50hz/1	263 lbs / 119 kg	<b>RFS1200WZ-251</b>



**Recommended Bins:** D570, D970


See pages 22-23 for required adapters.

Use cleaner (000000084) only with this model.

Price list performance rating is 60hz data.

Not compatible with SPA/SFA dispensers, iAuCS, or LuminIce® II **Not Stackable**  
 50 Hz Electric Connection: Add Z for Bare Lead cord.

RFF1220 / RFS1278



W 22" D 23.6" H 26"  
 W 55.9 D 59.9 H 66.0 cm  
 \*1092 lbs / 495 kg daily at 70/50°F  
 \*958 lbs / 435 kg daily at 90/70°F

<b>RFF1220C-261</b>	Flake	Remote	208-230v/60hz/1	186 lbs / 84 kg	<b>RFS1278C-261</b>
<b>RFS1278C-251</b>	Flake	Remote	230v/50hz/1	186 lbs / 84 kg	<b>n/a</b>

\*\*Requires RCUF1200 (60hz) or RJC 1275 (50hz) remote condensing unit and RC51 tubing kit. (see page 12)



**Recommended Bins:** D420, D970.


See pages 22-23 for required adapters.

Use cleaner (000000084) only with this model.

Price list performance rating is 60hz data.

Not compatible with SPA/SFA dispensers, iAuCS, or LuminIce II. **Not Stackable**


RFF2200C / RF2378C



W 30" D 23.6" H 27.4"  
 W 76.2 D 59.9 H 70.0 cm  
 \* 2063 lbs / 936 kg daily at 70/50°F  
 1702 lbs / 772 kg daily at 90/70°F

<b>RFF2200C-261</b>	Flake	Remote	208-230v/60hz/1	279 lbs / 127 kg	<b>RFS2378C-261</b>
<b>RFS2378C-251</b>	Flake	Remote	230v/50hz/1	279 lbs / 127 kg	<b>n/a</b>

\*\*Requires RCUF2200 (60hz) or RJC2375 (50hz) remote condensing unit and RC51 tubing kit. (see page 12)



**Recommended Bins:** D970, F1300, F1325, F1650, FC1350

See pages 22-23 for required adapters.

Use cleaner (000000084) only with this model.

Price list performance rating is 60hz data.

Not compatible with SPA/SFA dispensers, iAuCS, or LuminIce II. **Not Stackable**

★ **ENERGY STAR® Qualified Model**

\*Daily ice production based on air-cooled condenser model at air temperature/water temperature.