WE CREATE. WE INNOVATE.



Enclosed Facade 140 (EF140G) Gas Fired Ovens



Pizza Capacity

Cooking Surface = 16.36 sq. ft. Pizza Capacity 8" = 10-12 Pizza Capacity 10" = 9-11 Pizza Capacity 12" = 8-10

Pizza Capacity 16" = 6-7

Venting

The oven is vented through an 8" round duct collar. The Neapolitan gas ovens can be installed with a listed exhaust hood system or with a direct vent exhaust duct vented outside without an exhaust hood, but must be installed with a power exhausted vent. Cubic Feet per Minute: 150CFM Static Pressure: 0.01"W.C

Clearance Requirements

2" Minimum clearance for Combustibles on all sides.

0" Minimum clearance for Non Combustibles..

Overview

Our 140 Enclosed Facade model, which is designed specifically to accommodate the high-volume pizza making of a true pizzaiolo. Maximize your kitchen space with an Enclosed Facade oven. The oven is built directly into your wall and has an optional wood storage trim kit. The 140 features a 55.12 inch deck. The dome and deck consist of refractory bricks with 4 inches of multi-layered insulation in the dome and 8 inches in the deck. The oven features a 24 inch by 9.5 inch opening along with a stainless steel flue collar.

The oven requires a 2" tolerance in all directions, and comes standard with a fire-rated tile clay dome. The 140 Enclosed Facade model also features a 12 inch landing on the opening, as well as a control located between the deck and the top of the dome for getting a precise reading. Oven can be vented directly to the roof or vented through a powered type 1 exhaust hood with approved exhaust duct in accordance with all local and national codes. For wood burning ovens, they must be vented as a solid fuel burning appliance and must be installed following a manner that obeys all local and national codes and is acceptable to authority having jurisdiction.

Gas Requirements

Gas connections 3/4" NPT per burner, quick-disconnect flex gas hose recommended. Pressure required 10" - 14" W.C. (Water Column) at the gas valve. 84,000 BTU's per burner.

Electrical Requirements

120V/ Single Phase / 12 Amps 9 ft. power cable integrated.

Standard Features

Touch screen

Dome Terra Cotta Finish
Turbo Burner
Brick Deck
Door
Stainless Steel Flue Collar/Adapter
Steel Stand
Powder Coating
2 Year Deck and Dome Warranty
1 Year Parts and Labor Warranty

Shipping Dimensions

Actual Weight: 4,200 LBS Crated Weight: 4,600 LBS Crated Width: 83" Crated Depth: 96" Crated Height: 82"

Optional Features

Stainless Steel Mask
Stainless Steel Stand
Gas Burning Accessories
Burner Position (Left/Right)
Custom Tile Applications
Exhaust Fan
All Fuel Grease Duct
Aluminum Oven Tools
Integrated Exhaust System
Interior Lights

Approved





ANSI 283.1° CSA 1.8


WE CREATE. WE INNOVATE.




Enclosed Facade 140 (EF140G)

Gas Fired Ovens

Top View




Plan View




Legend

- **C-**Controls `
- E-Electrical Connection Flexable Cord
- F-Flue Collar
- **G-**Gas Connection
- S-Storage Shelf

Front View



Side View



Notes

An ongoing program of product improvement may require us to change specifications without notice.

All ovens are designed to suit commercial usage.

Spec dimensions to be +/ - 0.50 inch.

Oven sizes refer to dome interior size.

All Marra Forni ovens are ETL, and VPN approved.

All oven Freight Class 77.5 and must be shipped LTL.

All Marra Forni ovens are approved with a door that is used as a fire suppressor. The door completely closes the front cavity of the oven. Sprinkler/ansul systems not required.

Learn about gas, electrical, venting and clearance requirements at MARRAFORNI.







