



Item # \_\_\_\_\_

Job \_\_\_\_\_

## SUPER ERECTA SHELF® STEM CASTER CARTS – SOLID SHELVES

- **Stem Caster Carts** combine Super Erecta Shelf® solid shelving features with the mobility of stem casters to provide a high-quality, strong and versatile material handling cart.
- **Variety of Casters Available:** Select the caster that allows the right combination of rollability and maneuverability to suit your requirements. Casters are available in swivel, rigid or brake types. All Metro casters are non-marking and come complete with a 3 1/2" donut bumper. Refer to sheet #11.20 for additional caster information.
- **Strength:** Two-fold thickness of 18-gauge steel forms 1/8" raised edges on all four sides of the shelving. This ship's edge gives all-around rigidity and high-strength. Sturdy aluminum castings firmly lock the corners to the posts.
- **Sanitary:** The raised ship's edge on all four sides and at the corners contains spillage, minimizes contamination and permits easier clean-up. Embossed or louvered/embossed shelf designs allow air circulation under packages and containers.
- **Fast, Secure Assembly:** Post has rolled, circular grooves along its entire height at 1" (25mm) intervals. A patented, tapered split sleeve (plastic or aluminum) snaps together around each post. Tapered openings in the shelf corners slide over the tapered split sleeves providing a positive lock. Cart is assembled in minutes without the use of nuts or bolts and without the use of any special tools.
- **Adjustability:** Shelves can be adjusted at 1" (25mm) intervals along the entire height of the post.



Job \_\_\_\_\_

SUPER ERECTA SHELF®  
STEM CASTER CARTS –  
SOLID SHELVES



Dimensions

**Standard Units:**

Consist of four shelves, posts, plastic split sleeves\*, donut bumpers and designated casters.


**With Galvanized Flat Solid Shelves & Plated Posts**

62" (1575mm) Posts — Overall Height 68" (1730mm)

Solid Shelf				Cat. No. with Casters			
Width (in.)	(mm)	Length (in.)	(mm)	Four 5M	Two 5M Two 5MB	Four 5MP	Two 5MP Two 5MPB
18	455	36	910	F336AG	F336BG	F336DG	F336EG
18	455	48	1220	F356AG	F356BG	F356DG	F356EG
18	455	60	1525	F366AG	F366BG	F366DG	F366EG
21	530	36	910	F436AG	F436BG	F436DG	F436EG
21	530	48	1220	F456AG	F456BG	F456DG	F456EG
21	530	60	1525	F466AG	F466BG	F466DG	F466EG
24	610	36	910	F536AG	F536BG	F536DG	F536EG
24	610	48	1220	F556AG	F556BG	F556DG	F556EG
24	610	60	1525	F566AG	F566BG	F566DG	F566EG

**Posts**

Height		Approx. Pkd. Wt		Cat. No. Plated
(in.)	(mm)	(lbs.)	(kg)	
13 <sup>7</sup> / <sub>8</sub>	352	1	0.5	13UP
33 <sup>7</sup> / <sub>8</sub>	835	2	0.9	33UP
54	1370	3	1.4	54UP
62	1575	3 <sup>1</sup> / <sub>2</sub>	1.6	63UP
74	1880	4	1.8	74UP
86	2185	5	2.3	86UP



**SiteSelect™ Posts are grooved at 1" (25mm) increments and numbered at 2" (50mm) increments. Posts are double-grooved every 8" (203mm) for easy identification.**

\* Aluminum split sleeves are recommended when unit will be towed, transported over the road or otherwise subjected to vibration or jolting. To order, see catalog sheet #10.06 or price list.

**Load Rating:** 3 times the caster load rating, or not to exceed 800 lbs. (363 kg) per cart.

To Order By Components

1. Order shelves from catalog sheet #10.20 or price list. (Will be packed with plastic split sleeves.\*)
2. Order stem casters from catalog sheet #11.20 or price list. Donut bumper comes with caster.
3. Order posts from table at left. Except for rigid casters, posts are shipped assembled with caster and donut bumper.

**IMPORTANT:** When ordering by components remember that stability decreases as the ratio of height to width increases. Units should be kept as wide and low as possible.

Manufactured by:



**InterMetro Industries Corporation**  
North Washington Street, Wilkes-Barre, PA 18705  
Phone: 570-825-2741 • Fax: 570-825-2852  
For Product Information Call: 1-800-433-2232  
Visit Our Web Site: www.metro.com

L02-038  
Rev. 11/00  
Printed in U.S.A.

Information and specifications are subject to change without notice. Please confirm at time of order.

