



Item # _____

We put space to work.

Job _____

MetroMax® Q Polymer/Wire Shelving Starter and Add-on Units.

Quick-to-adjust, corrosion resistant shelving constructed of removable polymer open grid shelf mats, wire shelf frames, and corner releases. Shelf frames have an epoxy coating over an electroplated substrate and lift-off plastic shelf mats. Shelves offer a 20 year warranty against corrosion. Rust proof polymer posts offer a lifetime warranty against corrosion. Shelf mats and posts have built-in Microban® antimicrobial product protection. Rigid four-sided shelf frame and welded corners provide complete 360° capture of the wedge and post to ensure stability, strength and structural integrity. Each Starter and Add-on unit has a maximum capacity of 2,000 lbs. (907kg) evenly distributed. Units assemble easily — Shelves mount on four one-piece wedges along grooved, numbered posts. Shelves adjust on 1" (25mm) increments.

- **Starter units:** shelves and polymer posts under one easy to order model number.
- **Add-on units:** include (2) polymer posts, open grid mat shelves, and S-hooks to connect a unit end-to-end under one easy to order model number.
- **Corner (Right Angle) units:** allow easy access to the shelf contents by eliminating a front post. They are configured using a starter unit, an add-on unit and intermediate "S" hook brackets.
- **Forever Strong:** Proven corner connection and four-sided shelf frame with center truss(es) assures stability and strength in stationary, mobile, and high-density track shelving configurations. 800 lbs. (363kg) per shelf for lengths of 24" to 48" (610 to 1219mm) 600 lbs. (272kg) per shelf for lengths of 54" (1372mm) or longer
Stationary unit: 2000lbs (907kg) evenly distributed.
- **Life-Long Rust Resistant:** Shelves offer a 20 year warranty against rust and corrosion. Polymer posts are rust-proof.
- **Easy to Clean and Maintain:** Polymer mats can be easily removed and cleaned in a sink or commercial washer / dish machine.
- **Microban® Antimicrobial Product Protection:** is built into the shelf mats and posts to inhibit the growth of bacteria, mold, mildew, and fungus that cause odors and product degradation. Microban product protection keeps the product "cleaner between cleanings".
- **Quick-to-Adjust:** Patented corner release allows shelves to be adjusted without tools. Simply flip each corner release, relocate the wedge connectors on the posts, and reposition the shelf. Quickly adjust shelves to reclaim wasted vertical space.
- **Efficient Use of Space:** Shelves adjust on 1" (25mm) increments along the post to maximize the use of available vertical space.
- **Fast, Easy Assembly:** Shelves are ready to use right out of the box. One-piece wedges securely attach to the posts – Raised beads on the back of each wedge snap into the grooves on the post. Window on wedge aligns with numbers on the post to locate the desired shelf position. Shelf seats into position over the posts and wedges. A unit can be assembled without tools in minutes.
- **Open Grid (vented) Shelf mats:** Sectioned and promote air circulation and light penetration. Built-in ship's edge helps contain supplies.
- **NSF Listed for all environments.**
- **Maximum Versatility:** Complete line of accessories are found on spec sheet 9.25.



Four Shelf Starter Unit



Starter Unit

Add-on Unit

Supports good
HACCP
processes

MICROBAN® and the MICROBAN® symbol are registered trademarks of the Microban® Products Company, Huntersville, NC. Microban® product protection does not by itself protect a user from food borne illness. Product must be routinely cleaned.



InterMetro Industries Corporation
North Washington Street, Wilkes-Barre, PA 18705
Product Information. U.S. and Canada: 1.800.992.1776
Outside U.S. and Canada: www.metro.com/contactus

L02-202 Printed in U.S.A. 3/20

Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2020 InterMetro Industries Corp.



MetroMax® Q Polymer/Wire Shelving Starter and Add-on Units



9.11



MetroMax® Q Starter & Add-on Units


Material Specifications:

- Shelf Mats: Injection-molded polypropylene with exclusive built-in Microban® antimicrobial product protection.
- Shelf frames and epoxy-coated posts: Steel with electroplated substrate and highly durable, abrasion-resistant epoxy finish. The adjustable foot is reinforced nylon.
- Polymer Post: Pultrusions — continuous glass fibers and thermoset resin composite with built-in Microban® antimicrobial product protection.
- Shelf Wedge Connector: Reinforced nylon.
- Temperature range: -20°F (-29°C) to 125°F (52°C) continuous use, with intermittent exposure to 200°F (93°C) for cleaning.
- Visit metro.com/service-support for cleaning guidelines.



Starter Units: consist of four or five open grid shelves and four posts.

Add-on Units: consist of four or five shelves, (2) posts, and standard S-Hook Kits (2 per shelf) to configure end-to-end units.
 Four tier units include (8) standard "S" Hooks. (model number, M9995)
 Five tier units include (10) standard "S" Hooks. (model number, M9995)



Corner (Right Angle) Configurations: select one add-on unit and intermediate "S" Hook brackets.

| 5-Shelf Unit with 74" polymer posts | | | | | | | | | |
|-------------------------------------|-------------------------|---------------|-----------------------|---------------------------|-------------------------|---------------|----------------------|------|----------|
| Starter Units | | | Add-On Units | | | | | | |
| Nominal Width/Length (mm) | Approx. Pkd. Wt. (lbs.) | Pkd. Wt. (kg) | Cat. No. Starter Unit | Nominal Width/Length (mm) | Approx. Pkd. Wt. (lbs.) | Pkd. Wt. (kg) | Cat. No. Add-On Unit | | |
| 18x24 | 457x610 | 39.8 | 18.1 | 5Q317G3 | 18x24 | 457x610 | 37.4 | 17.0 | 5AQ317G3 |
| 18x30 | 457x760 | 48.8 | 22.1 | 5Q327G3 | 18x30 | 457x760 | 46.4 | 21.0 | 5AQ327G3 |
| 18x36 | 457x914 | 57.3 | 26.0 | 5Q337G3 | 18x36 | 457x914 | 54.9 | 24.9 | 5AQ337G3 |
| 18x42 | 457x1060 | 65.8 | 29.8 | 5Q347G3 | 18x42 | 457x1060 | 63.4 | 28.8 | 5AQ347G3 |
| 18x48 | 457x1219 | 74.8 | 33.9 | 5Q357G3 | 18x48 | 457x1219 | 72.4 | 32.8 | 5AQ357G3 |
| 18x54 | 457x1372 | | | | 18x54 | 457x1372 | | | |
| 18x60 | 457x1524 | 92.3 | 41.9 | 5Q367G3 | 18x60 | 457x1524 | 89.9 | 40.8 | 5AQ367G3 |
| 18x72 | 457x1829 | 108.8 | 49.4 | 5Q377G3 | 18x72 | 457x1829 | 106.4 | 48.3 | 5AQ377G3 |
| 21x24 | 530x610 | 48.8 | 22.1 | 5Q417G3 | 21x24 | 530x610 | 46.4 | 21.0 | 5AQ417G3 |
| 21x30 | 530x760 | 57.3 | 26.0 | 5Q427G3 | 21x30 | 530x760 | 54.9 | 24.9 | 5AQ427G3 |
| 21x36 | 530x914 | 65.8 | 29.8 | 5Q437G3 | 21x36 | 530x914 | 63.4 | 28.8 | 5AQ437G3 |
| 21x42 | 530x1060 | 72.8 | 33.0 | 5Q447G3 | 21x42 | 530x1060 | 70.4 | 31.9 | 5AQ447G3 |
| 21x48 | 530x1219 | 81.3 | 36.9 | 5Q457G3 | 21x48 | 530x1219 | 78.9 | 35.8 | 5AQ457G3 |
| 21x54 | 530x1372 | | | | 21x54 | 530x1372 | | | |
| 21x60 | 530x1524 | 101.3 | 45.9 | 5Q467G3 | 21x60 | 530x1524 | 98.9 | 44.9 | 5AQ467G3 |
| 21x72 | 530x1829 | 117.3 | 53.2 | 5Q477G3 | 21x72 | 530x1829 | 114.9 | 52.1 | 5AQ477G3 |
| 24x24 | 610x610 | 57.3 | 26.0 | 5Q517G3 | 24x24 | 610x610 | 54.9 | 24.9 | 5AQ517G3 |
| 24x30 | 610x760 | 65.8 | 29.8 | 5Q527G3 | 24x30 | 610x760 | 63.4 | 28.8 | 5AQ527G3 |
| 24x36 | 610x914 | 74.3 | 33.7 | 5Q537G3 | 24x36 | 610x914 | 71.9 | 32.6 | 5AQ537G3 |
| 24x42 | 610x1060 | 79.3 | 36.0 | 5Q547G3 | 24x42 | 610x1060 | 76.9 | 34.9 | 5AQ547G3 |
| 24x48 | 610x1219 | 87.8 | 39.8 | 5Q557G3 | 24x48 | 610x1219 | 85.4 | 38.7 | 5AQ557G3 |
| 24x54 | 610x1372 | | | | 24x54 | 610x1372 | | | |
| 24x60 | 610x1524 | 110.3 | 50.0 | 5Q567G3 | 24x60 | 610x1524 | 107.9 | 48.9 | 5AQ567G3 |
| 24x72 | 610x1829 | 126.3 | 57.3 | 5Q577G3 | 24x72 | 610x1829 | 123.9 | 56.2 | 5AQ577G3 |



74" Five Shelf Starter Unit



Starter & Add-on Unit Together

Actual Dimensions:
 Width: Add 3/8" (10mm) to nominal size. Length: Subtract 3/16" (5mm) from nominal size.



"S" Hook
 Cat. No. M9995



Intermediate "S"
 Hook Kit
 Cat. No. Q9995Z

Creating a Right Angle (Corner) configuration. Use one standard "S" Hook (included with the Add-on unit) and one Intermediate "S" Hook per tier. Intermediate "S" Hook Bracket Cat. No. Q9995Z



MetroMax® Q Starter & Add-on Units

We put space to work.®

4-Shelf Unit with 74" polymer posts

| Starter Units | | | | | Add-On Units | | | | |
|-------------------------------|----------|----------------------------|------|-----------------------|-------------------------------|----------|----------------------------|------|----------------------|
| Nominal Width/Length (in./mm) | | Approx. Pkd. Wt. (lbs./kg) | | Cat. No. Starter Unit | Nominal Width/Length (in./mm) | | Approx. Pkd. Wt. (lbs./kg) | | Cat. No. Add-On Unit |
| 18x24 | 457x610 | 33.6 | 15.2 | MQ-182474G-S-4 | 18x24 | 457x610 | 30.8 | 14.0 | MQ-182474G-A-4 |
| 18x30 | 457x760 | 40.8 | 18.5 | MQ-183074G-S-4 | 18x30 | 457x760 | 38.0 | 17.2 | MQ-183074G-A-4 |
| 18x36 | 457x914 | 47.6 | 21.6 | MQ-183674G-S-4 | 18x36 | 457x914 | 44.8 | 20.3 | MQ-183674G-A-4 |
| 18x42 | 457x1060 | 54.4 | 24.7 | MQ-184274G-S-4 | 18x42 | 457x1060 | 51.6 | 23.4 | MQ-184274G-A-4 |
| 18x48 | 457x1219 | 61.6 | 27.9 | MQ-184874G-S-4 | 18x48 | 457x1219 | 58.8 | 26.7 | MQ-184874G-A-4 |
| 18x54 | 457x1372 | 68.8 | 31.2 | MQ-185474G-S-4 | 18x54 | 457x1372 | 66.0 | 29.9 | MQ-185474G-A-4 |
| 18x60 | 457x1524 | 75.6 | 34.3 | MQ-186074G-S-4 | 18x60 | 457x1524 | 72.8 | 33.0 | MQ-186074G-A-4 |
| 18x72 | 457x1829 | 88.8 | 40.3 | MQ-187274G-S-4 | 18x72 | 457x1829 | 86.0 | 39.0 | MQ-187274G-A-4 |
| 21x24 | 530x610 | 40.8 | 18.5 | MQ-212474G-S-4 | 21x24 | 530x610 | 38.0 | 17.2 | MQ-212474G-A-4 |
| 21x30 | 530x760 | 47.6 | 21.6 | MQ-213074G-S-4 | 21x30 | 530x760 | 44.8 | 20.3 | MQ-213074G-A-4 |
| 21x36 | 530x914 | 54.4 | 24.7 | MQ-213674G-S-4 | 21x36 | 530x914 | 51.6 | 23.4 | MQ-213674G-A-4 |
| 21x42 | 530x1060 | 60.0 | 27.2 | MQ-214274G-S-4 | 21x42 | 530x1060 | 57.2 | 25.9 | MQ-214274G-A-4 |
| 21x48 | 530x1219 | 66.8 | 30.3 | MQ-214874G-S-4 | 21x48 | 530x1219 | 64.0 | 29.0 | MQ-214874G-A-4 |
| 21x54 | 530x1372 | 75.6 | 34.3 | MQ-215474G-S-4 | 21x54 | 530x1372 | 72.8 | 33.0 | MQ-215474G-A-4 |
| 21x60 | 530x1524 | 82.8 | 37.6 | MQ-216074G-S-4 | 21x60 | 530x1524 | 80.0 | 36.3 | MQ-216074G-A-4 |
| 21x72 | 530x1829 | 95.6 | 43.4 | MQ-217274G-S-4 | 21x72 | 530x1829 | 92.8 | 42.1 | MQ-217274G-A-4 |
| 24x24 | 610x610 | 47.6 | 21.6 | MQ-242474G-S-4 | 24x24 | 610x610 | 44.8 | 20.3 | MQ-242474G-A-4 |
| 24x30 | 610x760 | 54.4 | 24.7 | MQ-243074G-S-4 | 24x30 | 610x760 | 51.6 | 23.4 | MQ-243074G-A-4 |
| 24x36 | 610x914 | 61.2 | 27.8 | MQ-243674G-S-4 | 24x36 | 610x914 | 58.4 | 26.5 | MQ-243674G-A-4 |
| 24x42 | 610x1060 | 65.2 | 29.6 | MQ-244274G-S-4 | 24x42 | 610x1060 | 62.4 | 28.3 | MQ-244274G-A-4 |
| 24x48 | 610x1219 | 72.0 | 32.7 | MQ-244874G-S-4 | 24x48 | 610x1219 | 69.2 | 31.4 | MQ-244874G-A-4 |
| 24x54 | 610x1372 | 82.8 | 37.6 | MQ-245474G-S-4 | 24x54 | 610x1372 | 80.0 | 36.3 | MQ-245474G-A-4 |
| 24x60 | 610x1524 | 90.0 | 40.8 | MQ-246074G-S-4 | 24x60 | 610x1524 | 87.2 | 39.6 | MQ-246074G-A-4 |
| 24x72 | 610x1829 | 102.8 | 46.6 | MQ-247274G-S-4 | 24x72 | 610x1829 | 95.6 | 43.4 | MQ-247274G-A-4 |




4-Shelf Starter Unit



4-Shelf Add-On Unit



Includes 8 S-Hooks



Add-on mounts to starter unit via S-Hooks.

4-Shelf Unit with 63" polymer posts

| Starter Units | | | | Add-On Units | | | | | |
|-------------------------------|----------|----------------------------|------|-----------------------|-------------------------------|----------|----------------------|------|---------|
| Nominal Width/Length (in./mm) | | Approx. Pkd. Wt. (lbs./kg) | | Cat. No. Starter Unit | Nominal Width/Length (in./mm) | | Cat. No. Add-On Unit | | |
| 18x24 | 457x610 | 32.0 | 14.5 | Q316G3 | 18x24 | 457x610 | 30.0 | 13.6 | AQ316G3 |
| 18x30 | 457x760 | 39.2 | 17.8 | Q326G3 | 18x30 | 457x760 | 37.2 | 16.9 | AQ326G3 |
| 18x36 | 457x914 | 46.0 | 20.9 | Q336G3 | 18x36 | 457x914 | 44.0 | 20.0 | AQ336G3 |
| 18x42 | 457x1060 | 52.8 | 23.9 | Q346G3 | 18x42 | 457x1060 | 50.8 | 23.0 | AQ346G3 |
| 18x48 | 457x1219 | 60.0 | 27.2 | Q356G3 | 18x48 | 457x1219 | 58.0 | 26.3 | AQ356G3 |
| 18x54 | 457x1372 | | | | 18x54 | 457x1372 | | | |
| 18x60 | 457x1524 | 74.0 | 33.6 | Q366G3 | 18x60 | 457x1524 | 72.0 | 32.7 | AQ366G3 |
| 18x72 | 457x1829 | 87.2 | 39.6 | Q376G3 | 18x72 | 457x1829 | 85.2 | 38.6 | AQ376G3 |
| 21x24 | 530x610 | 39.2 | 17.8 | Q416G3 | 21x24 | 530x610 | 37.2 | 16.9 | AQ416G3 |
| 21x30 | 530x760 | 46.0 | 20.9 | Q426G3 | 21x30 | 530x760 | 44.0 | 20.0 | AQ426G3 |
| 21x36 | 530x914 | 52.8 | 23.9 | Q436G3 | 21x36 | 530x914 | 50.8 | 23.0 | AQ436G3 |
| 21x42 | 530x1060 | 58.4 | 26.5 | Q446G3 | 21x42 | 530x1060 | 56.4 | 25.6 | AQ446G3 |
| 21x48 | 530x1219 | 65.2 | 29.6 | Q456G3 | 21x48 | 530x1219 | 63.2 | 28.7 | AQ456G3 |
| 21x54 | 530x1372 | | | | 21x54 | 530x1372 | | | |
| 21x60 | 530x1524 | 81.2 | 36.8 | Q466G3 | 21x60 | 530x1524 | 79.2 | 35.9 | AQ466G3 |
| 21x72 | 530x1829 | 94.0 | 42.6 | Q476G3 | 21x72 | 530x1829 | 92.0 | 41.7 | AQ476G3 |
| 24x24 | 610x610 | 46.0 | 20.9 | Q516G3 | 24x24 | 610x610 | 44.0 | 20.0 | AQ516G3 |
| 24x30 | 610x760 | 52.8 | 23.9 | Q526G3 | 24x30 | 610x760 | 50.8 | 23.0 | AQ526G3 |
| 24x36 | 610x914 | 59.6 | 27.0 | Q536G3 | 24x36 | 610x914 | 57.6 | 26.1 | AQ536G3 |
| 24x42 | 610x1060 | 63.6 | 28.8 | Q546G3 | 24x42 | 610x1060 | 61.6 | 27.9 | AQ546G3 |
| 24x48 | 610x1219 | 70.4 | 31.9 | Q556G3 | 24x48 | 610x1219 | 68.4 | 31.0 | AQ556G3 |
| 24x54 | 610x1372 | | | | 24x54 | 610x1372 | | | |
| 24x60 | 610x1524 | 88.4 | 40.1 | Q566G3 | 24x60 | 610x1524 | 86.4 | 39.2 | AQ566G3 |
| 24x72 | 610x1829 | 101.2 | 45.9 | Q576G3 | 24x72 | 610x1829 | 99.2 | 45.0 | AQ576G3 |

Actual Dimensions:
Width: Add 3/16" (10mm) to nominal size. Length: Subtract 3/16" (5mm) from nominal size.

an Ali Group Company



The Spirit of Excellence