



Item # _____

Job _____

METRO® BRAKE LOCK/ SWIVEL LOCK COMBINATION CASTERS

- **A Metro Exclusive:** Metro's patented brake/lock mechanism enables a single pair of casters to serve as swivel, rigid or brake casters to meet varying operational needs.
- **How It Works:** Brake lock/swivel lock caster sets are operated by two separate foot pedals. One pedal locks the two wheels in a rigid position or releases them to swivel; the other pedal locks and releases brakes on the same two wheels.
- **"People Proof":** Pedals are positioned on the dolly rather than the wheels, making their operation more convenient. And because all changes are effected by downward pressure on the pedals, shoes are saved from scuffing.
- **Two Sizes:**
 - 6" (152mm) or 8" (203mm) wheels with 2" (51mm) face.
 - **Polyurethane Tread:** Long-wearing. Resists abrasion. Non-marking.
- **Cart-Washable:** Casters and mechanism designed to withstand cart-washing.
- **Replacement Parts** available for mechanism and casters.
- **Recommended Caster Selection** for trucks is two swivel casters at one end and brake/lock set at the other end. Other caster combinations can be used, however, including brake/lock sets at both ends. Wraparound bumper recommended.



Dimensions

Cat. No.	For Use With	Wheel Diameter	
		(in.)	(mm)
BL6P18	18" (455mm) deep dolly; 6" (152mm) caster	6	152
BL6P21	21" (533mm) deep dolly; 6" (152mm) caster	6	152
BL6P24	24" (610mm) deep dolly; 6" (152mm) caster	6	152
BL8P21	21" (533mm) deep dolly; 8" (203mm) caster	8	203
BL8P24	24" (610mm) deep dolly; 8" (203mm) caster	8	203

NOTE: Above part numbers include the brake/lock mechanism with two casters set only. Order dolly separately. Order either two C6P or two separately.
Maximum Load Rating for Dolly: 1000 lbs. (454 kg).



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com

Job _____



TOW BAR ASSEMBLY

METRO® TOW BAR ASSEMBLY

- **Attaches Directly** to the underside of dolly frame for maximum strength. Sure, instant lock/unlock mechanism.
- **Retractable Nose:** Swings up and out of the way when not in use.
- **Fits** truck sizes measuring 24" x 48" (610mm x 1220mm)
- **Chrome Finish**



Dimensions

Cat. No.	Length	
	(in.)	(mm)
TBA48	48	1220

NOTE 1: "C" plate caster must be used with Tow Bar Assembly. Tow Bar Assembly for use with 24" (610mm) units only.

NOTE 2: Number of carts to be towed, weight on carts, and towing route affect operation of tow bar assembly. **Before ordering, therefore,** contact InterMetro Industries or your Metro representative.

Manufactured by:



InterMetro Industries Corporation
 North Washington Street, Wilkes-Barre, PA 18705
 Phone: 570-825-2741 • Fax: 570-825-2852
 For Product Information Call: 1-800-433-2232
 Visit Our Web Site: www.metro.com

L02-050
 Rev. 11/00
 Printed in U.S.A.

Information and specifications are subject to change without notice. Please confirm at time of order.

