



Item # _____

Job _____

SUPER ERECTA SHELF® STEM CASTER CARTS – SOLID SHELVES

- **Stem Caster Carts** combine Super Erecta Shelf® solid shelving features with the mobility of stem casters to provide a high-quality, strong and versatile material handling cart.
- **Variety of Casters Available:** Select the caster that allows the right combination of rollability and maneuverability to suit your requirements. Casters are available in swivel, rigid or brake types. All Metro casters are non-marking and come complete with a 3 1/2" donut bumper. Refer to sheet #11.20 for additional caster information.
- **Strength:** Two-fold thickness of 18-gauge steel forms 1/8" raised edges on all four sides of the shelving. This ship's edge gives all-around rigidity and high-strength. Sturdy aluminum castings firmly lock the corners to the posts.
- **Sanitary:** The raised ship's edge on all four sides and at the corners contains spillage, minimizes contamination and permits easier clean-up. Embossed or louvered/embossed shelf designs allow air circulation under packages and containers.
- **Fast, Secure Assembly:** Post has rolled, circular grooves along its entire height at 1" (25mm) intervals. A patented, tapered split sleeve (plastic or aluminum) snaps together around each post. Tapered openings in the shelf corners slide over the tapered split sleeves providing a positive lock. Cart is assembled in minutes without the use of nuts or bolts and without the use of any special tools.
- **Adjustability:** Shelves can be adjusted at 1" (25mm) intervals along the entire height of the post.



Job _____

SUPER ERECTA SHELF® STEM CASTER CARTS – SOLID SHELVES



Dimensions

Standard Units:

Consist of four shelves, posts, plastic split sleeves*, donut bumpers and designated casters.


With Galvanized Flat Solid Shelves & Plated Posts

62" (1575mm) Posts — Overall Height 68" (1730mm)

| Solid Shelf | | | | Cat. No. with Casters | | | |
|----------------|------|-----------------|------|-----------------------|-------------------|-------------|---------------------|
| Width (in.) | (mm) | Length (in.) | (mm) | Four 5M | Two 5M Two 5MB | Four 5MP | Two 5MP Two 5MPB |
| 18 | 455 | 36 | 910 | F336AG | F336BG | F336DG | F336EG |
| 18 | 455 | 48 | 1220 | F356AG | F356BG | F356DG | F356EG |
| 18 | 455 | 60 | 1525 | F366AG | F366BG | F366DG | F366EG |
| 21 | 530 | 36 | 910 | F436AG | F436BG | F436DG | F436EG |
| 21 | 530 | 48 | 1220 | F456AG | F456BG | F456DG | F456EG |
| 21 | 530 | 60 | 1525 | F466AG | F466BG | F466DG | F466EG |
| 24 | 610 | 36 | 910 | F536AG | F536BG | F536DG | F536EG |
| 24 | 610 | 48 | 1220 | F556AG | F556BG | F556DG | F556EG |
| 24 | 610 | 60 | 1525 | F566AG | F566BG | F566DG | F566EG |

Posts

| Height | | Approx. Pkd. Wt | | Cat. No. Plated |
|--------------------------------|------|-------------------------------|------|--------------------|
| (in.) | (mm) | (lbs.) | (kg) | |
| 13 ⁷ / ₈ | 352 | 1 | 0.5 | 13UP |
| 33 ⁷ / ₈ | 835 | 2 | 0.9 | 33UP |
| 54 | 1370 | 3 | 1.4 | 54UP |
| 62 | 1575 | 3 ¹ / ₂ | 1.6 | 63UP |
| 74 | 1880 | 4 | 1.8 | 74UP |
| 86 | 2185 | 5 | 2.3 | 86UP |



SiteSelect™ Posts are grooved at 1" (25mm) increments and numbered at 2" (50mm) increments. Posts are double-grooved every 8" (203mm) for easy identification.

* Aluminum split sleeves are recommended when unit will be towed, transported over the road or otherwise subjected to vibration or jolting. To order, see catalog sheet #10.06 or price list.

Load Rating: 3 times the caster load rating, or not to exceed 800 lbs. (363 kg) per cart.

To Order By Components

1. Order shelves from catalog sheet #10.20 or price list. (Will be packed with plastic split sleeves.*)
2. Order stem casters from catalog sheet #11.20 or price list. Donut bumper comes with caster.
3. Order posts from table at left. Except for rigid casters, posts are shipped assembled with caster and donut bumper.

IMPORTANT: When ordering by components remember that stability decreases as the ratio of height to width increases. Units should be kept as wide and low as possible.

Manufactured by:



InterMetro Industries Corporation

North Washington Street, Wilkes-Barre, PA 18705

Phone: 570-825-2741 • Fax: 570-825-2852

For Product Information Call: 1-800-433-2232

Visit Our Web Site: www.metro.com

L02-038
Rev. 11/00
Printed in U.S.A.

Information and specifications are subject to change without notice. Please confirm at time of order.