

BARRIERMASTER FLAVOURLOCK™

Beverages: Beer, wine, juice, cold coffee and tea, soda, liquor, water, etc.

1/4" TRUNKLINE

.30 RESTRICTION PER FOOT – 15 oz BEER PER 50 FT



PART NO.	BTUs	PRODUCT LINES	I.D.	GLYCOL LINES	I.D.	BLACK DIAMOND® JACKET	BUNDLE O.D.
CDI242-BF	5.9	2	1/4"	2	3/8"	Yes	2-3/4"
CDI442-BF	6.3	4	1/4"	2	3/8"	Yes	2-3/4"
CDI542-BF	6.5	5	1/4"	2	3/8"	Yes	2-3/4"
CDI642-BF	6.5	6	1/4"	2	3/8"	Yes	2-3/4"
CDI842-BF	7.0	8	1/4"	2	3/8"	Yes	2-3/4"
CDI1044-BF	7.9	10	1/4"	4	3/8"	Yes	3-1/4"
CDI1244-BF	8.2	12	1/4"	4	3/8"	Yes	3-1/4"
CDI1644-BF	9.0	16	1/4"	4	3/8"	Yes	3-3/4"
CDI1042-BF	7.5	10	1/4"	2	1/2"	Yes	3-1/4"

BTU/HR/FT is based on an ambient temperature of 80° F and a glycol mix of 40% glycol / 60% water.



CDI642-BF

BARRIERMASTER FLAVOURLOCK™

Beverages: Beer, wine, juice, cold coffee and tea, soda, liquor, water, etc.

5/16" TRUNKLINE

.10 RESTRICTION PER FOOT – 25 oz BEER PER 50 FT



PART NO.	BTUs	PRODUCT LINES	I.D.	GLYCOL LINES	I.D.	BLACK DIAMOND® JACKET	BUNDLE O.D.
CDI252-BF	6.0	2	5/16"	2	3/8"	Yes	2-3/4"
CDI452-BF	6.5	4	5/16"	2	3/8"	Yes	2-3/4"
CDI552-BF	6.7	5	5/16"	2	3/8"	Yes	2-3/4"
CDI652-BF	7.1	6	5/16"	2	3/8"	Yes	2-3/4"
CDI852-BF	7.6	8	5/16"	2	3/8"	Yes	3"
CDI1054-BF	8.3	10	5/16"	4	3/8"	Yes	3-1/2"
CDI1254-BF	8.9	12	5/16"	4	3/8"	Yes	3-1/2"
CDI1454-BF	9.5	14	5/16"	4	3/8"	NA	3-1/2"
CDI1654-BF	9.7	16	5/16"	4	3/8"	NA	4"
CDI2054-BF	10.3	20	5/16"	4	3/8"	NA	4-1/4"
CDI2454-BF	10.9	24	5/16"	4	3/8"	NA	4-1/2"
CDI1052-BF	8.4	10	5/16"	2	1/2"	Yes	3-1/2"

BTU/HR/FT is based on an ambient temperature of 80° F and a glycol mix of 40% glycol / 60% water.



CDI852-BF

BARRIERMASTER FLAVOURLOCK™

Beverages: Beer, wine, juice, cold coffee and tea, soda, liquor, water, etc.

3/8" TRUNKLINE

.06 RESTRICTION PER FOOT – 37.5 oz BEER PER 50 FT



PART NO.	BTUs	PRODUCT LINES	I.D.	GLYCOL LINES	I.D.	BLACK DIAMOND® JACKET	BUNDLE O.D.
CDI232-BF	6.3	2	3/8"	2	3/8"	Yes	2-3/4"
CDI432-BF	6.8	4	3/8"	2	3/8"	Yes	2-3/4"
CDI532-BF	7.2	5	3/8"	2	3/8"	Yes	2-3/4"
CDI632-BF	7.5	6	3/8"	2	3/8"	Yes	2-3/4"
CDI832-BF	8.0	8	3/8"	2	3/8"	Yes	3"
CDI1034-BF	8.9	10	3/8"	4	3/8"	Yes	3-3/4"
CDI1234-BF	9.5	12	3/8"	4	3/8"	NA	3-3/4"
CDI1434-BF	10.0	14	3/8"	4	3/8"	NA	4"
CDI1634-BF	10.5	16	3/8"	4	3/8"	NA	4"
CDI2034-BF	11.0	20	3/8"	4	3/8"	NA	4-1/2"

BTU/HR/FT is based on an ambient temperature of 80° F and a glycol mix of 40% glycol / 60% water.



CDI632-BF