

## CO<sub>2</sub> LEAK DETECTOR & SENSORS

Wall-mountable multi-gas monitors for detecting carbon dioxide flexible and customizable solution. Detectors ensure employee and guest safety as well as facility compliance. All detectors are UL Listed and OSHA compliant. Perfect for restaurants, bars, breweries, wineries and agriculture applications.

### ANALOX AX60+

Ax60+ is a wall-mountable multi-gas monitor for detecting carbon dioxide with an option for monitoring oxygen, providing a flexible and customizable solution. The CO<sub>2</sub> and O<sub>2</sub> sensors are interchangeable and can be fully integrated as part of a multi-point, multi-gas detection and alarm system. Ax60+ CO<sub>2</sub> Alarm set points are now pre-configured to 0.5% 8 hr TWA, 0.5%, 1.5% and 3.0% making it ready to install out of the box.

#### FEATURES & SPECIFICATIONS:

- User customizable alarm set-points
- Percentage Range Present: 0.1 to 5% CO<sub>2</sub>
- Percentage Range Present: 0.1 to 25% O<sub>2</sub>
- Response Time: Less than 30 seconds
- Power Supply Input, 100-200V: Output, Less than 24V
- Meets NFPA, IFC and OSHA requirements. UL Listed.

| PART NO.       | DESCRIPTION                                                                               |
|----------------|-------------------------------------------------------------------------------------------|
| MM-AX60-AP1    | Single point detector complete kit, capable of expanding to 4 sensors and 8 alarm/strobes |
| MM-AX60MQANA   | Data output module, quick connect                                                         |
| MM-AX60RQYBA   | AX60+ Alarm, quick connect, blue strobe, includes cable                                   |
| MM-AX60RQYCA   | AX60+ Alarm, quick connect, white strobe, includes cable                                  |
| MM-AX60RQYDA   | AX60+ Alarm, quick connect, amber strobe, includes cable                                  |
| MM-AX60SAQYA   | Ax60 + CO <sub>2</sub> sensor unit, quick connect, , includes cable                       |
| MM-AX60SCQYA   | AX60 + O <sub>2</sub> sensor unit, quick connect, includes cable                          |
| MM-AX60CUQYXA  | Ax60+ central display unit, quick connect, universal power supply unit                    |
| MM-P0159-4305K | Analox protector kit, protector bar, splash guard                                         |

### AX60+ KIOSK

The Ax60+ Kiosk is a smaller version of the popular Ax60+ carbon dioxide gas detector built especially for smaller restaurants. OSHA compliant.

| PART NO.  | DESCRIPTION                  |
|-----------|------------------------------|
| MM-AX60-K | Sensor, alarm, quick connect |

Not recommended for use in walk-in coolers

### CO<sub>2</sub>METER® CO<sub>2</sub> 7000 SERIES MULTI-SENSOR SYSTEM

Configure your system specifically for your environment! The CO<sub>2</sub> Multi-Sensor System detects potentially hazardous levels of CO<sub>2</sub> in the air. 12+ sensors reporting concentration levels to the large touchscreen display. Customizable alarm settings to activate audible and visual alarms as well as relays to trigger third-party devices like fire panels or ventilation.

#### FEATURES:

- Wired CO<sub>2</sub> monitor and remote display
- Utilizes NDIR technology
- Easy to use and quick installation
- Both audible and visual alarms
- Configurable settings and relays
- Designed to meet all-state fire codes
- Meets NFPA, IFC, and NBIC requirements
- Meets OSHA and NIOSH TWA standards. UL Listed.

| PART NO. | DESCRIPTION                                                |
|----------|------------------------------------------------------------|
| CM-7005  | Tablet, main hub of the 7000 series, 3-built in relays     |
| CM-7003  | CO <sub>2</sub> sensor, sensing element of the 7000 series |
| CM-7004  | Horn/strobe, the audible and visual alarm for each sensor  |

### CO<sub>2</sub>METER® REMOTE CO<sub>2</sub> STORAGE SAFETY 3 ALARM

Ensure the safety of your employees and guests as well as the compliance of your facility with the Remote CO<sub>2</sub> Storage Safety 3 Alarm. LCD display clearly indicates current CO<sub>2</sub> level in ppm or % and temperature. Ships pre-set, also configurable on-site. Easy to install and use. UL Listed.

| PART NO.   | DESCRIPTION                                                                                                                                                                          |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RAD-0102-6 | CO <sub>2</sub> Storage Safety Three Alarm System. Includes: one main sensing unit, one remote display unit, 25 ft. CAT5 cable, mounting brackets, screws, and multilingual signage. |
| CM-1026    | Amber strobe kit, 2 strobes and cables                                                                                                                                               |

ANALOX  
Sensor Technology



MM-AX60-AP1



MM-AX60RQYBA  
BLUE STROBE

MM-AX60RQYCA  
WHITE STROBE

MM-AX60RQYDA  
AMBER STROBE



MM-AX60-K

CO<sub>2</sub>METER.COM  
CO<sub>2</sub> MEASUREMENT SPECIALISTS



Sensor, horn and tablet shown



RAD-0102-6