

CO₂ LEAK DETECTOR & SENSORS

Wall-mountable multi-gas monitors for detecting carbon dioxide flexible and customizable solution. Detectors ensure employee and guest safety as well as facility compliance. All detectors are UL Listed and OSHA compliant. Perfect for restaurants, bars, breweries, wineries and agriculture applications.

ANALOX AX60+

Ax60+ is a wall-mountable multi-gas monitor for detecting carbon dioxide with an option for monitoring oxygen, providing a flexible and customizable solution. The CO₂ and O₂ sensors are interchangeable and can be fully integrated as part of a multi-point, multi-gas detection and alarm system. Ax60+ CO₂ Alarm set points are now pre-configured to 0.5% 8 hr TWA, 0.5%, 1.5% and 3.0% making it ready to install out of the box.

FEATURES & SPECIFICATIONS:

- User customizable alarm set-points
- Percentage Range Present: 0.1 to 5% CO₂
- Percentage Range Present: 0.1 to 25% O₂
- Response Time: Less than 30 seconds
- Power Supply Input, 100-200V: Output, Less than 24V
- Meets NFPA, IFC and OSHA requirements. UL Listed.

PART NO.	DESCRIPTION
MM-AX60-AP1	Single point detector complete kit, capable of expanding to 4 sensors and 8 alarm/strobes
MM-AX60MQANA	Data output module, quick connect
MM-AX60RQYBA	AX60+ Alarm, quick connect, blue strobe, includes cable
MM-AX60RQYCA	AX60+ Alarm, quick connect, white strobe, includes cable
MM-AX60RQYDA	AX60+ Alarm, quick connect, amber strobe, includes cable
MM-AX60SAQYA	Ax60 + CO ₂ sensor unit, quick connect, , includes cable
MM-AX60SCQYA	AX60 + O ₂ sensor unit, quick connect, includes cable
MM-AX60CUQYXA	Ax60+ central display unit, quick connect, universal power supply unit
MM-P0159-4305K	Analox protector kit, protector bar, splash guard

AX60+ KIOSK

The Ax60+ Kiosk is a smaller version of the popular Ax60+ carbon dioxide gas detector built especially for smaller restaurants. OSHA compliant.

PART NO.	DESCRIPTION
MM-AX60-K	Sensor, alarm, quick connect

Not recommended for use in walk-in coolers

CO₂METER® CO₂ 7000 SERIES MULTI-SENSOR SYSTEM

Configure your system specifically for your environment! The CO₂ Multi-Sensor System detects potentially hazardous levels of CO₂ in the air. 12+ sensors reporting concentration levels to the large touchscreen display. Customizable alarm settings to activate audible and visual alarms as well as relays to trigger third-party devices like fire panels or ventilation.

FEATURES:

- Wired CO₂ monitor and remote display
- Utilizes NDIR technology
- Easy to use and quick installation
- Both audible and visual alarms
- Configurable settings and relays
- Designed to meet all-state fire codes
- Meets NFPA, IFC, and NBIC requirements
- Meets OSHA and NIOSH TWA standards. UL Listed.

PART NO.	DESCRIPTION
CM-7005	Tablet, main hub of the 7000 series, 3-built in relays
CM-7003	CO ₂ sensor, sensing element of the 7000 series
CM-7004	Horn/strobe, the audible and visual alarm for each sensor

CO₂METER® REMOTE CO₂ STORAGE SAFETY 3 ALARM

Ensure the safety of your employees and guests as well as the compliance of your facility with the Remote CO₂ Storage Safety 3 Alarm. LCD display clearly indicates current CO₂ level in ppm or % and temperature. Ships pre-set, also configurable on-site. Easy to install and use. UL Listed.

PART NO.	DESCRIPTION
RAD-0102-6	CO ₂ Storage Safety Three Alarm System. Includes: one main sensing unit, one remote display unit, 25 ft. CAT5 cable, mounting brackets, screws, and multilingual signage.
CM-1026	Amber strobe kit, 2 strobes and cables

ANALOX
Sensor Technology



MM-AX60-AP1



MM-AX60RQYBA
BLUE STROBE

MM-AX60RQYCA
WHITE STROBE

MM-AX60RQYDA
AMBER STROBE



MM-AX60-K

CO₂METER.COM
CO₂ MEASUREMENT SPECIALISTS



Sensor, horn and tablet shown



RAD-0102-6