



BACK BAR

PRO-LINE™ 95" - 5 KEG

- Designed by beer-industry experts for performance and value.
- Front breathing for cooling and exhaust.



MBB94-E
Black



MBB94S-E
Stainless Steel



MBB94G-E
Black with Glass Doors



MBB94GS-E
Stainless Steel with Glass Doors



*Adjustable Digital Thermostat!
Easy to read exterior mounted*



Listed by Edison Testing Laboratories.
Conforms to UL & NSF Standards.

www.micromatic.com • 1 (866) 327-4159

PRO-LINE™ 95" - 5 KEG

Job Number: _____ Location: _____

Part No.	Door Type	Door Type	Finish	Doors	Shipping Weight
☐ MBB94-E	Solid	☐ MBB94G-E	Glass	Black	3
					184 kg 406 lbs
☐ MBB94S-E	Solid	☐ MBB94GS-E	Glass	Stainless Steel	3
					184 kg 406 lbs

Operating Performance

Keg Capacity of 1/2 Kegs	5	Running Amps	3.0
Cubic Feet (liters)	39.2 (1112)	Voltage	115/60/1
Shelves, Flat - Included	2	Plug Type	NEMA-5-15P
Shelves, Dividers - Included	4	Cord Length	8'
Cans 12 oz (355ml)	1092	Refrigerant	R290
Approval	ETL Listed	Charge oz	4.9
Compressor HP	1/3	Working High/Low Pressure	300 psig / 150 psig
Exterior	All Models: 18 gauge 201 grade stainless steel (s/s) top, 22 gauge solid doors, 24 gauge steel front, sides and back. Black Models: Front, sides, back and doors black vinyl over steel. S/S Models: Front, sides, back and doors are s/s.		
Interior	20 gauge stainless steel floor and walls, rugged false floor, reinforced frame		
Ventilation	Front breathing for cooling and exhaust		
Plumbing	Automatic condensate evaporator, no drain connection required. Evaporator condensate has been plumbed to a condensate pan located in the compressor housing		
Insulation	Foamed-in-place using high density, CFC-free polyurethane; 2" top, walls and floor		
Accessories	Casters or 6" fixed legs (order separately)		

Dimensions

