

GAS BLENDERS

MICRO MATIC PRO-LINE™

Outlet pressure is preset at 47 psi to eliminate operator tampering and minimize unnecessary service calls.

PART NO.	BLEND	LEAK DETECTOR	FLOW RATE	KEGS / HR	ALE AND LAGER	BLEND* ALE AND LAGER	STOUT
MM100-LD	Single	Included	Standard	10	70% CO ₂ & 30% N*		
MM100-60-40-LD	Single	Included	Standard	10		60% CO ₂ & 40% N	
MM200-LD	Double	Included	Standard	20*	70% CO ₂ & 30% N*		25% CO ₂ & 75% N*
MM200-60-40-LD	Double	Included	Standard	20*		60% CO ₂ & 40% N	25% CO ₂ & 75% N
MM100	Single		Standard	10	70% CO ₂ & 30% N*		
MM100-60-40	Single		Standard	10		60% CO ₂ & 40% N	
MM100S	Single		Standard	10			25% CO ₂ & 75% N*
MM200	Double		Standard	20*	70% CO ₂ & 30% N*		25% CO ₂ & 75% N*
MM200-60-40	Double		Standard	20*		60% CO ₂ & 40% N	25% CO ₂ & 75% N
MM300	Triple		Standard	30*	70% CO ₂ & 30% N*	60% CO ₂ & 40% N	25% CO ₂ & 75% N*

*Micro Matic Pro-Line™ gas blenders meet blend standards established by major breweries and the Brewers Association. *Up to 10 kegs per hour per blend.

TRUMIX®

Inlet pressure can be adjusted from 55 – 150 psi. Includes gauge(s) to adjust outlet pressure from 0 – 47 psi. Available in any blend from 5 – 95% CO₂.

PART NO.	BLEND	FLOW RATE	KEGS / HR	BLEND* ALE AND LAGER
TM100HF	Single	High-Flow	20	Specify Gas Blend: from 5 – 95% CO ₂ Balance N
TM100	Single	Standard	10	Specify Gas Blend: from 5 – 95% CO ₂ Balance N
TM200HF	Double	High-Flow	40	Specify Gas Blend: from 5 – 95% CO ₂ Balance N
TM200	Double	Standard	20	Specify Gas Blend: from 5 – 95% CO ₂ Balance N

Made to order. Customer must specify custom blend when ordering.



MM100-LD



MM100

(7-3/4" x 8-3/4" x 4-1/2")



TM100HF

(9-1/2" x 10" x 4-1/2")

BLENDER ACCESSORIES

HIGH PRESSURE REGULATORS

Recommended use with Pro-Line™ and Trumix® gas blenders. Use with braided high pressure hose. Safety relief valve releases at 115 – 125 psi.

PART NO.	DESCRIPTION
942B-PP	Double gauge CO ₂ regulator – Premium Plus
942BN-PP	Double gauge nitrogen regulator – Premium Plus



942B-PP

IN-LINE CHECK VALVE TEES

Recommended with every installation. Protect the gas blender from being filled with water when used in conjunction with bulk CO₂ or a soda carbonator. Use with braided high pressure hose. The Pro-Line™ and Trumix® gas blender warranty only covers against water damage if a tee was installed.

PART NO.	THRU	OUTLET
MV013	1/4" x 1/4"	1/4"
MV042	3/8" x 3/8"	3/8"
MV044	1/4" x 3/8"	1/4"

HIGH PRESSURE HOSES

PART NO.	COLOR	I.D.	O.D.	CLAMP	LENGTH
548WD1200C	Clear	1/4"	1/2"	133SL	100'
549WD1200C	Clear	5/16"	9/16"	145SL	100'
550WD1200C	Clear	3/8"	5/8"	170SL	100'



MV044



MV013



Braided vinyl tubing