

PRF8200 PROVER RETARDER PROVER FREEZER PROVER

Compatible for tray sizes, inches/mm 18"x26" / 457x662 mm

18"x30" / 457x762 mm 20"x30" / 508x762 mm 23.62"x31.50" / 600x800 mm 31.50"x39.37" / 800x1000 mm

Revent's line of innovative baking technology is made to take any bread to the highest level. In bread we trust.



Features:

- > Touch screen control panel
- > 200 steps air speed regulation with complete air flow system
- > Stainless steel interior and front design. Rest outside in white painted galvanic panels
- > Bumber rails on interior walls, doors. Bumper rails on exterior doors
- > Electro-magnetic steam system
- > Standard interior height: 76.26" / 1937 mm
- > Doors available as single, double, and sliding doors
- > Voltage: All voltages available.
- > Drain: 1.26" / 32mm connection, left, rear or right side
- > Water inlet: 0.39"/10mm. Connection on top front

Options:

- 1. 3mm stainless steel floor with fluted molding, 22 mm water-repellent, plasticsub-floor as well as adjustable heating (standard on freezer prover)
- 2. Triple, energy-saving glazing
- 3. Co2 or glycol cooling medium
- 4. Lights
- 5. Warm bread all through the day (available on retarder prover and freezer provers)

UNITS	PROVER / RETARDER PROVER TYPE				
	8211	8212	8221	8222	8223
Depth, inch / mm	47.2 / 1200	53.1 / 1350	41.3 / 1050	76.7 / 1950	88.5 / 2250
Width, inch / mm	37.0 / 940	47.2 / 1200	64.9/ 1650	64.9 / 1650	82.6 / 2100
Height without floor, inch / mm	98.0 / 2490	98.0/ 2490	98.0 / 2490	98.0 / 2490	98.0 / 2490
Height incl. floor, inch / mm, Standard on freezer prover	98.9 / 2512	98.9 / 2512	98.9 / 2512	98.9/ 2512	98.9 / 2512
No. of doors	1		2	2	2
Doorway width x height, inch / mm	29.5 x 76.2 750 x 1937	35.43 x 76.2 900 x 1937	53.1 x 76.2 1350 x 1937	53.1 x 76.2 1350 x 1937	70.87 x76.2 1800 x 1937
Unit, KW	5.50	6.50	6.50	8.00	9.50
Retarder prover, Cooling capacity -10° to 43°C/14° to 110° F, kW	1.79	1.79	1.79	1.79	2.99
Freezer prover, Cooling capacity -15°to 43°C / 5° to 110° F. kW	1.48	2.51	2.51	3.67	5.77

