



# Where Legendary Kitchens Are Born

**Refrigeration Equipment**



[www.sabacorpusa.com](http://www.sabacorpusa.com)

# WHO WE ARE

## ENDURING QUALITY

SABA is a national restaurant and food service equipment provider with combined experience of 50+ years in the industry. Our mission at SABA is to “offer commercial food-service equipment that not only is competitively priced but also surpasses industry standards in **quality** and technology.”



## CUSTOMER-CENTRIC



Here at SABA, we take pride in our **customer-centric** philosophy, as well as our out-of-the-box solutions. Being progressive minded allows us the ability to quickly adapt to dynamic trends in the industry, so that we can adjust our business model to meet the needs of our customers.

## TECHNICAL SUPPORT

Our company has made substantial investments to engineer products to withstand commercial environments while offering **competitive pricing**. We are committed to provide our clients with highly personalized **after-sale** service and technical support.



## ECO-FRIENDLY



Our company's commitment to continual education and proactive thinking keeps our staff ahead of the game in all facets of the food service equipment industry. With an **eco-friendly** approach when implementing processes and materials for products we can better serve the environment as well as our customers.

## ACCOUNTABLE

You can confidently rely on SABA to hold ourselves and the people we hire **accountable**. We will also do everything in our power to make a positive difference at the point of sale and throughout the life of our equipment.



## SUCCESS



SABA strives to be proactive and **efficient** in every detail of our company. From the materials used in manufacturing to the service technicians we hire to service our units. Our goal is to be the secret to success for our customers by allowing them to focus on the growth of their business rather than their equipment!

# Table of Contents

|                                                 |       |    |
|-------------------------------------------------|-------|----|
| Solid Door Reach-In                             | ----- | 3  |
| Glass Door Reach-In                             | ----- | 4  |
| Glass Door Merchandiser                         | ----- | 5  |
| Sandwich/Salad Prep Table                       | ----- | 6  |
| Mega-Top Sandwich/Salad Prep Table              | ----- | 7  |
| Pizza Prep Table                                | ----- | 8  |
| Under-Counter                                   | ----- | 9  |
| Chef Base                                       | ----- | 10 |
| 24" Depth Back Bar (Glass Door)                 | ----- | 11 |
| 24" Depth Back Bar (Glass Door/Stainless Steel) | ----- | 12 |
| 24" Depth Back Bar (Solid Door)                 | ----- | 13 |
| 24" Depth Back Bar (Stainless Steel)            | ----- | 14 |
| 27" Depth Back Bar (Glass Door)                 | ----- | 15 |
| 27" Depth Back Bar (Solid Door)                 | ----- | 16 |
| 24" Depth Direct Draw Beer Dispenser            | ----- | 17 |
| Draft Beer Dispenser                            | ----- | 18 |
| Bottle Cooler                                   | ----- | 19 |
| Glass Froster                                   | ----- | 20 |
| Deli Case                                       | ----- | 21 |
| Dipping Cabinet                                 | ----- | 22 |
| Warranty                                        | ----- | 23 |



**S-23R  
S-23F**



**S-47R  
S-47F**



**S-72R  
S-72F**

| Model                              | S-23R/S-23F              | S-47R/S-47F                                                                                                  | S-72R/S-72F                                                                                                  |
|------------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Door                               | 1                        | 2                                                                                                            | 3                                                                                                            |
| Shelves                            | 3                        | 6                                                                                                            | 9                                                                                                            |
| Exterior Dimensions<br>(L x D x H) | 29 x 32 ¼ x 82 ½         | 54 x 32 ¼ x 82 ½                                                                                             | 81 x 32 ¼ x 82 ½                                                                                             |
| Capacity cu.ft.                    | 23                       | 47                                                                                                           | 72                                                                                                           |
| HP                                 | 1/4<br>1/2               | 1/2<br>1                                                                                                     | 3/4<br>1-1/4                                                                                                 |
| Voltage                            | 115/60/1                 | 115/60/1                                                                                                     | 115/60/1                                                                                                     |
| Amps                               | 2.76<br>7.92             | 4.56<br>11.16                                                                                                | 10.68<br>13.32                                                                                               |
| Nema Config                        | 5-15P                    | 5-15P<br>5-20P<br>30 amps Circuit Breaker is<br>recommended to be<br>connected to the plug<br>base directly. | 5-15P<br>5-20P<br>30 amps Circuit Breaker is<br>recommended to be<br>connected to the plug base<br>directly. |
| Crated/Uncrated<br>Weight          | 282/337 lb<br>282/337 lb | 447/513 lb<br>495/559 lb                                                                                     | 616/704 lb<br>673/763 lb                                                                                     |

- Bottom mount condensing unit
- Stainless steel interior and exterior
- Rounded corner design for easy cleaning of inside storage
- Heavy duty pull handle; Each door has two spring hinges making the door self-closing
- Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) or -8°F to 0°F (-22°C to -18°C) for optimum food preservation
- Electronic control system: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Adjustable, heavy duty PVC coated shelves
- Standard heavy duty casters make it easy to move and clean underneath

\* Specifications subject to change without notice





**S-23RG  
S-23FG**



**S-47RG  
S-47FG**



**S-72RG  
S-72FG**

| Model                              | S-23RG/S-23FG            | S-47RG/S-47FG                                                                                                | S-72RG/S-72FG                                                                                                |
|------------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Door                               | 1                        | 2                                                                                                            | 3                                                                                                            |
| Shelves                            | 3                        | 6                                                                                                            | 9                                                                                                            |
| Exterior Dimensions<br>(L x D x H) | 29 x 32 ¼ x 82 ½         | 54 x 32 ¼ x 82 ½                                                                                             | 81 x 32 ¼ x 82 ½                                                                                             |
| Capacity cu.ft.                    | 23                       | 47                                                                                                           | 72                                                                                                           |
| HP                                 | 1/4<br>3/4               | 1/2<br>1-1/4                                                                                                 | 3/4<br>1-1/4                                                                                                 |
| Voltage                            | 115/60/1                 | 115/60/1                                                                                                     | 115/60/1                                                                                                     |
| Amps                               | 2.88<br>7.68             | 4.56<br>13.44                                                                                                | 10.92<br>15.89                                                                                               |
| Nema Config                        | 5-15P                    | 5-15P<br>5-20P<br>30 amps Circuit Breaker is<br>recommended to be<br>connected to the plug<br>base directly. | 5-15P<br>5-20P<br>30 amps Circuit Breaker is<br>recommended to be<br>connected to the plug base<br>directly. |
| Crated/Uncrated<br>Weight          | 282/337 lb<br>292/347 lb | 447/513 lb<br>467/533 lb                                                                                     | 616/704 lb<br>646/734 lb                                                                                     |

- Bottom mount condensing unit
- Stainless steel interior and exterior
- Glass Door for ease in checking inventory without opening the doors
- Rounded corner design for easy cleaning of inside storage
- Heavy duty pull handle; Each door has two spring hinges making the door self-closing
- Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) or -8°F to 0°F (-22°C to -18°C) for optimum food preservation
- Electronic control system: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Adjustable, heavy duty PVC coated shelves
- Standard heavy duty casters make it easy to move and clean underneath
- LED lighting: Visibility of products, last longer and consume low energy

\* Specifications subject to change without notice





**SM-13R**  
**SM-13F**



**SM-23R**  
**SM-23F**



**SM-45R**  
**SM-45F**



**SM-45RS**



**SM-72R**  
**SM-72F**

| Model                              | SM-13R/SM-13F                                                                                                                                                                                         | SM-23R/SM-23F                                                                                                                                                                                        | SM-45R/SM-45F                                                                                                                                                            | SM-45RS                                                                                          | SM-72R                                                                                                                                                                                               |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Door                               | 1                                                                                                                                                                                                     | 1                                                                                                                                                                                                    | 2                                                                                                                                                                        | 2                                                                                                | 3                                                                                                                                                                                                    |
| Shelves                            | 4                                                                                                                                                                                                     | 4                                                                                                                                                                                                    | 8                                                                                                                                                                        | 8                                                                                                | 12                                                                                                                                                                                                   |
| Exterior Dimensions<br>(L x D x H) | 25 <sup>5</sup> / <sub>8</sub> x 22 <sup>7</sup> / <sub>8</sub> x 790 <sup>3</sup> / <sub>8</sub><br>27 <sup>3</sup> / <sub>8</sub> x 27 <sup>1</sup> / <sub>2</sub> x 80 <sup>3</sup> / <sub>4</sub> | 28 <sup>3</sup> / <sub>8</sub> x 31 <sup>7</sup> / <sub>8</sub> x 79 <sup>3</sup> / <sub>8</sub><br>31 <sup>1</sup> / <sub>8</sub> x 31 <sup>1</sup> / <sub>4</sub> x 80 <sup>3</sup> / <sub>4</sub> | 53 <sup>1</sup> / <sub>8</sub> x 32 x 79 <sup>3</sup> / <sub>8</sub><br>53 <sup>1</sup> / <sub>8</sub> x 31 <sup>7</sup> / <sub>8</sub> x 79 <sup>3</sup> / <sub>8</sub> | 53 <sup>1</sup> / <sub>8</sub> x 31 <sup>7</sup> / <sub>8</sub> x 79 <sup>3</sup> / <sub>8</sub> | 78 <sup>1</sup> / <sub>4</sub> x 29 <sup>7</sup> / <sub>8</sub> x 80 <sup>7</sup> / <sub>8</sub><br>79 <sup>1</sup> / <sub>2</sub> x 30 <sup>5</sup> / <sub>8</sub> x 80 <sup>3</sup> / <sub>4</sub> |
| Capacity cu.ft.                    | 13                                                                                                                                                                                                    | 23                                                                                                                                                                                                   | 45                                                                                                                                                                       | 45                                                                                               | 63                                                                                                                                                                                                   |
| HP                                 | 1/4<br>3/4                                                                                                                                                                                            | 1/3<br>3/4                                                                                                                                                                                           | 3/4<br>1 1/4                                                                                                                                                             | 1/2                                                                                              | 3/4 +<br>(2) 3/4 +                                                                                                                                                                                   |
| Voltage                            | 115/60/1                                                                                                                                                                                              | 115/60/1                                                                                                                                                                                             | 115/60/1                                                                                                                                                                 | 115/60/1                                                                                         | 115/60/1                                                                                                                                                                                             |
| Amps                               | 2.88<br>8.76                                                                                                                                                                                          | 3<br>9.36                                                                                                                                                                                            | 4.44<br>10.56                                                                                                                                                            | 4.32                                                                                             | 10.68<br>16.3                                                                                                                                                                                        |
| Nema Config                        | 5-15P                                                                                                                                                                                                 | 5-15P                                                                                                                                                                                                | 5-15P<br>5-20P                                                                                                                                                           | 5-15P                                                                                            | 5-20P                                                                                                                                                                                                |
| Crated/Uncrated<br>Weight          | 220/225 lb<br>374/418 lb                                                                                                                                                                              | 284/319 lb<br>506/550 lb                                                                                                                                                                             | 440/495 lb<br>572/627 lb                                                                                                                                                 | 440/495 lb                                                                                       | 614/704 lb<br>770/836 lb                                                                                                                                                                             |

- Bottom mount condensing unit
- Rounded corner design for easy cleaning of inside storage
- Double and/or triple pane thermal insulated glass door with aluminum frames
- Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) or -10°F to 0°F (-23°C to -18°C) for optimum food preservation
- Electronic control system: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Adjustable, heavy duty PVC coated shelves
- Standard heavy duty casters make it easy to move and clean underneath
- LED lighting: Visibility of products, last longer and consume low energy
- Lighted to panel: Lighted panel above the cabinet making the merchandiser more eye-catching

\* Specifications subject to change without notice.



# Sandwich/Salad Prep Table



**SPS-27-8**



**SPS-48-12**



**SPS-60-16**



**SPS-72-18**

| Model                              | SPS-27-8           | SPS-48-12          | SPS-60-16          | SPS-72-18         |
|------------------------------------|--------------------|--------------------|--------------------|-------------------|
| Door                               | 1                  | 2                  | 2                  | 3                 |
| Shelves                            | 1                  | 2                  | 2                  | 3                 |
| Exterior Dimensions<br>(L x D x H) | 27 ½ x 29 ½ x 42 ¼ | 46 ¾ x 29 ½ x 42 ¼ | 60 ¼ x 29 ½ x 42 ¼ | 70 ¾ x 29 ½ x 42¼ |
| Capacity cu.ft.                    | 5.7                | 9.5                | 15                 | 15.5              |
| HP                                 | 1/4                | 1/3                | 1/3                | 1/2               |
| Voltage                            | 115/60/1           | 115/60/1           | 115/60/1           | 115/60/1          |
| Amps                               | 4.4                | 6.1                | 6.7                | 8.6               |
| Nema Config                        | 5-15P              | 5-15P              | 5-15P              | 5-15P             |
| Crated/Uncrated<br>Weight          | 187/255 lb         | 271/394 lb         | 319/451 lb         | 378/513 lb        |

- Stainless steel interior and exterior and aluminum finished back
- Rounded corner design for easy cleaning of inside storage
- Positive seal self-closing door(s) with 90 degrees stay open feature
- Magnetic door gasket(s) with no tools removal for easy cleaning
- Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) for optimum food preservation
- Electronic control system: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Adjustable, heavy duty PVC coated shelves
- Standard heavy duty casters make it easy to move and clean underneath
- Condensing unit access in back of cabinet, slides out for easy maintenance
- Insulated lid on prep units helps maintain food freshness
- Analog temperature control: Easy adjust the temperature and the thermostat allows you to easily keep track of the units temperature in order to keep products properly cool
- Cutting board is easily secured and is easy to remove for cleaning

\* Specifications subject to change without notice.



# Mega-Top Sandwich/Salad Prep Table



**SPS-27-12M**



**SPS-36-15M**



**SPS-48-18M**



**SPS-60-24M**



**SPS-72-30M**

| Model                              | SPS-27-12M       | SPS-36-15M       | SPS-48-18M       | SPS-60-24M       | SPS-72-30M       |
|------------------------------------|------------------|------------------|------------------|------------------|------------------|
| Door                               | 1                | 2                | 2                | 2                | 3                |
| Shelves                            | 1                | 2                | 2                | 2                | 3                |
| Exterior Dimensions<br>(L x D x H) | 27 ½ x 34 x 45 ¾ | 36 ¼ x 34 x 45 ¾ | 46 ¾ x 34 x 45 ¾ | 60 ¼ x 34 x 45 ¾ | 70 ¼ x 34 x 45 ¾ |
| Capacity cu.ft.                    | 5.7              | 7.8              | 9.5              | 15               | 15.5             |
| HP                                 | 1/4              | 1/4              | 1/3              | 1/3              | 1/2              |
| Voltage                            | 115/60/1         | 115/60/1         | 115/60/1         | 115/60/1         | 115/60/1         |
| Amps                               | 4.4              | 5.2              | 6.1              | 6.7              | 8.6              |
| Nema Config                        | 5-15P            | 5-15P            | 5-15P            | 5-15P            | 5-15P            |
| Crated/Uncrated<br>Weight          | 198/264 lb       | 253/352 lb       | 282/407 lb       | 330/462 lb       | 396/528 lb       |

- Stainless steel interior and exterior and aluminum finished back
- Rounded corner design for easy cleaning of inside storage
- Positive seal self-closing door(s) with 90 degrees stay open feature
- Magnetic door gasket(s) with no tools removal for easy cleaning
- Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) for optimum food preservation
- Electronic control system: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Adjustable, heavy duty PVC coated shelves
- Standard heavy duty casters make it easy to move and clean underneath
- Condensing unit access in back of cabinet, slides out for easy maintenance
- Insulated lid on prep units helps maintain food freshness
- Analog temperature control: Easy adjust the temperature and the thermostat allows you to easily keep track of the units temperature in order to keep products properly cool
- Cutting board is easily secured and is easy to remove for cleaning

\* Specifications subject to change without notice.



# Pizza Prep Table



**SPP-44-6**



**SPP-67-9**



**SPP-91-12**

| Model                              | SPP-44-6           | SPP-67-9          | SPP-91-12        |
|------------------------------------|--------------------|-------------------|------------------|
| Door                               | 1                  | 2                 | 3                |
| Shelves                            | 1                  | 2                 | 3                |
| Exterior Dimensions<br>(L x D x H) | 44-½ x 31 ½ x 39 ¾ | 67 ¼ x 31 ½x 39 ¾ | 92 x 31 ½ x 39 ¾ |
| Capacity cu.ft.                    | 13                 | 16                | 24.2             |
| HP                                 | 1/4+               | 1/3+              | 1/2+             |
| Voltage                            | 115/60/1           | 115/60/1          | 115/60/1         |
| Amps                               | 4                  | 5.9               | 7.2              |
| Nema Config                        | 5-15P              | 5-15P             | 5-15P            |
| Crated/Uncrated<br>Weight          | 374/497 lb         | 431/563 lb        | 565/719 lb       |

- Stainless steel interior and exterior and aluminum finished back
- Rounded corner design for easy cleaning of inside storage
- Positive seal self-closing door(s) with 90 degrees stay open feature
- Magnetic door gasket(s) with no tools removal for easy cleaning
- Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) for optimum food preservation
- Electronic control system: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Adjustable, heavy duty PVC coated shelves
- Standard heavy duty casters make it easy to move and clean underneath
- Condensing unit access in back of cabinet, slides out for easy maintenance
- Insulated lid on prep units helps maintain food freshness
- Analog temperature control: Easy adjust the temperature and the thermostat allows you to easily keep track of the units temperature in order to keep products properly cool
- Cutting board is easily secured and is easy to remove for cleaning

\* Specifications subject to change without notice.





**SUC-27R**  
**SUC-27F**



**SUC-48R**  
**SUC-48F**



**SUC-60R**



**SUC-72R**

| Model                              | SUC-27R/SUC-27F          | SUC-48R/SUC-48F          | SUC-60R                  | SUC-72R        |
|------------------------------------|--------------------------|--------------------------|--------------------------|----------------|
| Door                               | 1                        | 2                        | 2                        | 3              |
| Shelves                            | 1                        | 2                        | 2                        | 3              |
| Exterior Dimensions<br>(L x D x H) | 27 x 29 ½ x 34           | 47 ¼ x 29 ½ x 34         | 60 ¼ x 29 ½ x 34         | 72 x 29 ½ x 34 |
| Capacity cu.ft.                    | 6.3                      | 12                       | 15                       | 15.5           |
| HP                                 | 1/4<br>1/2               | 1/3<br>1/2               | 1/3<br>1/2               | 1/2            |
| Voltage                            | 115/60/1                 | 115/60/1                 | 115/60/1                 | 115/60/1       |
| Amps                               | 1.92<br>2.04             | 2.76<br>3.12             | 2.88<br>6.36             | 3.24           |
| Nema Config                        | 5-15P                    | 5-15P                    | 5-15P                    | 5-15P          |
| Crated/Uncrated<br>Weight          | 169/220 lb<br>178/233 lb | 238/299 lb<br>251/312 lb | 275/341 lb<br>290/356 lb | 330/407 lb     |

- Stainless steel interior and exterior with aluminum finished back
- Rounded corner design for easy cleaning of inside storage
- Positive seal self-closing door(s) with 90 degrees stay open feature
- Magnetic door gasket(s) with no tools removal for easy cleaning
- Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) or -8°F to 0°F (-22°C to -18°C) for optimum food preservation
- Electronic control system: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Adjustable, heavy duty PVC coated shelves
- Standard heavy duty casters make it easy to move and clean underneath
- Condensing unit access in back of cabinet, slides out for easy maintenance

\* Specifications subject to change without notice.



# Chef Base Drawer Refrigerator



**SCB-36**



**SCB-52**



**SCB-72**

| Model                              | SCB-36                                                                                           | SCB-52                                                                                           | SCB-72                                                                                           |
|------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| Drawers                            | 2                                                                                                | 2                                                                                                | 4                                                                                                |
| GN Pans                            | 2*1/1 + 6*1/6                                                                                    | 6*1/1                                                                                            | 8*1/1                                                                                            |
| Exterior Dimensions<br>(L x D x H) | 36 <sup>3</sup> / <sub>8</sub> x 32 <sup>1</sup> / <sub>8</sub> x 25 <sup>3</sup> / <sub>8</sub> | 51 <sup>7</sup> / <sub>8</sub> x 32 <sup>1</sup> / <sub>8</sub> x 25 <sup>3</sup> / <sub>8</sub> | 72 <sup>3</sup> / <sub>8</sub> x 32 <sup>1</sup> / <sub>8</sub> x 25 <sup>3</sup> / <sub>8</sub> |
| Capacity cu.ft.                    | 2 full size pans                                                                                 | 6 full size pans                                                                                 | 8 full size pans                                                                                 |
| HP                                 | 1/6                                                                                              | 1/4                                                                                              | 1/3                                                                                              |
| Voltage                            | 115/60/1                                                                                         | 115/60/1                                                                                         | 115/60/1                                                                                         |
| Amps                               | 3.48                                                                                             | 4.56                                                                                             | 6.36                                                                                             |
| Nema Config                        | 5-15P                                                                                            | 5-15P                                                                                            | 5-15P                                                                                            |
| Crated/Uncrated<br>Weight          | 242/279 lb                                                                                       | 286/341 lb                                                                                       | 396/484 lb                                                                                       |

- Stainless steel interior and exterior with aluminum finished back
- Rounded corner design for easy cleaning of inside storage
- Cabinet top is one piece, heavy duty reinforced stainless steel
- Drip resistant "V" edge protects against spills
- Refrigeration system holds 33°F to 41°F (0.5°C to 5°C) for optimum food preservation
- Electronic control system: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Heavy duty pull handle; each drawer with tracks and rollers for ease in opening and closing
- Standard heavy duty casters make it easy to move and clean underneath
- Easily accessible condenser coil for cleaning and easy service access
- Simple installation with no plumbing required

\* Specifications subject to change without notice



## 24" Depth Back Bar Cooler (Glass Door)



**SBB-24-48G**



**SBB-24-60G**



**SBB-24-72G**

| Model                              | SBB-24-48G                                             | SBB-24-60G                                             | SBB-24-72G                                             |
|------------------------------------|--------------------------------------------------------|--------------------------------------------------------|--------------------------------------------------------|
| Doors                              | 2                                                      | 2                                                      | 3                                                      |
| Exterior Dimensions<br>(L x D x H) | 48 $\frac{7}{8}$ x 24 $\frac{3}{8}$ x 35 $\frac{5}{8}$ | 60 $\frac{7}{8}$ x 24 $\frac{3}{8}$ x 35 $\frac{5}{8}$ | 72 $\frac{7}{8}$ x 24 $\frac{3}{8}$ x 35 $\frac{5}{8}$ |
| Capacity cu.ft.                    | 11.8                                                   | 15.8                                                   | 19.6                                                   |
| HP                                 | 1/3                                                    | 1/3                                                    | 1/3                                                    |
| Voltage                            | 115/60/1                                               | 115/60/1                                               | 115/60/1                                               |
| Amps                               | 2.88                                                   | 2.88                                                   | 3.96                                                   |
| Nema Config                        | 5-15P                                                  | 5-15P                                                  | 5-15P                                                  |
| Crated/Uncrated<br>Weight          | 216/260 lb                                             | 255/319 lb                                             | 310/385 lb                                             |

- Standard cabinet exterior construction includes attractive, wear resistant vinyl on steel in black finish
- Standard interior construction utilizes stainless steel walls, floor and ceiling
- Refrigeration system uses R134a Refrigerant which is CFC and HCFC-free for compliance with environmental safety concerns
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- NSF-7 approved for packaged and bottled product
- LED lighting: Visibility of products, last longer and consume low energy
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Easily accessible condenser coil for cleaning and easy service access
- Designed to accommodate a variety of beer kegs

\* Specifications subject to change without notice



## 24" Depth Back Bar Cooler (Glass Door/Stainless Steel)



**SBB-24-48GSS**



**SBB-24-60GSS**



**SBB-24-72GSS**

| Model                              | SBB-24-48GSS                                                                                     | SBB-24-60GSS                                                                                     | SBB-24-72GSS                                                                                     |
|------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| Doors                              | 2                                                                                                | 2                                                                                                | 3                                                                                                |
| Exterior Dimensions<br>(L x D x H) | 48 <sup>7</sup> / <sub>8</sub> x 24 <sup>3</sup> / <sub>8</sub> x 35 <sup>5</sup> / <sub>8</sub> | 60 <sup>7</sup> / <sub>8</sub> x 24 <sup>3</sup> / <sub>8</sub> x 35 <sup>5</sup> / <sub>8</sub> | 72 <sup>7</sup> / <sub>8</sub> x 24 <sup>3</sup> / <sub>8</sub> x 35 <sup>5</sup> / <sub>8</sub> |
| Capacity cu.ft.                    | 11.8                                                                                             | 15.8                                                                                             | 19.6                                                                                             |
| HP                                 | 1/3                                                                                              | 1/3                                                                                              | 1/3                                                                                              |
| Voltage                            | 115/60/1                                                                                         | 115/60/1                                                                                         | 115/60/1                                                                                         |
| Amps                               | 2.88                                                                                             | 2.88                                                                                             | 3.96                                                                                             |
| Nema Config                        | 5-15P                                                                                            | 5-15P                                                                                            | 5-15P                                                                                            |
| Crated/Uncrated<br>Weight          | 216/260 lb                                                                                       | 255/319 lb                                                                                       | 310/385 lb                                                                                       |

- Standard Stainless exterior
- Standard interior construction utilizes stainless steel walls, floor and ceiling
- Refrigeration system uses R134a Refrigerant which is CFC and HCFC-free for compliance with environmental safety concerns
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- NSF-7 approved for packaged and bottled product
- LED lighting: Visibility of products, last longer and consume low energy
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Easily accessible condenser coil for cleaning and easy service access
- Designed to accommodate a variety of beer kegs

\* Specifications subject to change without notice



## 24" Depth Back Bar Cooler (Solid Door)



**SBB-24-48B**



**SBB-24-60B**



**SBB-24-72B**

| Model                              | SBB-24-48B                                             | SBB-24-60B                                             | SBB-24-72B                                             |
|------------------------------------|--------------------------------------------------------|--------------------------------------------------------|--------------------------------------------------------|
| Doors                              | 2                                                      | 2                                                      | 3                                                      |
| Exterior Dimensions<br>(L x D x H) | 48 $\frac{7}{8}$ x 24 $\frac{3}{8}$ x 35 $\frac{5}{8}$ | 60 $\frac{7}{8}$ x 24 $\frac{3}{8}$ x 35 $\frac{5}{8}$ | 72 $\frac{7}{8}$ x 24 $\frac{3}{8}$ x 35 $\frac{5}{8}$ |
| Capacity cu.ft.                    | 11.8                                                   | 15.8                                                   | 19.6                                                   |
| HP                                 | 1/3                                                    | 1/3                                                    | 1/3                                                    |
| Voltage                            | 115/60/1                                               | 115/60/1                                               | 115/60/1                                               |
| Amps                               | 2.88                                                   | 2.88                                                   | 3.96                                                   |
| Nema Config                        | 5-15P                                                  | 5-15P                                                  | 5-15P                                                  |
| Crated/Uncrated<br>Weight          | 216/260 lb                                             | 255/319 lb                                             | 310/385 lb                                             |

- Standard cabinet exterior construction includes attractive, wear resistant vinyl on steel in black finish
- Standard interior construction utilizes stainless steel walls, floor and ceiling
- Refrigeration system uses R134a Refrigerant which is CFC and HCFC-free for compliance with environmental safety concerns
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- NSF-7 approved for packaged and bottled product
- LED lighting: Visibility of products, last longer and consume low energy
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Easily accessible condenser coil for cleaning and easy service access
- Designed to accommodate a variety of beer kegs

\* Specifications subject to change without notice



## 24" Depth Back Bar Cooler (Stainless Steel)



**SBB-24-48SS**



**SBB-24-60SS**



**SBB-24-72SS**

| Model                              | SBB-24-48SS                                            | SBB-24-60SS                                            | SBB-24-72SS                                            |
|------------------------------------|--------------------------------------------------------|--------------------------------------------------------|--------------------------------------------------------|
| Doors                              | 2                                                      | 2                                                      | 3                                                      |
| Exterior Dimensions<br>(L x D x H) | 48 $\frac{7}{8}$ x 24 $\frac{3}{8}$ x 35 $\frac{5}{8}$ | 60 $\frac{7}{8}$ x 24 $\frac{3}{8}$ x 35 $\frac{5}{8}$ | 72 $\frac{7}{8}$ x 24 $\frac{3}{8}$ x 35 $\frac{5}{8}$ |
| Capacity cu.ft.                    | 11.8                                                   | 15.8                                                   | 19.6                                                   |
| HP                                 | 1/3                                                    | 1/3                                                    | 1/3                                                    |
| Voltage                            | 115/60/1                                               | 115/60/1                                               | 115/60/1                                               |
| Amps                               | 2.88                                                   | 2.88                                                   | 3.96                                                   |
| Nema Config                        | 5-15P                                                  | 5-15P                                                  | 5-15P                                                  |
| Crated/Uncrated<br>Weight          | 216/260 lb                                             | 255/319 lb                                             | 310/385 lb                                             |

- All-stainless steel
- Standard interior construction utilizes stainless steel walls, floor and ceiling
- Refrigeration system uses R134a Refrigerant which is CFC and HCFC-free for compliance with environmental safety concerns
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- NSF-7 approved for packaged and bottled product
- LED lighting: Visibility of products, last longer and consume low energy
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Easily accessible condenser coil for cleaning and easy service access
- Designed to accommodate a variety of beer kegs
- Self –Closing/Lockable doors: Positive seal, self-closing door(s) to help conserve energy and security

\* Specifications subject to change without notice



## 27" Depth Back Bar Cooler (Glass Door)



**SBB-27-23G**



**SBB-27-58G**



**SBB-27-69G**



**SBB-27-90G**

| Model                                   | SBB-27-23G         | SBB-27-58G             | SBB-27-69G             | SBB-27-90G             |
|-----------------------------------------|--------------------|------------------------|------------------------|------------------------|
| Doors                                   | 1                  | 2                      | 2                      | 3                      |
| Exterior Dimensions<br>(L x D x H)      | 23 ½ x 30 ¾ x 38 ¾ | 58 7/8 x 27 ¾ x 35 5/8 | 69 1/8 x 27 ¾ x 35 5/8 | 90 3/8 x 27 ¾ x 35 5/8 |
| Capacity:<br>1/2 Barrels<br>12 oz. Cans | 1<br>30 6-pks      | 2<br>88 6-pks          | 3<br>112 6-pks         | 4<br>152 6-pks         |
| HP                                      | 1/6+               | 1/3+                   | 1/3+                   | 1/3+                   |
| Voltage                                 | 115/60/1           | 115/60/1               | 115/60/1               | 115/60/1               |
| Amps                                    | 1.92               | 2.88                   | 3.6                    | 4.68                   |
| Nema Config                             | 5-15P              | 5-15P                  | 5-15P                  | 5-15P                  |
| Crated/Uncrated<br>Weight               | 161/172 lb         | 275/308 lb             | 319/359 lb             | 363/418 lb             |

- Standard cabinet exterior construction includes attractive, wear resistant vinyl on steel in black finish
- Standard interior construction utilizes stainless steel walls, floor and ceiling
- Refrigeration system uses R134a Refrigerant which is CFC and HCFC-free for compliance with environmental safety concerns
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- NSF-7 approved for packaged and bottled product
- LED lighting: Visibility of products, last longer and consume low energy
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Easily accessible condenser coil for cleaning and easy service access
- Designed to accommodate a variety of beer kegs
- Self –Closing/Lockable doors: Positive seal, self-closing door(s) to help conserve energy and security

\* Specifications subject to change without notice



## 27" Depth Back Bar Cooler (Solid Door)



**SBB-27-23B**



**SBB-27-58B**



**SBB-27-69B**



**SBB-27-90B**

| Model                                   | SBB-27-23B         | SBB-27-58B             | SBB-27-69B             | SBB-27-90B             |
|-----------------------------------------|--------------------|------------------------|------------------------|------------------------|
| Doors                                   | 1                  | 2                      | 2                      | 3                      |
| Exterior Dimensions<br>(L x D x H)      | 23 ½ x 30 ¾ x 38 ¾ | 58 7/8 x 27 ¾ x 35 5/8 | 69 1/8 x 27 ¾ x 35 5/8 | 90 3/8 x 27 ¾ x 35 5/8 |
| Capacity:<br>1/2 Barrels<br>12 oz. Cans | 1<br>30 6-pks      | 2<br>88 6-pks          | 3<br>112 6-pks         | 4<br>152 6-pks         |
| HP                                      | 1/6+               | 1/3+                   | 1/3+                   | 1/3+                   |
| Voltage                                 | 115/60/1           | 115/60/1               | 115/60/1               | 115/60/1               |
| Amps                                    | 1.92               | 2.88                   | 3.6                    | 3.84                   |
| Nema Config                             | 5-15P              | 5-15P                  | 5-15P                  | 5-15P                  |
| Crated/Uncrated<br>Weight               | 161/172 lb         | 275/308 lb             | 319/359 lb             | 363/418 lb             |

- Standard cabinet exterior construction includes attractive, wear resistant vinyl on steel in black finish
- Standard interior construction utilizes stainless steel walls, floor and ceiling
- Refrigeration system uses R134a Refrigerant which is CFC and HCFC-free for compliance with environmental safety concerns
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- NSF-7 approved for packaged and bottled product
- LED lighting: Visibility of products, last longer and consume low energy
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Easily accessible condenser coil for cleaning and easy service access
- Designed to accommodate a variety of beer kegs
- Self –Closing/Lockable doors: Positive seal, self-closing door(s) to help conserve energy and security

\* Specifications subject to change without notice



## 24" Depth Direct Draw Beer Dispenser

**SABA**



**SDD-24-48**



**SDD-24-60**



**SDD-24-72**

| Model                              | SDD-24-48                | SDD-24-60                | SDD-24-72                |
|------------------------------------|--------------------------|--------------------------|--------------------------|
| Doors                              | 2                        | 2                        | 3                        |
| Exterior Dimensions<br>(L x D x H) | 48 1/8 x 24 3/8 x 35 5/8 | 60 3/4 x 24 3/8 x 35 5/8 | 72 3/4 x 24 3/8 x 35 5/8 |
| Capacity<br>1/2 Barrels            | 2                        | 2                        | 3                        |
| HP                                 | 1/3+                     | 1/3+                     | 1/3+                     |
| Voltage                            | 115/60/1                 | 115/60/1                 | 115/60/1                 |
| Amps                               | 3                        | 3                        | 3.96                     |
| Nema Config                        | 5-15P                    | 5-15P                    | 5-15P                    |
| Crated/Uncrated<br>Weight          | 216/260 lb               | 255/319 lb               | 310/385 lb               |

- Standard cabinet exterior construction includes attractive, wear resistant vinyl on steel in black finish
- Standard interior construction utilizes stainless steel walls, floor and ceiling
- Refrigeration system uses R134a Refrigerant which is CFC and HCFC-free for compliance with environmental safety concerns
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- NSF-7 approved for packaged and bottled product
- LED lighting: Visibility of products, last longer and consume low energy
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Easily accessible condenser coil for cleaning and easy service access
- Designed to accommodate a variety of beer kegs
- Self –Closing/Lockable doors: Positive seal, self-closing door(s) to help conserve energy and security

\* Specifications subject to change without notice





**SDD-30-23**



**SDD-27-58**



**SDD-27-69**



**SDD-27-90**

| Model                              | SDD-30-23          | SDD-27-58              | SDD-27-69              | SDD-27-90              |
|------------------------------------|--------------------|------------------------|------------------------|------------------------|
| Doors                              | 1                  | 2                      | 2                      | 3                      |
| Exterior Dimensions<br>(L x D x H) | 23 ½ x 30 ¾ x 38 ¾ | 58 7/8 x 27 ¾ x 35 5/8 | 69 1/8 x 27 ¾ x 35 5/8 | 90 3/8 x 27 ¾ x 35 5/8 |
| Capacity<br>1/2 Barrels            | 1                  | 2                      | 3                      | 4                      |
| HP                                 | 1/6+               | 1/3+                   | 1/3+                   | 1/3+                   |
| Voltage                            | 115/60/1           | 115/60/1               | 115/60/1               | 115/60/1               |
| Amps                               | 1.92               | 2.88                   | 3.6                    | 4.68                   |
| Nema Config                        | 5-15P              | 5-15P                  | 5-15P                  | 5-15P                  |
| Crated/Uncrated<br>Weight          | 165/176 lb         | 279/312 lb             | 326/367 lb             | 374/429 lb             |

- Stainless steel tops with drain line and drip trays are standard
- Standard stainless steel floor and inner wall
- Space-saving side mounted evaporator optimizes interior cabinet space
- Cold air is directed into draft towers ensuring optimum beer dispensing
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- NSF-7 approved for packaged and bottled product
- LED lighting: Visibility of products, last longer and consume low energy
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Easily accessible condenser coil for cleaning and easy service access
- Designed to accommodate a variety of beer kegs
- Self –Closing/Lockable doors: Positive seal, self-closing door(s) to help conserve energy and security

\* Specifications subject to change without notice





**SBC-25B**



**SBC-50B**



**SBC-65B**



**SBC-95B**

| Model                                     | SBC-25B                                                                                          | SBC-50B                                                                                          | SBC-65B                                                                                          | SBC-95B                                                                                          |
|-------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| Lids                                      | 1                                                                                                | 2                                                                                                | 2                                                                                                | 3                                                                                                |
| Exterior Dimensions<br>(L x D x H)        | 26 <sup>3</sup> / <sub>8</sub> x 26 <sup>5</sup> / <sub>8</sub> x 34 <sup>1</sup> / <sub>4</sub> | 49 <sup>1</sup> / <sub>2</sub> x 26 <sup>5</sup> / <sub>8</sub> x 34 <sup>1</sup> / <sub>4</sub> | 64 <sup>1</sup> / <sub>2</sub> x 26 <sup>5</sup> / <sub>8</sub> x 34 <sup>1</sup> / <sub>4</sub> | 95 <sup>1</sup> / <sub>4</sub> x 26 <sup>5</sup> / <sub>8</sub> x 34 <sup>1</sup> / <sub>4</sub> |
| Capacity<br>12 oz. Bottles<br>12 oz. Cans | 4.5 cases<br>6 cases                                                                             | 16.5 cases<br>24 cases                                                                           | 22 cases<br>32 cases                                                                             | 37.5 cases<br>55 cases                                                                           |
| HP                                        | 1/6                                                                                              | 1/4                                                                                              | 1/3+                                                                                             | 1/2+                                                                                             |
| Voltage                                   | 115/60/1                                                                                         | 115/60/1                                                                                         | 115/60/1                                                                                         | 115/60/1                                                                                         |
| Amps                                      | 2.04                                                                                             | 2.28                                                                                             | 2.64                                                                                             | 4.2                                                                                              |
| Nema Config                               | 5-15P                                                                                            | 5-15P                                                                                            | 5-15P                                                                                            | 5-15P                                                                                            |
| Crated/Uncrated<br>Weight                 | 154/176 lb                                                                                       | 220/253 lb                                                                                       | 253/286 lb                                                                                       | 363/429 lb                                                                                       |

- Exteriors include attractive wear-resistant vinyl on steel in black finish with stainless steel top
- Interior: 304 stainless steel floors with smooth white finish on interior sides
- Standard removable bottle cap opener and cap catcher
- Aluminum coated interior metal and epoxy coated steel wire adjustable dividers
- Oversized, factory balanced, refrigeration system holds 33°F to 38°F (0.5°C to 3.3°C)
- NSF-7 approved for packaged and bottled product
- Guided airflow cools bottles on top first
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Condensing units slides out for easy maintenance

\* Specifications subject to change without notice





**SGF-25**



**SGF-50**

| Model                                        | SGF-25                                                 | SGF-50                                                 |
|----------------------------------------------|--------------------------------------------------------|--------------------------------------------------------|
| Lids                                         | 1                                                      | 2                                                      |
| Exterior Dimensions<br>(L x D x H)           | 26 $\frac{3}{8}$ x 26 $\frac{5}{8}$ x 34 $\frac{1}{4}$ | 49 $\frac{1}{2}$ x 26 $\frac{5}{8}$ x 34 $\frac{1}{4}$ |
| Capacity:<br>10 oz. Steins<br>8"(204 mm)Mugs | 85<br>90                                               | 240<br>250                                             |
| HP                                           | 1/3                                                    | 1/2                                                    |
| Voltage                                      | 115/60/1                                               | 115/60/1                                               |
| Amps                                         | 2.04                                                   | 3                                                      |
| Nema Config                                  | 5-15P                                                  | 5-15P                                                  |
| Crated/Uncrated<br>Weight                    | 154/176 lb                                             | 220/253 lb                                             |

- Exteriors include attractive wear-resistant vinyl on steel in black finish with stainless steel top
- Interior: 304 stainless steel floors with smooth white finish on interior sides
- Aluminum coated interior metal and epoxy coated steel wire adjustable dividers
- Oversized, factory balanced, refrigeration system holds 0°F (-17.7°C)
- NSF-7 approved for packaged and bottled product
- Guided airflow cools bottles on top first
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Condensing units slides out for easy maintenance
- Large storage capacity to meet the supply and demand

\* Specifications subject to change without notice





**SCGG-47**



**SCGG-78**

| Model                              | SCGG-47            | SCGG-78          |
|------------------------------------|--------------------|------------------|
| Doors                              | 2                  | 3                |
| Shelves                            | 6                  | 9                |
| Exterior Dimensions<br>(L x D x H) | 47 ¼ x 32 ½ x 42 ⅞ | 82 x 32 ½ x 42 ⅞ |
| Capacity cu.ft.                    | 18                 | 32               |
| HP                                 | 1/3                | 1/2              |
| Voltage                            | 115/60/1           | 115/60/1         |
| Amps                               | 3.12               | 7.08             |
| Nema Config                        | 5-15P              | 5-15P            |
| Crated/Uncrated<br>Weight          | 319/429 lb         | 506/638 lb       |

- Exteriors include attractive wear-resistant vinyl on steel in black finish with stainless steel top and floor
- Rounded corner design for easy cleaning of inside storage
- Double pane, curved Tempering frontal glass
- Gravity coil refrigeration system provides high humidity environment for exceptional preservation of meats and deli products
- NSF-7 approved for packaged and bottled product
- Adjustable, heavy duty PVC coated shelves
- Digital temperature control: Adjustable temperature set point and defrost frequency as well as error codes to diagnose service issues
- Standard heavy duty casters make it easy to move and clean underneath
- Easily accessible condenser coil for cleaning and easy service access

\* Specifications subject to change without notice



# Dipping Cabinet

**SABA**



**SDC-46**



**SDC-66**

| Model                                   | SDC-46                              | SDC-66                               |
|-----------------------------------------|-------------------------------------|--------------------------------------|
| Lids                                    | 1                                   | 2                                    |
| Exterior Dimensions<br>(L x D x H)      | 47 x 27 ¾ x 51 ⅛                    | 67 ¾ x 27 ¾ x 51 ⅛                   |
| Capacity<br>3 Gallon (12 Liter)<br>Cans | 13 Total<br>(Display 8 & Storage 5) | 20 Total<br>(Display 12 & Storage 8) |
| HP                                      | 1/4+                                | 1/2+                                 |
| Voltage                                 | 115/60/1                            | 115/60/1                             |
| Amps                                    | 5.16                                | 5.64                                 |
| Nema Config                             | 5-15P                               | 5-15P                                |
| Crated/Uncrated<br>Weight               | 240/345 lb                          | 310/431 lb                           |

- Exterior - high quality white powder coat finish on steel.
- Interior - powder coat finish on aluminum.
- Top - 300 stainless steel top and attached frame structure.
- Plain glass - plain glass front and side glass panels provide extra large viewing area to maximize ice cream presentation
- Refrigeration system: R290 Cold wall refrigeration system. Maintains -10°F to +0°F (-23.3°C to -18°C).
- ETL safety and NSF-7 sanitation approved.
- Night covers for case opening.
- Electronic control system: Adjustable temperature set point and defrost frequency Error codes to diagnose service issues
- Display and Storage: Designed to hold 3 gallon (12 L) ice cream containers in display and beneath area
- LED lamp provides more even lighting throughout the cabinet to enhance product appearance.

\* Specifications subject to change without notice



---

## Warranty Claims

All claims for parts or labor must be made directly through SABA. All claims should include: model number of the unit, the serial number, proof of purchase, date of installation, and all pertinent information supporting the alleged defect. In case of compressor replacement under warranty, either compressor or compressor tag must be returned to SABA along with above listed information. Failure to comply with warranty policies will result in voiding claims.

SABA warrants all new refrigerated components, the cabinet and all parts, to be free from defects in materials or workmanship, under normal and proper use and maintenance service as specified by SABA and upon proper installation\* (indoor building only) and start-up in accordance with the instruction packet supplied with each SABA unit. SABA's obligation under this warranty is limited to a period of one (1) year from the date of original installation or twelve (12) months after shipment date from SABA, whichever occurs first. Any part, covered under this warranty, that are by SABA to have been defective within one (1) year of original installation or twelve (12) months after shipment date from manufacturer, whichever occurs first, is limited to the repair or replacement, including labor charges, of defective parts or assemblies. The labor warranty shall include standard straight time labor charges only and reasonable travel time, as determined by SABA.

(\*Installation in unstable, mobile, and enclosed area may not be considered as proper installation. Remote units are limited to one-year parts warranty, relative only to original cabinet components. No labor will be covered)

## Additional Three-Year Compressor Warranty

In addition to the one (1) year warranty stated above, SABA warrants its compressor to be free from defects in both material and workmanship under normal and proper use and maintenance service for a period of four (4) additional years from the date of original installation, but not to exceed five (5) years. Compressor determined by SABA to have been defective within this extended period will, at SABA's discretion, be either repaired or replaced with a compressor or compressor parts of similar design and capacity. The four (4) year extended compressor warranty applies only to hermetically sealed parts of the compressor and does not apply to any other parts or components, including, but not limited to, cabinet, paint finish, temperature control, refrigerant, metering device, driers, motor starting equipment, fan assembly or and other electrical components, etc.

## What is Not Covered by This Warranty

SABA's sole obligation under this warranty is limited to either repair or replacement of parts, subject to the additional limitations below. This warranty neither assumes nor authorizes any person to assume obligations other than those expressly covered by this warranty. NO CONSEQUENTIAL DAMAGES. SABA IS NOT RESPONSIBLE FOR ECONOMIC LOSS; PROFIT LOSS; OR SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOSSES, OR DAMAGES ARISING FROM FOOD OR PRODUCT SPOILAGE REGARDLESS OF WHETHER OR NOT THEY RESULT FROM REFRIGERATION FAILURE. PROPER VENTILATION (3" INCHES) AROUND THE UNIT AREA INDOOR IS A NECESSITY FOR THE UNIT TO FUNCTION, AND FAILURE MAY RESULT IN TERMINATION OF WARRANTY. AVOIDING INSTALLATION IN HIGH HUMIDITY OR DUSTY AREAS AS IT MAY CAUSE MALFUNCTION OF UNIT. MANUFACTURER IS NOT RESPONSIBLE HEREOF. WARRANTY IS NOT TRANSFERABLE, THIS WARRANTY IS NOT ASSIGNABLE AND APPLIES ONLY IN FAVOR OF THE ORIGINAL PURCHASER/USER TO WHOM DELIVERED. ANY SUCH ASSIGNMENT OR TRANSFER SHALL VOID THE WARRANTIES HEREIN AND SHALL VOID ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR LABOR COVERAGE FOR COMPONENT FAILURE OR OTHER THE WARRANTY PACKET PROVIDED WITH THE UNIT. SABA WILL NOT BE HELD RESPONSIBLE FOR THE FOLLOWING EXTERNAL FACTORS: ALTERATION, NEGLIGENCE, ABUSE, MISUSE, ACCIDENT, DAMAGE DURING TRANSIT OR INSTALLATION, FIRE, FLOOD, ACTS OF GOD, OR IMPROPER ELECTRICAL CONNECTIONS. SABA IS NOT RESPONSIBLE FOR THE REPAIR OR REPLACEMENT OF FAULTY OR DAMAGED COMPONENTS RESULTING FROM ELECTRICAL POWER FAILURE, THE USE OF EXTENSION CORDS, LOW VOLTAGE, OR VOLTAGE DROPS TO THE UNIT. NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE; THE FOREGOING WARRANTIES ARE EXCLUSIVE AND EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED, IMPLIED OR STATUTORY. THERE ARE NO WARRANTIES, WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. Warranty information card must be submitted via post mail or electronically on our website at [www.sabacorpusa.com/registration](http://www.sabacorpusa.com/registration) within 30 days from the purchase date. Failure to comply may result in your warranty being voided. All coverage provided within this warranty is applicable only to the United States, excluding Alaska and Hawaii, and Canada, excluding U.S. Territories. Saba is not responsible for any warranty claims made on products sold or used outside the forty-eight states of the United States nor for Canada.

Please e-mail all of this information to: [info@sabacorpusa.com](mailto:info@sabacorpusa.com)  
or fill out the form online at <http://Sabacorpusa.com/warranty-form>

## Warranty Form

This form must be returned within sixty (60) days of the purchase date to  
receive registered warranty service terms

Product / Model \_\_\_\_\_

Serial number \_\_\_\_\_

Invoice / receipt no. \_\_\_\_\_

Date of purchase \_\_\_\_\_

Purchased from \_\_\_\_\_

Your name \_\_\_\_\_

Business name \_\_\_\_\_

Address \_\_\_\_\_

\_\_\_\_\_

Your e-mail \_\_\_\_\_

## **SABA also carries cooking equipment**



### **Saba Headquarters**

3390 Enterprise Avenue  
Hayward, CA 94545-3328  
Toll Free: (844) 422-8900  
Office: (510) 293-0189  
Fax: (510) 293-0199  
Email: [info@sabacorpusa.com](mailto:info@sabacorpusa.com)  
Website: [www.sabacorpusa.com](http://www.sabacorpusa.com)

### **Saba Florida**

4740 E Lakeland Commerce Parkway #1  
Lakeland, FL 33805-7647  
Office: (863) 333-4444  
Fax: (863) 333-4443  
Email: [FL@sabacorpusa.com](mailto:FL@sabacorpusa.com)