



STERO SD1

DOOR-TYPE DISHWASHER



STANDARD FEATURES

- 1.7 gallons per rack
- 37 racks per hour
- Stainless steel construction
- Field adjustable from straight to corner operation
- Door cycle switch controls machine operation
- Filling machine initially, auto fill after first cycle, fill time field adjustable
- Solenoid operated positive seating drain valve – open and closed, no water waste
- Chemical pumps included
- Interchangeable upper and lower wash arms
- 1 H.P. pump motor
- Self-flushing stainless steel pump strainer, large scrap accumulator

MACHINE RATINGS	SD1
	Chemical Sanitizing
Racks per Hour <i>(Maximum)</i>	37
Wash Motor H.P.	1
Rinse Cycle – <i>Gallons per Rack</i>	1.7 Gallon/Rack
Incoming Water Temperature <i>(Recommended Minimum)</i>	140°F
Required Minimum Final Rinse Temperature	120°F

ELECTRICAL CONNECTION MOTORS AND ELECTRIC TANK HEAT			
ELECTRIC SPECS.	RATED AMPS	MINIMUM SUPPLY CIRCUIT CONDUCTOR AMPACITY	MAXIMUM OVERCURRENT PROTECTIVE DEVICE
120/60/1	14.0	20	20

MACHINE WEIGHT		
MODEL	NET WEIGHT	SHIPPING WEIGHT
SD1	210 lbs.	235 lbs.

OVERALL DIMENSIONS: 69"H x 29"W x 32-1/2"D

ST50402 (11/14)