SANDWICH UNIT REFRIGERATOR

Model: SW36N10-FB

Natural Refrigerant R-290 Model

36" Standard Top Sandwich Unit Refrigerator with Solid Door - 10 Pans Front Breathing

Stainless steel front, top and end panels, aluminum back and interior.



Options and Accessories

(upcharge and lead times may apply)

Stainless steel interior	Crumb catcher
Stainless steel back	Rear-mounted cutting board
Overshelves (single or double)	Composite cutting board
Add'l epoxy-coated steel shelves	Flat insulated night cover
Stainless steel shelves	Vision panel lid
Door locks	Modified pan openings

Consult factory for other model configurations, options and accessories.



Standard Model Features

REFRIGERATION SYSTEM

Performance-rated refrigeration system

Natural, environmentally-safe, high-efficiency R-290 refrigerant¹

Unique air flow distribution allows pan product to maintain 33° - 41°F

Automatic, hot gas condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, back mounted compressor

CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation
Smooth, polished chrome door handles
Spring loaded, self closing doors
Magnetic snap-in door gaskets
Heavy-duty, epoxy-coated steel shelves
12" deep, full length nylon cutting board
Insulated lid
Completely enclosed, vented and removable case back
3 3/4" casters

MODEL FEATURES

(10) 1/6 size recessed pans, 4" deep
Removable interior tub below pans
Electronic controller w/digital display & hi-low alarm
Field rehingeable doors

¹ R-290 refrigerant meets all federal and state regulatory requirements.

Front breathers are a unique, field assembled, bottom mounted ventilation system designed to allow cabinets to be flush against a wall or built into a counter to conserve space. For proper operation, the area under and in front of the cabinet <u>must</u> not be obstructed in any way.



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

APPROVAL:

Model Specifications

10.3 (292 cu l)

DIMENSIONAL DATA
Net Capacity (cu. ft.)

(incl. handles & bumpers)

No. of Doors

	•
1/6 Size Pans (4" deep)	10
Width Overall (in)	36 (914 mi

 Width, Overall (in.)
 36 (914 mm)

 Depth, Overall (in.)
 32 3/16 (818 mm)

Depth, Cutting Board (in.) 12 (305 mm)

Height, Overall (in.) (incl. 3 3/4" casters) 41 (1041 mm)

 Shelf Area (sq. ft.)
 4.6 (.4 sq m)

 No. of Shelves
 2

 Interior Depth (in.)
 19 3/8 (492 mm)

 Interior Height (in.)
 26 1/4 (667 mm)

2

Interior Width (in.) 32 (813 mm)

REFRIGERANT DATA

Condensing Unit Size (H.P.)	1/5	
Capacity (BTU/Hr)*	1625	

ELECTRICAL DATA

Voltage (int'l)	115/60/1 (220/50/1)
Total Amps (int'l)	2.46 (1.85)
10 ft. Cord/Plug [attached] (int'l)	Yes (No)

SHIPPING DATA

Weight (lbs.)	254 (115 kg)
Height - Crated (in.)	43 1/4 (1099 mm)
Width - Crated (in.)	44 (1118 mm)
Depth - Crated (in.)	37 1/4 (946 mm)

^{*} Rating @ +25°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug (varies by country)

ntinantal

Refrigerator

Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.







© Copyright 2019. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

Model Plan Views





