GALILEO 350 EVO TOP - 14"

Full-size, Heavy-duty Deli / Supermarket slicer



The EVOlution continues with Galileo 350 EVO TOP 14" full-size capacity, heavy duty slicer designed for high-volume retail applications, setting the highest standards in the industry for:

- One-piece sanitary polished and anodized aluminum construction
- Longest carriage travel for the widest cut capacity
- Low-profile, ergonomic design with an extremely smooth carriage motion
- ½ Hp heavy-duty motor for continuous service and higher torque for cheese slicing
- Stainless steel controls, IP67 dustproof and waterproof rating
- Dual stage cam system allows precise, thin and thick slicing
- Complete stainless steel drive shaft assembly
- Built-in sharpener for perfect results and safety - unlike remote devices
- Waterproof from above
- All metal knobs, handles and dials, minimized use of plastic
- Rounded, edgeless design
- Increased gap between blade and machine body
- One-piece carriage with seamless, see-through hand guard
- Improved blade guard removal system
- Zero blade exposure to prevent injuries when cleaning
- Removable carriage with zero blade exposure
- Permanent blade rim guard covering the non-slicing portion of the blade edge
- Lift lever to easily and safely clean under the slicer (factory installed)
- Overload protection
- No volt release

Operation:	Gravity feed.
Construction:	Polished, anodized aluminum alloy.
Knife:	One piece, chromium plated 100Cr6 forged carbon steel blade.
Sharpener:	Built-in, removable, two stone dual action.

Slice thickness:	0-1" (0-24 mm), infinitely variable
Motor:	0.55 Hp (410 W), fan cooled.
Electrical:	110-120V AC, 60Hz, 4.5A.
Plug & Cord:	Attached, flexible, 3 wire SJTO AWG 18, 6'4" long. NEMA 5-15 P
Controls:	ON/OFF stainless steel keypad, IP 67 waterproof protection. No voltage release.

Certified to UL Standard 763
and NSF Standard 08



Improved blade guard removal system




Completely sealed stainless steel shaft



IP67 controls



One-piece carriage with seamless,
see-through hand guard




Increased gap between blade
and machine body





Dual stage cam system allows precise,
thin and thick slicing



Lift lever







	Ø Blade	Motor	Cut thickness	Blade rpm	Carriage stroke	Hopper	A	B	C	D	E	F	G	X	Y	H	W	Net weight	Shipping	Gross weight
	mm/inch	*watt/Hp*	*inch.*	*rpm*	*inch.*	*inch.*	*inch.*	*inch.*	*inch.*	*inch.*	*inch.*	*inch.*	*inch.*	*inch.*	*inch.*	*inch.*	*inch.*	*lbs.*	*inch.*	*lbs.*
Galileo 350 EVO TOP	350/14″	410-0.55	1″	319	$14^{3/8}$″	$13^{25/32}$″ x $12^{9/32}$″	$20^{9/32}$″	$16^{5/32}$″	$28^{3/4}$″	$29^{9/64}$″	$20^{31/64}$″	$31^{57/64}$″	$22^{3/64}$″	$11^{1/2}$″	$7^{31/64}$″	$11^{39/64}$″	$9^{27/32}$″	132	34″ x 33″ x 33″	168