

Standard Features

- 7.5kW high efficiency heating elements
- Available in standard depth
- Double deck TruVection height is 47-1/2" (51" with flue)
- Triple deck TruVection height is 70" (72-1/2" with flue)
- Stainless steel front, sides and top
- Dependent glass doors (Full 180° opening)
- Energy saving high efficiency glass windows
- Heat keeping dual door seal system
- Coved, porcelain interior
- Stay cool heavy duty door handle
- Two speed, 1/2 hp, fan motor
- 5-position rack guides and 3 plated oven racks
- Solid state temperature controls
- Forced cool down fan mode
- Oven "heat" light cycles with burners
- Interior oven lights

Available Control

SC-Standard Controls

150°F to 550°F solid state thermostat and 60 minute mechanical cook timer.

TVES/20SC - double deck TruVection
TVES/30SC - triple deck TruVection



TVES/20SC shown with
optional casters



TVES/30SC shown with
optional casters

STANDARD CONSTRUCTION SPECIFICATIONS

Exterior Finish: Stainless steel front, sides and top.

Doors: Dependent doors with windows. Low emission glass, stainless steel construction, heavy-duty welded steel frame and 5/8" diameter full-length hinge pin.

Oven Interior: Porcelain enamel finish, coved, fastener free.

Rack and Rack Guides: Heavy-duty removable wire rack guides spaced on 1-5/8" centers offer 5 different rack positions. Three wire racks provided with each oven.

Blower Fan and Motor: 1/2hp, 2-speed motor, 1710/1120 r.p.m

Oven Heating: Oven heating is regulated by an adjustable thermostat control. Blower fan circulates air within the cavity "scrubbing" heat to the oven interior for even heat distribution within the cavity.

Note: Oven cannot be operated without fan in operation.

Control Panel: Located on front, at right side of oven, away from heat zone. Removable panel pulls out for easy servicing.

Interior Lights: Two 40 watt high temperature recessed lamps located within the oven cavity.


Legs: 6" stainless steel legs standard.

Electrical System: Terminal connections are located below oven section and are accessible from the front of the oven. These sheath type electrical heating elements located at the rear of the oven function as a single heating unit with a combined rating of 7.5 kW. Available voltages include 208, 240, 380, and 480 VAC single or three phase, 50/60 Hz. Ovens equipped with 480VAC single or three phase heating elements use 240V controls and motors and do not require separate electrical lead wires.



Models: ☐ TVES/20SC ☐ TVES/30SC

Dimensions -in (mm)



MODEL	OVEN INTERIOR (PER DECK)			RACK CLEARANCE		SHIPPING CRATE				
	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	WIDTH	DEPTH	HEIGHT	VOLUME	WEIGHT
TVES/20SC	29" (737)	21.5" (546)	14" (356)	28.25" (718)	21.00" (533)	57.50" (1461)	45.50" (1156)	81.50" (2070)	123.4 cu. ft. (3.49 cu. m.)	600 lbs (272.2kg)
TVES/30SC	29" (737)	21.5" (546)	14" (356)	28.25" (718)	21" (533)	57.50" (1461)	45.50" (1156)	81.50" (2070)	123. cu. ft. (3.49 cu. m.)	900 lbs (408.2kg)

UTILITY INFORMATION

Standard: 1/2 horsepower, 2 speed motor, 1710/1120 r. p. m.

PER OVEN CAVITY			
ELECTRICAL DATA		AMPS*	
EACH OVEN	VOLTAGE	1 PHASE	3 PHASE
7.5 kW Heating Elements*	208 VAC, 60Hz	36.1	20.8
	220/240 VAC, 50Hz	34.1	19.7
	240 VAC, 60Hz	31.3	18.0
	380/220 VAC, 50Hz	20.0	11.4
	415/240 VAC, 50Hz	18.1	10.4
	480 VAC, 60Hz	16.0	9.0

* Phase shipped per order. Add an additional 4 amps for the control panel.

MISCELLANEOUS

- Clearances from combustibles: Top, bottom, right, left side -0".
- Recommend- Install under vented hood
- Check local codes for fire and sanitary regulations.

Notice: Southbend reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions, or replacements for previously purchased equipment.

OPTIONS AND ACCESSORIES

- ☐ List the voltage, frequency, and amps required (see utility information above).
- ____ VAC, ____ Phase, ____ Hz.
- ☐ Casters 4" or 6"

- ☐ Marine edge top
- ☐ Swivel Caster - front with locks
- ☐ Export crating
- ☐ Stainless steel dirt tray

**INTENDED FOR COMMERCIAL USE ONLY.
NOT FOR HOUSEHOLD USE.**



1100 Old Honeycutt Road, Fuquay-Varina, NC 27526
(919) 762-1000 www.southbendnc.com