

Pivot Head

- ✓ Premium 18/10 brushed stainless steel
- ✓ Solid positioning, pivoting head design

Single 2791-5

250 W | 110-120 V | 2.1 amps | 60 Hz
NEMA 5-15P
14.6 lbs
8.0"W x 10.5"D base, (16.7"D
from back of base to
farthest edge of shade)
x 25.6"H (with shade parallel
to base)
ETL. UL | 5.5 ft. cord



2791-5-220 
250 W | 220-240 V | 1.0 amps | 50-60 Hz
CEE-7/7 16A Schuko Plug
(BS 1363 (13A) U.K. Plug also available)

Double 2792-5

500 W | 110-120 V | 4.2 amps
60 Hz
NEMA 5-15P
22.8 lbs
8.0"W x 10.5"D base, (15.7"D
from back of base to farthest edge
of shade) x 25.6"H (with shade
parallel to base)
ETL. UL | 5.5 ft. cord



2792-5-220 
500 W | 220-240 V | 2.1 amps | 50-60 Hz
CEE-7/7 16A Schuko Plug
(BS 1363 (13A) U.K. Plug also available)

Adjustable Height, Pivot Head

- ✓ Knurled knob smoothly, but firmly adjusts height 22-26"
- ✓ Outlet in base

NEW!

Special Order

Copper 2791-6C

250 W | 110-120 V | 2.1 amps | 60 Hz
NEMA 5-15P
14.6 lbs
8.0"W x 17.0"D x 22- 26.0"H
ETL. UL | 5.5 ft. cord



DAISY CHAIN 6 UNITS
ON A 15 AMP CIRCUIT

NEW!

Special Order

Onyx 2791-6B

250 W | 110-120 V | 2.1 amps | 60 Hz
NEMA 5-15P
14.6 lbs
8.0"W x 17.0"D x 22- 26.0"H
ETL. UL | 5.5 ft. cord



DAISY CHAIN 6 UNITS
ON A 15 AMP CIRCUIT