

INDUCTION & FROST TOP TABLES

Hidden or Exposed Frost Tops

Chill items without the mess of ice

- ✓ Request a remote compressor to minimize noise
- ✓ Works with a variety of stone or porcelain materials
- ✓ Custom sizes available
- ✓ Surface temperature of hidden: 0 to 30°F (-18 to -1°C) Exposed: 0 to 20°F (-18 to -7°C)



Hidden Frost Tops

SS-FT-2422

24.0"W x 22.0"D
115 V | 3 amps

SS-FT-3622

36.0"W x 22.0"D
115 V | 10.3 amps

SS-FT-4822

48.0"W x 22.0"D
115 V | 14 amps

SS-FT-6022

60.0"W x 22.0"D
115 V | 14.8 amps

SS-FT-7222

72.0"W x 22.0"D
208 V | 7.2 amps

Exposed Frost Tops

RT-FT-2026

19.5"W x 25.25"D
120 V | 3.5 amps

RT-FT-2040

19.5"W x 39"D
120 V | 6.2 amps

RT-FT-2053

19.5"W x 53.13"D
120 V | 6.4 amps

RT-FT-2066

19.5"W x 66.5"D
120 V | 6.4 amps

RT-FT-2080

19.5"W x 80.25"D
120 V | 7 amps

Down Draft Air Filtration System for Exposed Cooking Ranges See page 11

- ✓ Captures 96.7% of grease-laden vapor, odor and particulates caused from cooking
- ✓ 3-part filtration system runs quiet
- ✓ UL 197 Certified and UL-Sanitation to ANSI/NSF No.2



AF-350

350 W | 110-120 V | 2.9 amps | 60 Hz
NEMA 5-15P

AF9876

Trim Piece

AF9879

Galvanized Baffle
Pre Filter

AF98710

High Efficiency
Primary Cell Filter

AF98711

Carbon Absorption
Final Filter

AF-350-3

350 W | 220-240 V | 1.5 amps | 50-60 Hz
CEE 7/7 Schuko Plug OR BS 1363 (13A) U.K. Plug