

INDUCTION RANGES

Custom Induction Range Cases

Complement your décor with custom housing for Spring USA warming or cooking ranges. Choose an item number below, then select finishes from pages 18-19. Protective storage cases available.



Single Range Custom Cases

Hidden Hold Only 650 Watt Range w/Custom Case **SRC-651SS**

650 W | 110-120 V | 5.4 amps | 60 Hz
4 Settings | 145-185°F/62-85°C
NEMA 5-15P
14.125"W x 20.125"D x 6.0"H
FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197
7 ft. cord

Cook & Hold 1800 Watt Range w/Custom Case **SRC-181SS**

1800 W | 110-120 V | 15 amps | 60 Hz
20 Settings | 110-400°F/43-204°C
NEMA 5-15P
14.125"W x 20.125"D x 6.0"H
FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197
7 ft. cord

Cook & Hold 2600 Watt Range w/Custom Case **SRC-261SS**

2600 W | 208-240 V | 10.8 amps | 60 Hz
20 Settings | 110-400°F/43-204°C
NEMA 6-20P
14.125"W x 20.125"D x 6.0"H
FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197
7 ft. cord

Double Range Custom Cases

Two Hidden Hold Only 650 Watt Double Ranges w/Custom Case **SRC-2-651SS**

650x2 W | 110-120 V | 5.4 x 2 amps | 60 Hz
4 Settings | 145-185°F/62-85°C
NEMA 5-15P
33.5"W x 20.125"D x 6.0"H
FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197
7 ft. cord

Two Cook & Hold 1800 Watt Double Ranges w/Custom Case **SRC-2-181SS**

1800x2 W | 110-120 V | 15 x 2 amps | 60 Hz
20 Settings | 110-400°F/43-204°C
NEMA 5-15P
33.5"W x 20.125"D x 6.0"H
FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197
7 ft. cord

Two Cook & Hold 2600 Watt Double Ranges w/ Custom Case **SRC-2-261SS**

2600x2 W | 208-240 V | 10.8 x 2 amps | 60 Hz
20 Settings | 110-400°F/43-204°C
NEMA 6-20P
33.5"W x 20.125"D x 6.0"H
FCC, ETL, ETL-Sanitation to NSF-4, CETL, UL 197
7 ft. cord