

ACR51WNSF456



34" x 23.5" x 21.88" (H x W x D)

Built-In healthcare all-refrigerator certified to NSF/ANSI 456 with self-closing glass door, front lock, digital controls, and NIST calibrated temperature readout

Highlights:


Certified to NSF/ANSI 456 Vaccine Storage Standard

Specially designed to meet current CDC/VFC vaccine refrigeration guidelines for convenient storage in pharmacies, medical offices, and other healthcare facilities

Designed and constructed for reliable cold storage in healthcare facilities

Product Features:

EQTemp Healthcare Refrigerator	All-refrigerator designed to operate between 2 and 8°C for a variety of storage application in medical offices and other healthcare facilities	
Certified to NSF/ANSI 456 Vaccine Storage Standard	Tested to comply with the latest standards	
Certificate of calibration included	The temperature monitoring device (TMD) is calibrated to NIST standards in our ISO/IEC 17025:2017 certified calibration laboratory and ships with a 2-year certificate of calibration for your records	
Temperature Range: 2º to 8ºC	Preset to 5°C as recommended for many storage applications	
External temperature readout	Includes continuous display of the current interior and high/low temperature, and can be switched from Celsius to Fahrenheit at the touch of a button	
Digital thermostat	Digital microprocessor for easy and precise temperature management, with all controls externally located for added convenience	
Built-In capable	Front-breathing design lets you make the best use of space by installing your appliance under the counter	
High/low temperature alarm	Audible alarm sounds if the interior temperature rises or falls out of set range	





ACR51WNSF456 Specifications:

Overview	
Height of Cabinet	34.0" (86 cm)
Width	23.5" (60 cm)
Width with Door Open	23.75" (60 cm)
Depth	21.88" (56 cm)
Depth with door at 90°	43.63" (111 cm)
Capacity	3.88 cu.ft. (110 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S to NSF 456
Amps	2.0
Voltage/Frequency	115 V AC/60 Hz
Weight	81.6 lbs. (37 kg)
Shipping Weight	117.0 lbs. (53 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101083087
Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Wire
Shelf Qty	3
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	1.23oz.
High Side PSI	1.45
Low Side PSI	0.8
Level Legs Qty	2
Interior Light	Yes
Temperature Range	2º to 8ºC
Dimensions	
Interior Height	25.88" (66 cm)
Interior Width	18.75" (48 cm)

Interior Depth	16.5" (42 cm)
Compressor Step Height	4.0" (10 cm)
Compressor Step Width	18.75" (48 cm)
Compressor Step Depth	11.5" (29 cm)

