FF31L7FRTPC



26.13" x 17" x 22.38" (H x W x D)

Compact commercially approved front tap cold brew coffee dispenser in a classic white finish

Highlights:

Designed to serve cold brew coffee on tap

Compact kegerator with front tap for easy and accessible dispensing

ETL-S listed to ANSI-NSF Standard 7 for commercial use

Product Features:

Compact Cold Brew Coffee Dispenser	Kegerator features a pre-installed front tap accessed via the door, with all of the equipment needed to serve coffee from a 2.5 gallon keg
Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for commercial use
Complete cold brew coffee tap kit included	Includes a nitrogen tank and regulator, tap draft arm, Sankey American tap, and the needed connection hardware
Commercial-grade equipment	The included tapping equipment is constructed from commercial-grade materials for added durability
2.5 gallon mini keg included	Model is packaged with a refillable 2.5 gallon mini keg for easy service
Stainless steel drip tray	Removable two-piece drip tray included for added convenience
Accessible tap	Cold brew coffee tap is located on the front of the door, requiring no added reach
Lightweight design	Specifically designed for easier portability, opening up where unit can be placed
Factory-installed lock	Keyed lock allows you to secure the interior as needed, with a set of two keys included

FF31L7FRTPC Specifications:

Overview	
Height of Cabinet	26.13" (66 cm)
Width	17.0" (43 cm)
Width with Door Open	17.75" (45 cm)
Depth	22.38" (57 cm)
Depth with door at 90°	34.75" (88 cm)
Capacity	2.5 cu.ft. (71 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	1.3
Voltage/Frequency	115 V AC/60 Hz
Weight	45.0 lbs. (20 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101158952
Kegerator	
Door Swing	RHD
Reversible	No
Tap Kit	Yes
Number of Taps	1
Adjustable Shelves	Yes
Shelf Type	Chrome
Shelf Qty	4
Thermostat Type	Digital
Interior Light	Yes
Refrigerant	R600a
Refrigerant Amount	0.06 oz.
High Side PSI	270.0
Low Side PSI	103.0
Inter Height	21.25" (54 cm)
Interior Width	13.5" (34 cm)
Interior Depth	14.75" (37 cm)
Compressor Step Height	7.5" (19 cm)
Compressor Step Width	13.5" (34 cm)
Compressor Step Depth	5.0" (13 cm)

Temperature Range	34°F to 43°F
Sound Level	34 dB



SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified
770 Garrison Avenue Bronx, NY 10474 USA **TEL** 718-893-3900 **FAX** 844-478-8799 info@summitappliance.com **www.summitappliance.com**